[INCH-POUND]
A-A-3033
October 29, 1996
SUPERSEDING
GG-I-271C
February 20, 1964

COMMERCIAL ITEM DESCRIPTION

IGNITER, FRICTION, OXYACETYLENE-TORCH

The General Services Administration has authorized the use of this Commercial Item Description for procurement of type I, style A igniter specified in GG-I-271C for all federal agencies.

1. SCOPE.

1.1 Scope. This Commercial Item Description covers hand-operated igniters (spark igniters)

1.2 Intended purpose. The igniter is used for igniting gas welded and cutting torches.

2. CLASSIFICATION.

2.1 Classification. Not applicable.

3. SALIENT CHARACTERISTICS.

3.1 Design. Igniters shall be of a wire frame, single flint, round file, hooded design consistent with the best commercial practices and shall be so constructed that the parts will not become detached during normal use. A means shall be provided to prevent the flint from striking the hood or frame at either end of the file. The igniter shall be similar to Figure 1.




Figure 1. Igniter, wire frame, single flint, round file, hooded.

3.1.1 Frame. The frame shall be of spring-tempered wire having a minimum diameter of 1/8 inch. The end of the movable arm shall have at least 5 and no more than 7 threads, size number 6-40 NF, Class 2 fit. The threaded end shall be bent so that with normal hand pressure the flint end of the movable arm will travel perpendicular to the file lengthwise and return when released.

3.1.2 Flint. The flints shall be of a pyrophoric alloy substance of adequate strength to withstand severe frictional movement across the file surface without chipping or breaking. The flints shall have a nominal diameter of 1/8 or 5/32 inch, and the frictional movement across the file shall produce a spark of sufficient intensity to ignite the gases

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center, Kansas City, MO 64131.

Distribution Statement A. Approved for public release; distribution is unlimited.

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the current version before use.

used in welding and cutting torches. The flint shall be capable of producing a minimum of 1500 ignitions. The flints shall be covered with a high grade waterproof paint, or otherwise properly treated to minimize deterioration in storage.

3.1.3 Flint holder. The flint holder shall be similar to a metal sleeve with approximate dimensions of a 3/16 inch outside diameter, 9/32 inch length, and a knurled section 1/8 inch in length. One end of the holder shall have a minimum of 5 internal threads, size 6-40 NF Class 2 fit.

3.1.4 File. The file shall be of steel, heat treated to show a minimum hardness of 64 on the Rockwell C scale, or case hardened to show a minimum hardness of 78 on the Rockwell 30N scale (superficial) when tested in accordance with ASTM E18. The file shall be approximately 1 inch long, round in shape, and be capable of rotating on the fixed arm of the frame.

3.1.5 Hood. The hood shall be of a suitable metal, securely attached to the fixed arm of the frame, and partially surround the file without interfering with the normal operation of the movable arm.

3.1.6 Spring compression load. The igniter shall have the fixed arm of the frame clamped in a horizontal position with the movable arm directly above. A 3-pound weight shall be attached to the movable arm 1-1/2 inches from the flint end. The movable arm shall not compress to the end of its normal travel. The 3-pound weight shall then be removed and the 6-pound weight shall be attached to the movable arm 1-1/2 inches from the flint end. The movable arm shall compress to the end of its normal travel.

3.2 Identification marking. The igniter shall be marked with the manufacturer's name or identifying symbol and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item. Markings are not required on the replacement flint.

3.3 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Paints, coatings, platings, and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g., sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g., pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The product provided to the Government shall conform to the contractually specified requirements. For product characteristics and requirements which are not contractually specified, the provided product shall conform to the producer's own drawings, standards, specifications, and quality assurance practices for the highest quality product commercially offered by the producer. If the product is not commercially offered by the producer, the best commercial practices shall apply. The Government reserves the right to require proof of such conformances prior to first delivery and thereafter as provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the current version before use.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample(s) shall be inspected for all salient characteristics by the Government. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

6. PACKAGING.

6.1 Packaging. Requirements of preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

7. NOTES.

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents:

Federal Specifications and Standards: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC 20407.

Federal Acquisition Regulations (FAR): Government Printing Office, Superintendent of Documents, Washington, DC 20402-9371.

ANSI/ASQC Z1.4: American Society for Quality Control, P.O. Box 3005, 611 East Wisconsin Avenue, Milwaukee, WI 43201-4606.

ASTM E18: American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description.
(b) When applicable, the appropriate NSN(s).
(c) If bid samples are required, the number of samples required, and the subjective inspection requirements.
(d) If first article samples are required and the number of samples required.
(e) If lot sampling inspection is required and the applicable lot sampling requirements. For example:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Inspection. Each sample tool shall be examined and tested for all salient characteristics. The Inspection Level shall be S-2 with an Acceptable Quality Level of 4.0, expressed in terms of defects per hundred units.

(f) What preservation, packing, packaging, and marking of packages are required.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the current version before use.

7.3 National Stock Numbers (NSNs). The following NSNs are associated with this Commercial Item Description. This list may not be indicative of all possible NSNs associated with this CID.

NSN	
5120-00-965-0326	
5120-00-965-0603	Replacement flint tip

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions or notices to this Commercial Item Description until further notice.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.