[Metric]
A-A-66C
September 26, 1996
Superseding
A-A-66B
January 06, 1994

COMMERCIAL ITEM DESCRIPTION

PUNCH, PAPER, HAND-HELD, OFFICE TYPE

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. Scope: This Commercial Item Description covers hand-held office type paper punchers intended for punching holes in paper. Paper punchers shall be of the following types and sizes.

2. Classification:

Type:
I. - Light duty
II. - Heavy duty

Size:
A. For 3.18 mm (1/8") diameter holes
B. For 3.97 mm (5/32") diameter holes
C. For 4.76 mm (3/16") diameter holes
D. For 6.35 mm (1/4") diameter holes

3. Salient Characteristics:

3.1 Construction.

3.1.1 The puncher shall be a plier-type design activated by squeezing the handles together. The handles shall be curved to fit the hand in accordance with normal commercial practice.

3.1.2 Type I punchers handle shall be knurled. The Type II puncher shall have a depth gauge and clipping receptacle and its handles shall be plastic coated or in accordance with normal commercial practice.

3.1.3 Handles shall be spring loaded so that they return to the open position once compression on the handles is removed. The spring mechanism shall withstand repeated compressions without losing its resilience. The puncher shall be permanently marked with the name or trademark of the manufacturer.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:04Z
Check the source to verify that this is the current version before use.

Table I.
Dimensions: Metric/Inches

Type I.			
Length	**Width**	**Throat Depth/Reach**	**Feed Clearance**
13.34 ± 0.64 cm 5-1/4 ± 1/4 inches	5.72 ± 0.64 cm 2-1/4 ± 1/4 inches	2.54 cm (1 inch)	3.81 ± .157 cm .150 ± .062 inch
Type II.			
Length	**Width**	**Throat Depth/Reach**	**Feed Clearance**
14.6 ± 1.9 cm 5-3/4 ± 3/4 inches	6.40 ± 0.64 cm 2-1/2 ± 3/8 inches	2.54 cm (1 inch)	6.35 ± .317 cm .250 ± .125 inch
Size (Both Types) - Die Diameter			
(A) 3.18 ± 0.40 mm - (1/8 ± 1/64 inches) **(B)** 3.97 ± 0.40 mm - (5/32 ± 1/64 inches) **(C)** 4.76 ± 0.40 mm - (3/16 ± 1/64 inches) **(D)** 6.35 ± 0.40 mm - (1/4 ± 1/64 inches)			

Note: Thickness of the handles shall be in accordance with normal commercial practice for this product.

3.3 Materials. The spring mechanism shall be made of commercially available spring steel, and the handles shall be made of a normally used, for the function of that part, commercially available material. Surface plating shall be either nickel, or a combination of chromium used in conjunction with an electrodeposited underplate system of nickel.

3.4 Performance. Punched holes shall be neither torn nor ragged and the puncher shall not experience any damage or jamming and continue to operate properly after being subjected to the performance testing specified in paragraph 5.3.

3.5 Workmanship. The punch shall be free of any defects that may affect its durability, appearance or cause injury to the end user. All exposed surfaces shall be free of sharp edges, burrs, scales, fins, or nodules.

4. Regulatory Requirements: The offerer/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T08:04Z
Check the source to verify that this is the currentversion before use.

5. Quality Assurance Requirements:

5.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5.2 Performance Testing.

5.2.1 Type I punch shall be made to punch a hole through 5 sheets of 25 percent bond paper with a basis weight of 75 grams per square meter (20 pounds, 17 x 22 - 500).

5.2.2 Type II punch shall be made to punch a hole through 15 sheet of 25 percent bond paper with a basis weight of 75 grams per square meter (20 pounds, 17 x 22 - 500).

6. Packaging:

6.1 Preservation, packing, and marking shall be as specified in the contract or order.

7. Notes:

7.1 Source of Documents. Issues of the following documents, in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

7.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington. DC 20402.

7.2 National Stock Number Listing (NSN's). The following is a list of nsn's assigned which correspond to this CID. The list may not be indicative of all possible nsn's associated with the CID.

7520-00-271-8892
7520-00-286-6988

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:04Z
Check the source to verify that this is the current version before use.