GGG-B-50a
February 8, 1966
SUPERSEDING
Int. Fed. Spec. GGG-B-0050 (GSA-FSS)
November 20, 1963

FEDERAL SPECIFICATION

BAG, LINEMAN'S TOOL, ROUND

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 This specification covers the requirements for one type of tool bag used by line crews for raising and lowering tools and materials.

1.1.1 *Federal specification coverage.* Federal specifications do not include all varieties of the commodity as indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications:

KK-L-156—Leather, Cattlehide, Harness, Vegetable-Tanned.
PPP-B-636—Box, Fiberboard.
PPP-B-665—Boxes; Paperboard, Metal Stayed (Including Stay Material).

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 **Materials.** The materials shall be as specified herein. Materials not specified herein shall be of the quality best suited for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

3.1.1 *Cloth.* The cloth used to fabricate the tool bag, except the inside pocket, shall be not less than number 1 (28.71 ounces per square yard) cotton duck. The cloth used to fabricate the inside pocket shall be not less than number 12 (11.16 ounces per square yard) cotton duck.

3.1.2 *Leather.* Leather shall be full grain in accordance with KK-L-156.

3.1.3 *Thread.* Thread used in sewing shall be heavy cotton and have a minimum breaking strength of 14 pounds.

3.2 **Construction.** The tool bag shall be of sturdy construction so as to withstand hard and rough usage. Construction shall conform to the requirements of this specification and the bag shall be suitably reinforced to withstand the tests specified herein.

3.2.1 *Stitches.* All stitches shall be the lock stitch type, properly formed and evenly spaced with not less than 4 stitches per inch.

3.3 **Design.** The tool bag shall consist of a cloth body with leather bottom, a ring to hold the top open, a rope handle, and an inside pocket.

3.3.1 *Dimensions.* The nominal overall dimensions of the tool bag excluding the handle shall be 16-1/2 inches high and 12 inches in diameter. The tolerance shall be plus or minus 5 percent.

3.4 **Details of components.**

3.4.1 *Body.* The body shall be cloth with leather covered bottom. The sides of the body shall be made from one piece of cloth with one vertical side seam held together with two rows of stitching. The bottom shall consist of hardboard reinforcing material covered on the inside with cloth and covered on the outside with leather. The bottom shall be sewed to the sides. The leather shall extend up the sides a minimum of 2 inches. The top edge of the side shall be folded over the top ring a minimum of two inches and sewed with two rows of stitching. Two leather strips, approximately 2 inches wide and 6 inches long, shall be folded over the top edge of the bag and sewed in place on opposite sides for handle reinforcements.

3.4.2 *Top ring.* The top ring shall be fabricated from nonmetallic material. The ring shall be capable of holding the top open in round form when the tool bag is loaded with 50 pounds and lifted with a rope attached to the handle.

3.4.3 *Handle.* The handle shall be fabricated from approximately 36 inches of 1/2 inch diameter manila rope. Each end of the rope shall be looped around the top ring, through the leather reinforcements, and spliced with a minimum of 3 tucks.

3.4.4 *Inside pocket.* A cloth pocket, at least 8 inches square, shall be sewed on the inside of the tool bag to accommodate small tools, bolts, and similar items.

3.5 **Identification of product.** Tool bags shall be permanently marked in a plain and legible manner with the manufacturer's name or with a trademark of such known character that the source of manufacture may be readily determined.

3.6 **Workmanship.** Workmanship shall be in accordance with high grade industrial practice.

4. QUALITY ASSURANCE PROVISIONS

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

TABLE I. *Sampling data*

Category	Sample unit	Inspection level	Acceptable quality level	AQL expressed in terms of	Reference
Visual examination	1 each	II	6.5	Defects per hundred units	4.3.1
Dimensional examination	1 each	S-4	2.0	Defects per hundred units	4.3.2
Testing	1 each	S-3	1.0	Defects per hundred units	4.4
Preparation for delivery	See 4.5	S-3	1.5	Defects per hundred units	4.5

4.1.1 *Inspection of materials and components.* In accordance with 4.1, the supplier is responsible for insuring that materials and components used were manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.2 **Sampling procedures.** Sampling procedures shall be in accordance with MIL-STD-105. Data for sampling shall be as stated in table I.

4.3 **Examination.**

4.3.1 *Visual examination.* Each sample unit shall be examined for any nonconformance in design, material, finish, coating, construction, workmanship, and marking.

4.3.2 *Dimensional examination.* Each sample unit shall be examined for any nonconformance with dimensional requirements.

4.4 **Testing.** Each sample unit shall be tested in accordance with 4.4.1 and 4.4.2.

4.4.1 *Load test.* Each sample tool bag shall be loaded with 150 pounds of tools, lead shot, or other similar bulk material, and lifted clear of the floor 10 times by a rope attached to the center of the handle. The bag shall be rejected if any damage or distortion results which would affect its serviceability.

4.4.2 *Deformation test.* Each sample tool bag that has passed the load test shall be loaded with 50 pounds of tools, lead shot, or other similar bulk material and suspended by a rope attached to the center of the handle. While suspended with the 50 pound load, the bag shall be examined for excessive sagging of the bottom and closing in at the top. The tool bag shall be rejected if the bottom sags more than 1/4 inch, or if the opening at the top is less than 9-1/2 inches, measured at any point across the inside excluding the thickness of the rope handle.

4.5 **Inspection of preparation for delivery requirements.** An inspection shall be made to determine that the packaging, packing, and marking requirements comply with section 5. Defects shall be scored in accordance with table II. The sample unit shall be one shipping container fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot.

TABLE II. *Classification of preparation for delivery defects*

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, or inadequate stapling. Distortion of container.

5. PREPARATION FOR DELIVERY

(For civil agency procurement, the defini-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

tions and application of levels of packaging and packing shall be in accordance with Fed. Std. No. 102.)

5.1 **Packaging.** Packaging shall be level A, B, or C as specified (see 6.1).

5.1.1 *Level A or B.* Each bag shall be collapsed to a minimum safe cube and packaged in a close-fitting box conforming to PPP-B-636, type CF, class domestic, style RSC or to PPP-B-665, style optional. Each box shall be securely closed to prevent accidental opening.

5.1.2 *Level C.* The bags shall be packaged in accordance with the supplier's commercial practice.

5.2 **Packing.** Packing shall be level A, B, or C as specified (see 6.1).

5.2.1 *Level A.* The bags, packaged as specified in 5.1, shall be packed in close-fitting boxes conforming to PPP-B-636, V3c, style RSC. Each box shall be closed, waterproof sealed with tape and reinforced with bands of filament tape in accordance with the appendix to the box specification.

5.2.2 *Level B.* Sixteen bags, packaged as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-636, type CF, class domestic, style RSC. The box shall be closed and sealed in accordance with the appendix to the box specification.

5.2.3 *Level C.* The bags shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 **Marking.**

5.3.1 *Civil agencies.* In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 *Military activities.* In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 **Ordering data.** Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.

(*b*) Level of packing and packaging required (see 5.1 and 5.2).

(*c*) Any special marking required (see 5.3).

6.2 **Transportation descriptions.** Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Tool bags.
Carload minimum weight 20,000 pounds, subject to Rule 34, Uniform Freight Classification.

Motor:

Bags, tools.
Truckload minimum weight 20,000 pounds, subject to Rule 115, National Motor Freight Classification.

DOD coordination has been waived.
Preparing Activity:—GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.