INTERIM AMENDMENT

FEDERAL SPECIFICATION

HAMMERS, HAND & MALLETS, SURFACE PROTECTIVE; HOLDERS AND

ADAPTERS, INSERTED HAMMER FACE, AND FACES, HAMMER, INSERTED

This Interim Amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20407, based upon currently technical available information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

NOTE: The details of Amendment-5 form a part of this amendment although not reproduced herein. The Specification and Amendment-5 are modified by this Interim Amendment as provided below. Otherwise Federal Specification GGG-H-33a and Amendment-5 remain in effect until publication of the fully coordinated document.

Page 3, paragraph 3.9.3, *fifth sentence*: Delete and substitute the following:

"The grip portion shall be covered with rubber, neoprene, or other comparable material".

Page 3, add as paragraph 3.9.4: "Replacement fiberglass reinforced plastic handle kits.- Replacement kits shall include the following: one (1) fiberglass reinforced handle as specified in 3.9.3, of the type, class, weight, length and eye size specified (see 6.2.1), one (1) ferrule cap, one ferrule collar, sufficient quantity of chemical adhesive bonding cement or other suitable bonding material, one (1) mixing container and stirring stick for bonding material, and one (1) set of instructions".

"3.9.5 Chemical adhesive bond.- Handles secured by chemical adhesive bond or means other than wedging shall be capable of withstanding temperature of minus 30 degrees fahrenheit. When specified (see 6.2 or 6.2.1 as applicable), chemical adhesive bond or means other than wedging shall be capable of withstanding temperature of minus 60 degrees fahrenheit".

Page 9, table X: Delete the note under table and substitute:

"Note.--Tolerance for seat diameters shall be as follows:
Plus 0.000, minus 0.015 for tough and softer grades;
Plus 0.000, minus 0.025 for medium hard and harder grades".

Page 10, table XI, under column B: Change tolerance "$\pm$0.000 $-$ .015" to "$\pm$.015 $-$0.000".

Page 15, paragraph 4.2.2.2, line 6: Delete "L-4" and substitute "S-2."

Page 15, paragraph 4.2.2.5: Delete and substitute:

"4.2.2.5 Pull-apart, striking and temperature test.- Testing shall be performed on each sample hammer (when applicable) for determination of requirements as specified in 4.4.2.6 and 4.4.2.12. Hammers shall be kept at the temperature specified in 3.9.5 for at least five hours and be allowed to return to a temperature of 70 degrees, $\pm$ 10 degrees prior to conducting tests. The inspection level shall be S-2 with an AQL of 2.5 defects per hundred units".

Page 20, paragraph 6.2, option (c): Delete and substitute the following:

"(c) Type of handle required; wood (state whether grade A or AA), fiberglass or steel; except for type II, class 2 (see 3.9)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

Page 20, paragraph 6.2, option (k): Delete and substitute the following:

"(k) If chemical adhesive bond must withstand minus 60 degrees fahrenheit, (see 3.9.5)".

Page 20, after paragraph 6.2: Add the following:

"6.2.1 Replacement fiberglass handle kits.- Procurement document should specify the following:

(A) Type, class, weight, handle length and eye number that replacement handles are for.

(B) Temperature requirements (see 3.9.5 and 6.2 option (k).

(C) Quantity of kits required".

☆ U. S. GOVERNMENT PRINTING OFFICE: 1971-714-156/845

GSA DC 84-15423

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.