# INTERIM AMENDMENT

# TO

# FEDERAL SPECIFICATION

## HAMMER, HAND; WELDERS', CHIPPING

This interim amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, DC 20405, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification GGG-H-35A, dated February 28, 1957.

PAGE 1

Paragraph 2.1, under "Military Specification:" Delete in its entirety and substitute:

"Federal Specification:

PPP-P-40 - Packaging and Packing of Hand Tools."

Paragraph 2.1, under "Military Standard:" Delete in its entirety.

PAGE 2

Paragraph 3.1: At the end of the paragraph add the following: "When applicable, welding symbols shall be disregarded (see 3.3.2)."

Paragraph 3.3.1, last line: After the word "octagonal" add the word "round".

Paragraph 3.3.2: Delete in its entirety and substitute:

"3.3.2 Handles. The handles shall be welded to, or be an integral forged part of, or press fitted and pinned to the hammer head. Unless otherwise specified in the contract or order (see 6.1 and figures 1 to 6, inclusive), handles shall be of one of the following styles at the option of the contractor."

Paragraph 3.3.2.1: Delete in its entirety and substitute:

"3.3.2.1 Style A, flat steel handle. Style A handles shall be of round, mild-steel bar so formed as to present a flat steel handgrip. A substantial washer or ring shall be securely welded to the handle at right angles at a point just above the grip of the handle. Style A handles shall be similar in design, and shall conform to the dimensions of figure 1 (see 3.6.1)."



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:36Z
Check the source to verify that this is the current version before use.

PAGE 3

TABLE I, under column headed "Length of handle grip": Delete "5 inches" and substitute "5 to 5-1/2 inches".

Paragraph 3.3.3, first sentence: At the beginning of the sentence insert "When applicable,".

Paragraph 3.5, at end of last sentence: Add "or be coated as indicated in the immediately preceding sentence."

TABLE II, under column headed "Length B": Delete "6 inches" and substitute "6 to 6-1/2 inches".

TABLE II, under column headed "Width (distance across flats and chipping edge)": Delete "5/8 inch" and substitute "5/8 to 1 inch".

PAGE 4

FIGURE 1, handle length dimensions: Delete "5 ±1/8" and substitute "4-1/8 ±1 inch" and delete "6-1/2 ±1/8" and substitute "5-3/4 ±1 inch".

Insert new paragraph after 3.9:

"3.9.1 Wire brush. When specified (see 6.2), type IV, straight peen and brush hammers shall be supplied with additional brushes conforming to 3.9 and table III."

PAGE 5

TABLE III, under column headed "Thickness ±1/4": Delete "1" inch and substitute "7/8" inch.

TABLE III, under column headed "Over-all length A ±1/4": Delete "10-1/2" inches and substitute "10-1/2 to 11" inches.

PAGES 6 AND 7

Paragraphs 4 through 4.3.2, 4.5, and tables IV, V, and VI: Delete in their entirety and substitute.

"4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated herein.

4.2.1 Inspection of materials and components. In accordance with 4.1 above, the supplier is responsible for insuring that materials and components used were manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

4.2.2 Inspection of the end item.

4.2.2.1 Visual examination. Examination of the hammers shall be in accordance with the classification of defects set forth below. The lot size shall be expressed in units of hammers for the purpose of determining the sample size in accordance with MIL-STD-105. The sample unit for this examination shall be one completely fabricated hammer. The inspection level shall be level II with an Acceptable Quality Level (AQL) of 2.5 for major defects and a total of 6.5, expressed in terms of defects per hundred units.

| Examine | Defect | Classification | |
|---|---|---|---|
| | | Major | Minor |
| Finish | Not as specified. | X | |
| | Hammers not free from burrs, roughness, or excessive oxide scale. | | X |
| | Finish not smooth and even or free from blisters, runs, or imbedded foreign matter. | | X |
| Design | Type, class, or style not as specified. | X | |
| Construction and Workmanship | Hammer (head and handle) not properly assembled, heads not aligned with handles as specified. | X | |
| | Wooden handle has split, knots, or slivers. | X | |
| | Welds unsound, porous, incomplete, cracked, or fractured. | X | |
| | Welds not free from pits, holes, fissures, scale, or splatter. | | X |
| Marking | Marking, manufacturer's name or trademark missing, not permanent, incorrect, illegible, or not as specified. | | X |

4.2.3 Dimensional examination. Inspection shall be made of the hammers for compliance with dimensions specified in applicable paragraphs and tables. Any deviation therefrom shall constitute a defect. The inspection level shall be level II, with an AQL of 2.5 defects, expressed in terms of defects per hundred units.

4.2.4 Testing of end item. Testing shall be performed on each sample unit for characteristics specified in 4.4 through 4.4.3.2, as applicable. The inspection level shall be level S-3 with an AQL of 1.5 defects, expressed in terms of defects per hundred units.

4.2.5 Inspection of preparation for delivery. Inspection shall be made to determine compliance with the requirements of PPP-P-40."



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

PAGE 7

Paragraph 4.4.1: Delete the third sentence and substitute: "The blow shall be struck with sufficient force to produce an indentation."

PAGES 7 AND 8

Delete section 5 in its entirety and substitute:

"5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking shall be in accordance with PPP-P-40. The level of preservation, packaging, and packing shall be level A, B, or C, as specified (see 6.1)."

PAGE 8

Paragraph 6.2: Add "(c-1) If additional brushes are required (see 3.9 and 3.9.1)."

Insert new paragraph after 6.2:

"6.2.1 Replacement brushes. Procurement documents should specify the following:

(a) Type and manufacturer's model that replacement brushes are for.
(b) Quantity or brushes required."



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.