GGG–J–60a
January 11, 1967
SUPERSEDING
Int. Fed. Spec. GGG–J–0060(GSA–FSS)
March 31, 1964

FEDERAL SPECIFICATION

JACK KIT, HYDRAULIC, HAND (WITH TRUCK OR CHEST)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers kits consisting of hydraulic jacks (type I, class 1, styles A and B in accordance with GGG–J–63), with various attachments and accessories for harnessing the ram action for pulling, clamping, and spreading in addition to the pushing action of the hydraulic jacks. It also covers a chest or handtruck for transporting the complete kit.

1.1.1 *Federal specification coverage.* Federal specifications do not include all varieties of the commodity as indicated by the titles of the specifications, but are intended to cover only those which are generally used by the Federal Government.

1.2 Classification. The jack kit covered by this specification shall be of the following sizes as specified (see 6.2):

I—4 ton.
II—10 ton.
III—20 ton.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

GGG–J–63—Jacks, Hydraulic, Hand Operated.

Federal Standard:

Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL–H–15424—Hand Tools, Packaging of.

Military Standard:

MIL–STD–105—Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

invitation for bids or request for proposal shall apply.

National Bureau of Standards (NBS) Handbook:

H28—Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C., 20402.)

3. REQUIREMENTS

3.1 Design and construction. The jack kit shall consist essentially of a hand-operated hydraulic jack (see 3.3), attachments and/or accessories (see 3.4), and a chest or handtruck for transporting the complete kit (see 3.5).

3.1.1 *Castings and forgings.* All castings shall be free from blowholes, porosity, hard spots, shrinkage defects, cracks, or other defects. Forgings shall be free from scale, cold shuts, mismatching and other defects that may affect the structural strength of the forgings involved. Strength and other essential physical and chemical properties of the castings and forgings shall be adequate to meet the performance requirements specified herein.

3.1.2 *Welding, brazing, and soldering.* Welding, brazing, and soldering shall be performed in accordance with good commercial practice. In no event shall such processes, including peening or plugging, be used on castings or forgings for reclaiming any parts of the jack kit without authorization of the procuring activity.

3.1.3 *Fastening devices.* All screws, pins, bolts, and similar parts shall be installed with means for preventing loss of tightness and adjustment. All such parts when subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently deformed.

3.1.4 *Threads.* All threaded parts shall be in the inch system and shall comply with NBS H28. Unified screw threads shall be utilized in lieu of American National screw threads and nonunified American Standard screw threads, except when it is necessary to have a deeper thread to insure full contact or mesh.

3.1.5 *Interchangeability.* All replaceable parts shall be manufactured to definite standards, clearances, and tolerances in order that any such parts of a particular type or model can be replaced or adjusted without requiring modification. Where practicable, all such parts shall be permanently and legibly marked with the manufacturer's part number.

3.2 Handbook of instructions. Unless otherwise specified, the contractor shall furnish two copies of a handbook of instructions with each jack kit supplied under this specification (see 6.2). The handbook shall contain operating instructions, necessary drawings, and parts list. The handbook shall also include attachment parts list and instructions for general use of the attachments. Additional copies of the handbook and the mailing address to which the additional copies are to be sent shall be as specified by the procuring activity (see 6.2).

3.2.1 *Handbook approval.* When specified (see 6.2), a preliminary copy of the instruction handbook shall be submitted to the contracting officer for approval prior to publication and delivery.

3.3 Jacks. The hand-operated hydraulic jacks shall be in accordance with type I, class 1, styles A and B of GGG–J–68, and of 4–, 10–, or 20–ton capacity as specified (see 6.2).

3.4 Attachments or accessories. Each jack kit shall be furnished with attachments or accessories for the purpose of pulling, clamping, and spreading in addition to the pushing action of the hydraulic jack. Each metal accessory or attachment that is subject to a direct push or pull load shall withstand a test load of one-half the rated maximum pressure of the jack. Each flexible head, and each metal accessory subject to an indirect push shall withstand a test load of 1600 pounds for the 4-ton jack; 2 tons for the 10-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

ton jack; and 4 tons for the 20-ton jack. All attachments and accessories shall be made of material suitable for the purpose intended, and shall be furnished for the respective sizes as specified in tables I, II, and III.

Table I. *Attachments for 4-ton jack kit*

1 – 4-ton jack.
1 – Short connector which screws into the ram of the jack.
6 – Steel extension tubes – one each of the following:
  1 – 3-inch tube.
  1 – 5-inch tube.
  1 – 15-inch tube,
  and the remaining three tubes shall provide a total length of 47 inches (none of these to be less than 6 nor more than 23 inches in length). The total length of all six tubes shall be not less than 70 inches.
3 – Couplings or connectors for the extension tubes.
1 – Chain pull plate.
2 – Five-foot minimum length chains (1/4-inch minimum diameter) each furnished with hook.
1 – Flat base.
1 – Flexible (rubber) head, 3 inches nominal diameter, with a tolerance of plus 3/8, minus 1/4 inch.
1 – V-base, 90° nominal.
1 – Serrated or grooved saddle which screws onto the plunger.
1 – Plunger toe.
4 – Lockpins.
2 – Male adaptors.
1 – Female adaptor.
1 – Slip lock extension.
1 – Offset head.
1 – Spreader head.
1 – Wedge.
1 – Ram toe.
1 – Body toe.
  Additional accessories to be furnished when specified (see 6.2):
1 – Adjustable body spoon.
1 – 90° concave head.
1 – "V" head.

Table II. *Attachments for 10-ton jack kit*

1 – 10-ton jack.
1 – Short connector which screws into the ram of the jack.
  Steel extension tubes, one each of the following nominal lengths: 19, 11, and 5 inches, each with a tolerance of plus or minus 1–1/4 inches; and the remaining tube(s) shall provide a total length of at least 15 inches (total length of all tubes to be 50 inches minimum).
2 – Couplings or connectors for the extension tubes.
1 – Chain pull plate.
2 – Six-foot minimum length chains (5/16-inch minimum diameter) each furnished with a hook.
1 – Adjustable body spoon.
1 – Flat base with at least 13-1/2 square-inch base surface area.
1 – Flexible head, 3 inches nominal diameter, with a tolerance of plus 3/8, minus 1/4 inch.
1 – Flexible head, 4-1/2 inches nominal diameter, with a tolerance of plus 3/4 or minus 1/2 inch.
1 – V-base, 90° nominal.
1 – Serrated or grooved saddle, which screws onto the plunger.
1 – Clamp head.
1 – Clamp end toe.
1 – Plunger toe.
2 – Pins for clamp toe.
1 – Ram toe.
1 – Spreader toe.
1 – Slip lock extension with 7 inches minimum adjustment. The slip lock extension shall have a 5-ton minimum capacity.

Table III. *Attachments for 20-ton jack kits*

1 – 20-ton jack.
2 – Couplings, female threaded, from ram to extension.
  Steel extension tubes of the following lengths:
  1 – 10– to 12-inch tube.
  1 – 18– to 20-inch tube.
  1 – 24– to 30-inch tube,
  and the remaining tube(s) shall provide a total length of 60 inches minimum.
2 – Eight-foot minimum length chains (3/8-inch diameter) each furnished with grabhook.
1 – Base plate threaded to fit ram cylinder end opposite the plunger end, and the ram cylinder extensions.
1 – Serrated or grooved saddle to fit threaded end of ram.
1 – Toe lift threaded to fit ram cylinder.
1 – Plate pull – large attachment plate for use with ram and chain, threaded to fit ram cylinder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

3.5 Truck or chest. Jack kits shall be furnished with either a four-wheeled hand-truck or a chest as specified (see 6.2).

3.5.1 *Truck.* The truck shall provide for either a suitable mounting or storage space for the jack and all attachments or accessories. The truck shall be made of not less than 16 gage (0.0598 inch nominal thickness, with commercial tolerances allowed) sheet steel. The truck shall be equipped with either four swiveling, ball-bearing casters, or two nonswiveling casters and two swiveling casters having ball-bearing swivels. The four caster wheels shall be of rubber composition or similar material. Each caster wheel shall be not less than 2–7/8 inches in outside diameter and not less than 3/4 inch in tread width. The overall height of the truck (including wheels), shall be at least 29 inches. The truck shall have a bottom, two ends, and at least two shelves. The truck shall be capable of holding the complete kit without any of the components falling off when tested as specified in 4.4.1. The components of the truck shall be fastened by one or more of the following means: spot-welding, bolting, riveting, or other equally suitable means. The truck shall be finished with a durable enamel and, unless otherwise specified (see 6.2), the color shall be the manufacturer's standard.

3.5.1.1 *Footlocks.* Footlocks shall be provided on at least two wheels or casters to hold the truck stationary when necessary.

3.5.2 *Chest.* The chest, when furnished, shall be constructed of sheet metal or wood of sturdy construction so as to withstand hard and rough usage. The chest shall be equipped with a hinged cover with a positive-acting latch. The chest shall have a handle(s) for carrying the kit. Storage space shall be provided for the handbook of instructions.

3.6 Finish. Unless otherwise specified (see 6.2), the jack shall be treated and painted in accordance with GGG–J–68. Trucks and chests shall be finished in accordance with the manufacturer's standard practice.

3.7 Item identification. The truck, chest, and each item in the jack kit, where feasible, shall be marked in a plain and permanent manner with the name of the manufacturer or a trademark of such known character that the source of manufacture may be readily determined.

3.8 Workmanship. Workmanship shall be first class in every respect. All fastenings such as bolts, screws, and nuts shall be securely fastened, and rivets shall be properly set. Edges shall be rounded, beveled, or deburred in a manner to prevent injury to the operator.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 *Inspection of materials and components.* In accordance with 4.1, the supplier is responsible for insuring that materials and components used were manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.2 Sampling procedures. Sampling procedures shall be in accordance with MIL–STD–105. Data for sampling shall be as stated in table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

Table IV. *Sampling data*

Category	Sample unit	Inspection level	Acceptable quality level	AQL expressed in terms of	Reference
Visual examination	1 kit	II	4.0	Defects per 100 units	4.3.1
Dimensional examination	1 kit	S-2	4.0	do.	4.3.2
Testing of truck	1 truck	S-2	2.5	do.	4.4.1
Testing of chest handle(s)	1 chest	S-2	2.5	do.	4.4.2
Drop test for chest	1 chest	S-2	2.5	do.	4.4.3
Testing of kit	1 kit	S-2	2.5	do.	4.4.4
Examination of preparation for delivery	One container	S-2	4.0	do.	4.5

Note: Jack kit – Each item in the kit, including container, shall be considered as an individual sample unit and formed into lots and inspected accordingly.

4.3 Examination.

4.3.1 *Visual examination.* Each sample unit shall be examined for any nonconformance in design, material, finish, coating, construction, workmanship, and marking. Defects are listed in table V.

Table V. *Classification of defects*

Examine	Defects
Design	Not capacity specified or not similar to specified type.
Material	Not fabricated from specified material.
Construction and workmanship	Welding, soldering, or brazing not in accordance with specifications.
	Component missing.
	Foot locks for casters omitted.
	Screws, pin, or bolts swaged, peened, or staked.
	Casting, blowholes, peened, or plugged.
	Castings not free of blowholes, porosity, cracks, or other casting defects.
	Chest split, cracked, or dented.
	Parts not interchangeable.
	Means not provided to prevent overtravel.
	Connecting hose not size specified.
	Attachments not complete.
	Tubing extension sets not as specified.
	Safety devices not as required.
	Handbook of instructions missing or incomplete.
Finish or coating	Not type specified.
	Chipping, peeling, flaking, runs, sags, orange peel, or scratches.

Table V. *Classification of defects (cont'd)*

Examine	Defects
	Area of thin film or no film.
	Paint tacky (not completely dry).
	Natural finish not free from scale, rust, or other harmful imperfections.
Identification marking	Parts not marked with manufacturer's name or trademark, illegible, or incorrect.

4.3.2 *Dimensional examination.* Each sample unit shall be examined for any nonconformance with dimensional requirements.

4.4 Testing. Each sample unit shall be tested in accordance with 4.4.1 through 4.4.4.

4.4.1 *Performance test for handtruck.* The handtruck with hydraulic jack, and the accessories in place on the truck, shall be rolled over three, 3/8-inch thick, sharp edged (90°) hardwood boards at a walking pace. The boards shall be spaced 6 feet apart perpendicular to and lengthwise across the line of travel of the truck. One round trip shall be made over the three boards. The truck should be observed to determine the following: (1) none of the accessories have fallen off the truck, (2) none of the balls have fallen out of the bearing races, (3) the swiveling casters swivel freely, (4) the wheels rotate freely, and (5) no damage has been done to any component of the truck or kit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

4.4.2 *Performance test for chest handle(s).* Each of the sample chests shall be tested for compliance with the specification by loading the chest with the jack and all accessories, plus overweight of 10 percent, and lifting 10 times. The handle(s) and chest shall then be examined for separation from the chest or permanent distortion which would affect the serviceability of the chest.

4.4.3 *Drop test for chest.* Each sample chest shall be loaded as specified in 4.4.2, and dropped from a height of 12 inches three times in a normal upright (bottom down) position. The chest shall then be examined to determine whether split or cracked, hinges operate satisfactorily, any rivets or welds have pulled loose or broken, or if any permanent distortion has occurred which would affect the serviceability of the chest.

4.4.4 *Performance test for the jack kit.* The inspector shall test the hydraulic jack in accordance with GGG–J–63 and its accessories to determine that the complete kit operates satisfactorily, and that the accessories meet the test requirements of 3.4.

4.5 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the preservation, packaging, packing, and marking comply with the requirements in section 5. Defects shall be scored in accordance with table VI. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL–STD–105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot.

Table VI. *Classification of preparation for delivery defects*

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling.
	Distortion of container.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, and packing. Unless otherwise specified (see 6.2), the jack kits shall be preserved, packaged, and packed in accordance with MIL–H–15424. The levels of preservation and packaging shall be A or C and the level of packing A, B, or C, as specified (see 6.2).

5.1.1 As part of the requirements of section 5 of this specification, table VII is considered as part of table I of MIL–H–15424.

5.2 Marking.

5.2.1 *Civil agencies.* In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 *Military activities.* In addition to markings required by the contract or order,

Table VII

Col 1	Col 2	Col 3	Col 4	Col 5	Col 6	Col 7
Jack, kit: hydraulic, hand (with truck or chest)	P–1 (See 3.3.1.4)	I	1		1*	

*The hydraulic jack with attachments and accessories shall be preserved, packaged, and packed as one kit.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:36Z
Check the source to verify that this is the current version before use.

the interior packages and shipping containers shall be marked in accordance with MIL–STD–129.

6. NOTES

6.1 **Intended use.** It is intended that with the aid of the hydraulic jack with attachments and accessories, the operator shall be capable of (1) pulling with chains and pull plate, (2) pushing with the flat base, V-base, adjustable body spoon, flexible heads, and/or serrated saddle, (3) clamping with the clamp head and toes, and (4) spreading with the spreader toes. The truck or chest is intended for use in moving and storing the jack kit and transporting from one job to another.

6.2 **Ordering data.** Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(*a*) Title, number, and date of this specification.
(*b*) Size required (see 1.2 and 3.3).
(*c*) Handbook of instructions if different and address where additional copies are to be sent (see 3.2).
(*d*) Preliminary handbook approval when required (see 3.2.1).
(*e*) Additional accessories when required for 4-ton jack kit (see table I).
(*f*) Whether truck or chest required (see 3.5).
(*g*) State color of truck if a specific color is required (see 3.5.1).
(*h*) Finish, if different (see 3.6).
(*i*) Selection of applicable levels of preservation, packaging, and packing required (see 5.1 and 5.1.1).

6.3 **For civil agency procurements.** When level B packaging is required for civil agency procurements, the level A requirements in 5.1 shall apply.

MILITARY INTEREST:

Army
Navy
Air Force

CUSTODIANS

GL
SH
69

Review activities:

WC, GL, MO
SH
69

User activities:

– –
MC
– –

Preparing activity:

GSA–FSS

Orders for this publication are to be placed with General Service Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced. Price 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.