GGG-S-51D
INTERIM AMENDMENT-2(GSA-FSS)
January 19, 1971
SUPERSEDING
Int. Amendment-1(GSA-FSS)
October 12, 1970

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

SAW, CIRCULAR, PORTABLE, ELECTRIC

This Interim Amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C., 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Amendment as a valid exception to Federal Specification GGG-S-51D, dated November 12, 1969.

PAGE 1

Paragraph 2.1, under "Federal Specifications." Add "PPP-P-40 - Packaging and Packing of Hand Tools."

PAGE 2

Paragraph 2.1, under "Military Specifications." Delete "MIL-H-15424 - Hand Tools; Packaging of."

Paragraph 2.1, under "Military Standards." Delete "MIL-STD-129 - Marking for Shipment and Storage."

Paragraph 2.1, under "Military Standards." Delete "MIL-STD-1338" and substitute "MIL-STD-1337."

PAGE 3

Paragraph 3.4.1: Delete and substitute the following:

3.4.1 Conformance to standards of Underwriters' Laboratories, Inc. The contractor shall submit to the contracting agency proof that the basic saw he proposes to supply under this specification conforms to the requirements of the UL-45. The label, or listing with re-examination of the UL may be accepted as evidence that the saw conforms to this requirement. In lieu of the label, or listing with re-examination, the contractor may submit independent proof, satisfactory to the contracting agency, that the saw conforms to the applicable requirements of the published standards including methods of tests of the UL Standards noted above. Compliance with requirements of UL regarding fire and casualty hazards does not absolve the contractor from complete compliance with the requirements of this specification in order to secure the acceptance of his saw. In event of difference between any of the requirements of this specification and those of UL, the requirements of this specification shall govern.

Paragraph 3.4.1.1: Delete in its entirety.

FSC 5130

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

PAGE 4

TABLES I & II, delete in their entirety and substitute the following:

TABLE I. Type I saw requirements

Size	Blade diameter	No-load blade speed minimum	Cutting capacity			Power output at spindle minimum	Rated current minimum	Blade arbor hole diameter	Weight (excluding cord 1/ maximum
			90° at least	45° at least	Minimum cutting range				
Inches	Inches	R.P.M.	Inches	Inches	Inches	HP	Amps	Inch	Pounds
6	6-1/2 to 6-3/4	5500	2	1-1/4	0 to 1/2	1/2	7	5/8	15
7	7 to 7-1/4	5200	2-3/8	1-3/4	0 to 3/4	1/2	8	5/8	18
8	8 to 8-1/4	5000	2-5/8	1-7/8	0 to 1	3/4	9	5/8	18
10	10 to 10-1/4	3800	3-3/8	2-1/4	0 to 1-1/4	1-1/8	12	3/4	35
12	12	3800	4-1/4	3	0 to 2	1-1/2	15	3/4	37

1/ UL approved power cord.

TABLE II. Type II saw requirements

Size	Blade diameter	No-load blade speed minimum	Cutting capacity			Power output at spindle minimum	Rated current minimum	Blade arbor hole diameter	Weight (excluding cord 1/ maximum
			90° at least	45° at least	Minimum cutting range				
Inches	Inches	R.P.M.	Inches	Inches	Inches	HP	Amps	Inch	Pounds
6	6-1/2 to 6-3/4	4500	2	1-1/4	0 to 1/2	3/4	8	5/8	15
7	7-1/4 to 7-1/2	4200	2-3/8	1-3/4	0 to 3/4	3/4	9	5/8	18
8	8 to 8-1/4	4200	2-5/8	1-7/8	0 to 1	3/4	9	5/8	18
10	9-7/8 to 10-1/4	2900	3-3/8	2-1/4	0 to 1-1/4	1-1/8	12	3/4	35
12	11-7/8 to 12	2500	4-1/4	3	0 to 2-3/8	1-1/2	15	3/4	37

1/ UL approved power cord.

PAGE 7

Paragraph 3.10: Delete in its entirety and substitute the following:

3.10 Carrying case. Each saw shall be furnished with durable carrying case of sufficient size to contain the circular saw, maintenance tools, and accessories. The case shall be complete with hinged cover, carrying handle, and closing fastener. The interior and exterior surfaces of the carrying case shall have a durable coating of paint or enamel, except surfaces which are inherently corrosion free or electroplated. The case shall be marked or lettered to show the following:

(a) Saw, Circular, Portable, Electric.
(b) Stock number FSC 5130-...-....
(c) Saw size.
(d) Electrical characteristics.
(e) Manufacturer's name or trademark.

Paragraph 3.11, on the lines "(g)" and "(h)". Delete the words "blade capacity".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

PAGE 8

Paragraph 4.4 (b): Delete "4.5.4" and substitute "4.5.3".

PAGE 9

Paragraph 4.4.2, line 5. Delete "4.5.4" and substitute "4.5.3".

Paragraph 4.5.3: Delete in its entirety and substitute:

4.5.3 No load test. Sample saws selected shall be operated thirty minutes at no-load operation. During the test, the saw shall be checked for switch operation, loss of lubricant, and indication of overheating.

Paragraph 4.5.4: Under "Performance test", delete line "(d)" in its entirety.

Section 5.: Delete Section 5 in its entirety and substitute the following:

5. PREPARATION FOR DELIVERY.

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking shall be in accordance with the requirements of PPP-P-40 for portable electric circular saws.

PAGE 10

Paragraph 6.2: Line "(h)" delete in its entirety.
Line "(i)" delete "(i)" and substitute "(h)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

▲ DC 71-8760