GGG-T-00400a(GSA-FSS)
August 4, 1965
SUPERSEDING
Int. Fed. Spec. GGG-T-00400(GSA-FSS)
December 29, 1955

INTERIM FEDERAL SPECIFICATION

TAMPERS, HAND

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C., 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. The tampers covered by this specification are long-handled tools with flat surface for tamping concrete, earth, or asphalt.

1.1.1 Federal specification coverage. Federal specifications do not include all varieties of the commodity as indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

1.2 Classification.

1.2.1 Types and classes. Tampers shall be of the following types and classes as specified (see 6.1):

Type I. - Wood handle with metal head, square type.

Type II. - Metal, square type.

Type III. - Bar.
Class 1. - All metal.
Class 2. - Wood and metal, combination.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids, or request for proposals, form a part of this specification:

Federal Standards:
Fed. Std. No. 102 - Preservation, Packaging and Packing Levels.
Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:36Z
Check the source to verify that this is the current version before use.

Military Specifications:
MIL-H-15424 - Hand Tools, Packaging of.

Military Standards:
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Illustrations. The illustrations shown herein are for the convenience of identification and are not intended to preclude the purchase of tampers which are otherwise in accordance with the requirements of this specification.

3.2 Material. All material used in the tampers shall be of good quality and suitable for the purpose intended.

3.3 Castings. Castings shall be of uniform quality, free from blowholes, porosity, cracks, fins, sprues, burrs and other injurious defects or harmful extraneous material which might affect their serviceability. The four corners and edges shall be rounded or chamfered to prevent injury to the user.

3.4 Steel plates. Steel plates, if used in construction of the tamper head, shall be free from burrs and excessive scale, and the corners and edges of the plate shall be slightly rounded or chamfered to prevent injury to the user.

3.5 Finish. Tamper plates, or heads, shall have either a natural or painted finish, at the option of the contractor.

3.6 Handle. Handle shall be of wood or metal as specified (see 1.2 and 6.1). It shall be securely fastened in the tamper in a manner to preclude loosening or coming out of the socket head during service.

3.6.1 Wood. When wood handle is furnished, it shall be circular in cross section and have the free end rounded. Handle shall be smooth and free from knots, checks, excessive cross grain or any other defects which might affect serviceability or durability. Handle shall be finished and covered with two durable coats of transparent lacquer, varnish, or wax; or one coat after surface treatment utilizing heat, such as flame-treating or charring. The coating shall be applied in a manner not to conceal defects in the wood. Handle shall have a minimum diameter of 1-1/2 inches.

3.6.2 Metal. Metal handle may be of 1-1/4-inch iron pipe, or steel tubing not less than 1-1/4 inches in diameter. It shall be either galvanized or a natural finish which, at the option of the contractor, may or may not be painted.

3.7 Type I tamper. Type I tamper (see figure 1) shall consist of a metal tamping head and a wooden handle, either tapered or straight. Tamper shall comply with the dimensions and weights specified in table I.




Figure 1. - Types I and II tampers.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:36Z
Check the source to verify that this is the current version before use.

Table I. - Dimensions.

Size of head		Overall length (min.)	Weight
Width D	Length C	A	(min.)
Inches	Inches	Inches	Pounds
8	8	48	15
10	10	48	20

3.7.1 Head. The tamper head shall consist of a square steel or cast iron plate with a socket for attachment of a handle. The reverse side of the plate from the socket side shall have a flat surface. The socket portion and the flat plate portion of the head may be either two separate components, or cast integral. The tamper may be furnished either plain or with reinforcing ribs. When the head is fabricated from more than one component, the final assembly shall afford equal strength and serviceability to a head of one-piece construction.

3.7.1.1 Plate thickness. The plate shall have either a uniform thickness of not less than 5/16 inch or a tapering thickness, starting with 5/16 inch at the four outer edges and gradually increasing in thickness toward the socket portion of the head.

3.7.2 Handle. Handle shall be in accordance with 3.6 and 3.6.1.

3.8 Type II. - Type II tampers shall be of all metal, conform to the requirements of 3.7.1 and 3.7.1.1, and have a handle as specified in 3.6 and 3.6.2. Tamper shall be similar to figure 1, and conform to the dimensions specified in table I.

3.8 Type III, bar.

3.8.1 Class 1 tamping bar shall consist of a steel tubing handle not less than 1-5/16 inch in diameter with tamping head on each end. The tamping heads may be of steel or malleable iron, securely fastened to the handle ends to prevent loosening. The tamping heads shall have a flat surface for tamping and the opposite side of the head shall be either flat or beveled. Tamper shall be similar to figure 2 and conform to dimensions specified in table II.




Figure 2. - Type III, class 1, tamping bar.

Table II. - Type III, class 1, dimensions.

Size of large head		Size of small head		Overall length (min.)	Weight
Length (min.) C	Width (min.) D	Length (min.) C	Width (min.) D	A	(min.)
Inches	Inches	Inches	Inches	Inches	Pounds
6	2-3/4	3-3/4	2-1/2	90	12

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:36Z
Check the source to verify that this is the current version before use.

3.8.2 Finish. The tamper shall be painted, lacquered, or otherwise finished to retard rusting.

3.8.3 Class 2. Class 2 tamping bar shall be of wood as specified in 3.6.1. The tamping head shall be paddle-shaped with a 1/4-inch minimum thickness steel shoe securely riveted around the edge. Rivets shall be neatly set. Bar shall be similar to figure 3 and conform to dimensions specified in table III.




Figure 3. - Type III, class 2, tamping bar.

Table III. - Type III, class 2 dimensions.

Size of head		Overall length (min.)	Weight (min.)
Length (min.) C	Width (min.) D	A	
Inches	Inches	Inches	Pounds
3-1/2	1-1/2	90	12

3.9 Marking. Each tamper shall be marked in a plain and permanent manner with the name of the manufacturer or trademark of such known character that the source of manufacture may be readily determined.

3.10 Workmanship. Workmanship shall be first class in every respect. Tampers shall be free from defects which might affect their durability or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection of materials and components. In accordance with 4.1, the supplier is responsible for insuring that materials and components used were manufactured, tested and inspected in accordance with requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.2 Sampling procedures. Sampling procedures shall be in accordance with MIL-STD-105. Data for sampling shall be as stated in table IV.

4.3 Examination.

4.3.1 Visual examination. Each sample unit shall be examined for any nonconformance in design, material, finish, coating, construction, workmanship, and marking.

4.3.2 Dimensional and weight examination. Each sample unit shall be examined for any nonconformance with dimensional and weight requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:36Z
Check the source to verify that this is the current version before use.

Table IV. - Sampling data.

Category	Sample Unit	Inspection Level	Acceptable Quality Level	AQL Expressed In Terms Of	Reference
Visual examination	1 ea.	II	4.0	Defects per 100 units	4.3.1
Dimensional and weight examination	1 ea.	II	4.0	Defects per 100 units	4.3.2
Preparation for delivery	One container	S-2	4.0	Defects per 100 units	4.4

4.4 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the preservation, packaging, packing and marking comply with the requirements in section 5 of this specification Defects shall be scored in accordance with table V.

Table V. - Classification of preparation for delivery defects.

Examine	Defects
Markings (exterior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.

5. PREPARATION FOR DELIVERY
(For civil agency procurement the definitions and application of levels of packaging and packing shall be in accordance with Fed. Std. No. 102).

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The tampers shall be preserved and packaged in accordance with MIL-H-15424 as specified for level A.

5.1.2 Level C. The tampers shall be packaged in accordance with the supplier's commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.1).

5.2.1 Level A. The tampers shall be packed in accordance with MIL-H-15424 as specified for level A.

5.2.2 Level B. The tampers shall be packed in accordance with MIL-H-15424 as specified for level B.

5.2.3 Level C. The tampers shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the rules and regulations applicable to the mode of transportation.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:36Z
Check the source to verify that this is the currentversion before use.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the shipping containers or each bundle shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to markings required by the contract or order, the shipping containers or each bundle shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Type and class required (see 1.2).
(c) Size required (see tables I, II and III).
(d) Applicable levels of preservation, packaging, and packing required (see 5.1 and 5.2).
(e) Special marking, if required (see 5.3).

GSA DC 86-3733

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:36Z
Check the source to verify that this is the current version before use.