RR-C-114c
September 21, 1964
SUPERSEDING
Fed. Spec. RR-C-114b
August 25, 1953

FEDERAL SPECIFICATION

CANS, FLAMMABLE WASTE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers metal foot or hand operated flammable waste cans.

1.2 Classification.

1.2.1 *Types and sizes.* Flammable waste cans shall be of the following types and sizes, as specified (see 6.2).

Type I—Foot operated
Size—6-gallon
Size—10-gallon
Type II—Hand operated
Size—21-gallon

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 The following specifications and standards, of the issues, in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

PPP-B-636—Box, Fiberboard.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).
Fed. Test Method Std. No. 151—Metals; Test Methods.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection By Attributes.
MIL-STD-129—Marking for Shipment and Storage.
MIL-STD-130—Identification Marking of U. S. Military Property.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publication. The following document forms a part of this specification to the extent specified herein. Unless other-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

wise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

Underwriters' Laboratories, Inc. Standard:

Standard for Waste Cans, Subject 32.

(Copies of the Underwriters' Laboratories, Inc., standards are available from the Underwriters' Laboratories, Inc., 161 Sixth Avenue, New York 13, New York; 207 East Ohio Street, Chicago 11, Illinois; or 1655 Scott Lane, Santa Clara, California.)

3. REQUIREMENTS

3.1 Preproduction sample. When specified (see 6.2), before production is commenced, samples of the flammable waste cans shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production item.

3.2 Standard product. The flammable waste cans shall be the manufacturer's current standard commercial design, except as specified herein.

3.3 Safety standard. Flammable waste cans shall conform to Underwriters' Laboratories, Inc. Standard for Waste Cans.

3.3.1 *Certification.* Prior to approval of the preproduction sample, if one is submitted, or prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer that the flammable waste cans he proposes to furnish under this specification meet the requirements of the applicable UL standard. Acceptable evidence of meeting the requirements of this standard shall be the UL label, an approved UL listing, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the cans offered have been tested and conform to the requirements of the applicable UL standard.

3.4 Materials. The material for the body panel, bottom panel, cover and all sheet-metal members for the flammable waste cans shall be zinc-coated (galvanized), sheet steel, tin-coated steel, lead-coated sheet steel (terneplate) or uncoated steel, at the option of the contractor. The bail shall be zinc-coated (galvanized) drawn wire or side handles may be made of steel strip.

3.4.1 *Thickness and diameter dimensions for material.* The thickness of sheet steel, the diameter of reinforcing wire for can body, and the diameter of rod for bail and side handles, shall be as shown in table I for the size specified (see 6.2).

3.5 Construction. The construction of all components and assemblies of the waste cans covered herein shall conform to this specification as specified hereinafter. Formed bail for the completed can fabricated from uncoated sheet steel shall be attached after the can is finished as specified in 3.6. There shall be no binding or catching that will prevent the foot-operated cover-lifting device from elevating the cover. The bail shall swing freely in the clips and shall not interfere with the free movement of the cover.

3.5.1 *Seams.* The vertical body panel seam and the bottom panel seam shall be formed and joined in accordance with Underwriters' Laboratories, Inc. Standard for waste cans. Formed seams shall be not less than 1/4-inch in width, and shall have a metal overlap of not less than 1/8-inch. All seams shall be sealed with solder except where hot galvanized dipping or electric seam welding is used. The bottom and lower 6 inches of the body shall not leak when tested as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE I.—*Thickness and diameter dimensions for material*

Capacity (size)		Thickness of sheet steel before coating, and equivalent U. S. standard gage, minimum						Reinforcements		Bails or side handles, diameter of steel rod, minimum [1]	Leg thickness and width, minimum [2]
		Body		Bottom		Cover		Body Wire diameter in top bead, minimum	Cover Thickness and width of steel straps, minimum		
Gallons	Cubic inches	Inch	Gage	Inch	Gage	Inch	Gage	Inch	Inch	Inch	Inches
6	1,386	0.0179	26	0.0179	26	0.0239	24	0.148	1/8 x 7/8	1/4	0.108 x 7/8
10	2,310	.0218	25	.0218	25	.0281	23	.148	1/8 x 7/8	1/4	0.108 x 7/8
21	4,851	.0239	24	.0239	24	.0299	22	.172	1/8 x 1	*5/16	3/16 x 1-1/4

[1] Steel forgings, if used, shall have a diameter or minimum dimensions not less than that shown; castings, if used, shall not be less than 3/16 inch thick.

[2] Cast (malleable iron) legs, if used, shall be not less than 3/16 inch thick.

* Applies to side handles.

3.5.2 *Dimensions and capacities.* The capacity and inside width and length or diameter and height dimensions shall be as shown in table II for the size specified, (see 1.2). The can inside diameter shall be not less than 90 percent of the inside height of the body. The inside dimensions of the triangular or square can shall be proportioned to the depth to maintain the proper stability of the can.

TABLE II.—*Dimensions and capacities*[1]

Inside width and length or diameter (inches)	Inside height (inches)	Nominal capacity (gallons)
12	13-3/8	6
14	15-1/2	10
17-1/2	19-15/16	21

[1] Dimensions and capacities shall be not less than specified.

3.5.3 *Screws, bolts or tinners rivets.* Screws, bolts or tinners rivets shall be commercial type, plain or zinc coated, as applicable. The screws or bolts shall be used with lock washers, or the screws or bolts shall be headed over a nut without lockwasher in such a manner that the nut cannot work loose.

3.5.4 *Details of components.*

3.5.4.1 *Body panel.* The body panel shall be fabricated from material specified in 3.4. The panel shape shall be either round, triangular with round corners, or square with round corners. The panel shall be formed from a single sheet with the ends joined as specified in 3.5.1.

3.5.4.2 *Bottom panel.* The bottom panel shall be fabricated from the same material as the body panel (see 3.5.4.1). The panel shall be formed from a single sheet, and joined to the body panel as specified in 3.5.1. The panel bottom shall be not less than three (3) inches nor more than four (4) inches above the floor when bottom support is assembled.

3.5.4.3 *Body panel top edge reinforcement.* The top edge of the body panel shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

be beaded over the reinforcing wire specified in table I, or beaded over without wire reinforcement, to form a rolled rim not exceeding 1/4-inch diameter, or the tope edge shall be reinforced with a full circumferential steel strap. When steel-strap reinforcement is used on the 10- and 6-gallon cans, the strap shall be not less than 1/8-inch thick and not less than 7/8-inch wide; on the 21-gallon size, the strap shall be not less than 1/8-inch thick and not less than 2 inches wide. The strap shall be either riveted or spot-welded to the body. If riveted, the rivets shall be spaced on not more than 4-inch centers. If spot welded, the welds shall be spaced on not more than 2-inch centers.

3.5.4.4 *Cover, single moveable type or two-section type.* There shall be either a single moveable cover arranged to completely enclose the waste compartment, or a cover in two sections, one section moveable and hinged to the other stationary section. The single moveable cover shall be reinforced by 2 steel straps, each not less than 7/8 inch wide and 1/8 inch thick, one of which runs parallel to the base of the cover and protects the cover when it is raised against the cover stop. The other strap shall run at right angles to the base of the cover with its length being not less than 70 percent of the altitude of cover. This band may be attached to the underside of the cover. The straps shall be attached to the cover by means of at least 5 spot welds per strap. The cover stop shall be of substantial construction, integral with the hinge, and shall bear on a steel reinforcing plate permanently secured to the can body. When the cover is rapidly elevated, the impact on the stop shall not produce any deformation. For the cover in two sections, the width of the stationary section, measured at right angles to its straight edge, shall not exceed one-third of the inside dimension of the body measured at the widest point. The stationary section shall be flanged or rolled over the outside of the body, and reinforced on the top surface with a riveted or welded steel strap, or flanged and embossed to provide substantial reinforcement, and on the bottom surface with a steel strap or embossing at right angles to the top strap. The top strap shall form a rigid stop for the moveable section and may serve as a carrying handle. Ends of the straps shall be permanently secured to the body. The rim of the moveable section shall be flanged to overlap the end of the body and the flanged edge shall be rolled or curled.

3.5.4.5 *Cover hinge.* The cover hinge shall be of substantial construction and arranged to maintain the cover in permanent alignment and permit free movement. Hinge pins shall be of the full-length type or of the rivet type. Full-length hinge pins shall have a diameter of not less than 0.156 inch on 10- and 6-gallon cans and not less than 0.172 inch on the 21-gallon can. Rivets, if used for hinge pins, shall have a body diameter of not less than 3/16-inch. Hinge pins shall be headed or mechanically secured to prevent lateral movement. The total length of the hinge pin bearings in the moveable sections and in the stationary sections of the hinge shall be not less than 1/6 of the longest inside dimension of the can. The thickness of the metal forming the hinge body shall be not less than the thickness of the metal used for the cover. Separate hinges of a two-piece cover shall have a metal thickness of not less than 3/64 inch.

3.5.4.6 *Cover-lifting handle (type II.)* The type II can, without foot-operated cover-lifting device, shall be provided with a curved or looped rigid cover-lifting handle, integral with a reinforcing steel strap of the moveable cover top and arranged for conveniently elevating the cover top, or a pressed steel handle, free from sharp edges, not less than 1-inch wide at the center and with a grip length of not less than 1-1/4 inches. The pressed steel handle shall be not less than 0.0359-inch thick (No. 20 U. S. Standard gage) and shall be either riveted or spot-welded to the cover. If riveted there shall be two (2) or more rivets; if welded, there shall be four (4) or more spot welds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

3.5.4.7 *Foot-operated, cover-lifting device (type I).* The type I can shall be provided with a foot-operated cover-lifting device. The device shall consist of a foot pedal, horizontal treadle beam member and upright lift member. Application of foot pressure on the pedal, with the heel in contact with the floor, shall elevate the cover to its maximum height. The foot pedal, horizontal treadle beam member and the upright lift member shall be steel, not less than 0.108-inch thick, and shall not visibly deform when the cover is rapidly elevated by operation of the foot pedal. The pivots of pivoted members shall have a body diameter of not less than 3/16-inch, and shall be either headed at the ends or provided with split cotter pins in a manner to insure a permanent pivoted joint.

3.5.4.8 *Side and top handles or bail.* The 10- and 6-gallon size cans shall be provided with either a single rigid top handle, handle and stop combined, pivoted bail, or two pivoted side handles, at the option of the contractor. The 21-gallon size shall be provided with two side handles. The rigid top handle shall be integral with, and the same size as, the top reinforcing steel strap of the stationary section of the cover (see 3.5.4.4), and, at the option of the contractor, may be used to serve as the stop for the moveable cover. The bail shall be secured to the can body with metal clips. The bail, in any position, shall not interfere with the free movement of the cover. Side handles shall be either castings, forgings, formed sheet steel or formed wire rod, at the option of the contractor. The opening in the top handle and side handles shall be not less than 1-1/2 inches wide and not less than 3-1/2 inches long.

3.5.4.9 *Clips.* Clips for attaching the bail and side handles shall be sheet steel, not less than 0.0538-inch thick. (No. 18 U. S. Standard gage) and riveted or welded to the body. On 6-gallon cans, each clip shall be fastened to the body with two or more rivets, or with four or more spot welds. On 10-gallon and 21-gallon cans, each clip shall be fastened to the body with three rivets, or with six or more spot welds. Rivets shall have a body diameter of not less than 1/8 inch.

3.5.4.10 *Supports.* The can shall have three or more pressed-steel, strap-steel or malleable-iron legs shaped to provide flat floor rests equally spaced around the bottom panel, or a cylindrical support suitably perforated for venting. Each leg shall be riveted to the body or bottom panel with one or more rivets. The cylindrical support shall be either riveted to or integral with the body panel and the bottom edge shall be reinforced with either a full circumferential steel strap not less than 1.8-inch thick and not less than 1-3/4 inches wide. The steel strap shall be either riveted to the support with rivets spaced on not more than 4-inch centers or welded with spot welds spaced on not more than 2-inch centers. In lieu of the steel strap, 10- and 6-gallon cans may have a rolled rim with or without an inserted steel wire not less than 1/4-inch in diameter. There shall be at least eight 1-inch diameter holes in the support below the bottom panel or the equivalent area opening in not less than three holes. The completed empty can shall not tip over of its own accord when placed in an upright position on an inclined plane surface which forms an angle of 30 degrees with the horizontal.

3.6 Finish. Completely fabricated cans shall be delivered in the natural zinc-coated (galvanized) finish or lead-tin-coated sheet steel (terneplate). The cans may be sprayed with a solvent-resistant enamel (when specified). The zinc and terneplate surfaces shall be suitably prepared prior to application of the enamel. The enamel shall be red or yellow, as specified (see 6.2), and the finish shall be free from cracks, chips, wrinkles, blisters, and uncoated areas. If fabricated from uncoated sheet steel, completed cans, without bails attached, shall be cleaned, and loose scale and rust removed. Every portion of the uncoated cans, inside and outside, shall be completely coated with

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

zinc by the molten bath process. Weight of the coating shall be not less than 2 ounces per square foot, total on both sides, determined by the test method specified in 4.4.2. The zinc coating shall be smooth, continuous, and thorough, the coating shall be free from such imperfections as lumps, blisters, gritty areas, uncoated spots, acid and black spots, dross and flux, and other injurious defects within the limits consistent with best commercial practice. There shall be no flaking or peeling when tested as specified in 4.4.3.

3.7 Marking. Unless otherwise specified (see 6.2) the method of marking shall be in accordance with MIL-STD-130. All cans shall be permanently marked to show capacity or trade number indicating the capacity together with either the manufacturer's name or a readily identifiable trademark, and the instruction notice in large letters "EMPTY EVERY NIGHT" located on the can side.

3.8 Workmanship. The finished cans shall conform to the grade and quality of product established by this specification.

4. SAMPLING, INSPECTION AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 **Preproduction sample inspection.** When a preproduction sample is required, the preproduction sample shall be examined in accordance with defects in table III, dimensions specified, and tested in accordance with 4.4.1 thru 4.4.3.

4.3 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3.1 *Inspection of materials and components.* In accordance with 4.1 above, the supplier is responsible for insuring that components and materials used were manufactured, tested and inspected in accordance with the specified requirements of referenced subsidiary specifications and standards to the extent specified or, if none, in accordance with this specification.

4.3.2 *In-process inspection.* Inspection shall be made during any phase of the manufacturing process to determine whether galvanizing is accomplished prior to enameling, when required, as specified in 3.6. Whenever nonconformance is noted, correction shall be made to affected items and lot in process.

4.3.3 *Inspection of the end item.* The lot shall consist of all complete cans of one type and size offered for acceptance at one time. The sample unit for this inspection shall be one completely fabricated can.

4.3.3.1 *Visual examination.* Examination of the end item shall be in accordance with the classification of defects specified in table III. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects, and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE III.—*Classification of defects*

Examine	Defect	Classification	
		Major	Minor
Finish	Coating not as specified.	X	
	Coating not smooth, continuous or thorough.		X
	Not free of lumps, blisters, gritty or uncoated areas, acid or black spots, dross or flux.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE III.—*Classification of defects (cont'd)*

Examine	Defect	Classification	
		Major	Minor
Finish (cont'd)	Enamel (if applicable) not type or color.		X
	Area of no film.		X
	Not continuous, smooth or adherent.		X
	Cracked, blistered, chipped.		X
Construction and workmanship (general, types I and II)	Component missing.	X	
	Any component not fabricated as specified.	X	
	Body panel not formed of one piece or not joined as specified.		X
	Bottom panel not joined to body as specified.		X
	Not provided with carrying handle or handles as specified.		X
	Vertical body seam, bottom panel seam and rivets with beads on inside of waste compartment, except for rivets in cover, not fabricated as specified.	X	
	Empty can tips over when placed on inclined plane surface of 30 degrees.		X
	Body panel ends not joined as specified.		X
	Circumferential steel-strap reinforcement missing or not attached as specified.	X	
	Any part malformed, bent, out of shape, warped, or mispositioned.	X	
	Any component not securely mounted or attached as specified.	X	
	Any component fractured or split.	X	
	Any sharp edge, projection or sliver.	X	

TABLE III.—*Classification of defects (cont'd)*

Examine	Defect	Classification	
		Major	Minor
Construction and workmanship (general, types I and II) (cont'd)	Top edge of can body not reinforced as specified.	X	
	Wire reinforcement not completely inclosed within a rim rolled around the entire periphery of the body (if applicable).		X
	Steel-strap reinforcement not riveted or spot welded to body (if applicable).		X
Foot-operated, cover-lifting device (type I)	Not provided with foot-operated cover-lifting device.	X	
	Foot-operated lifting device does not function as specified.		X
	Application of foot pressure on foot pedal does not elevate the cover to its maximum height.		X
	Foot pedal lifting device members show deformation when cover is rapidly elevated.	X	
Cover-lifting handle (type II)	Not provided with a curved or looped rigid cover lifting handle.		X
	Handle not integral with a reinforcing steel strap of the movable cover top or not arranged for conveniently elevating the cover top.		X
	Pressed steel handle not free of any sharp edges (if applicable).	X	
	Pressed steel handle not riveted or spot welded to cover (if applicable).	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE III.—*Classification of defects (cont'd)*

Examine	Defect	Classification	
		Major	Minor
Cover-lifting handle (type II) (cont'd)	Not riveted with two or more rivets or four spot welds (if applicable).		X
Cover, single section, types I and II (if applicable)	Cover not arranged to completely inclose waste compartment.	X	
	Cover not stiffened with straps and not spot welded as specified.		X
	Cover stop not of substantial construction, integral with the hinge, or does not bear on steel reinforcing plate permanently secured to can body.	X	
Cover, two section (types I and II) (if applicable)	One section of cover not moveable and hinged to the other stationary section.	X	
	Stationary section of cover not flanged or rolled over the outside of the body.	X	
	Stationary section not reinforced on the top surface by a steel strap, either by riveting or welding, or flanged and embossed.	X	
	Stationary section not reinforced on the bottom surface with a welded or riveted steel strap, or embossing at right angles to the top strap or embossing.		X
	Top reinforcing strap does not form a rigid stop for the moveable section, or does not serve as a carrying handle.		X
	Ends of strap not permanently secured to the body.	X	

TABLE III.—*Classification of defects (cont'd)*

Examine	Defect	Classification	
		Major	Minor
Cover, two section (types I and II) (if applicable) (cont'd)	Rim of the moveable section not flanged to overlap the end of the body or the flanged edge not rolled or curled.		X
Cover hinges (types I and II)	Not arranged to maintain cover in alignment or does not permit free movement of cover.	X	
	Hinge pins length less than 1/6 of the longest inside dimension of the can.		X
	Pins not headed or mechanically secured to prevent lateral movement.	X	
Side and top handles or bail (types I and II)	Not provided with type handles specified (6-, 10- and 21-gallon cans).	X	
	Rigid top handle not integral with, or the same size as the top reinforcing strap of the stationary section of cover.		X
	Pivoted bail or side handles not secured to can body with metal clips.	X	
	Pivoted bail in any position interferes with free movement of the cover.		X
Clips (types I and II)	Clips for attaching bail or side handles not riveted or welded to the body.	X	
	Not fastened to body by two or more rivets, or four or more spot welds (6-gallon cans).	X	
	Not fastened to body by three or more rivets or by six or more spot welds (10- and 21-gallon cans).		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE III.—*Classification of defects (cont'd)*

Examine	Defect	Classification	
		Major	Minor
Legs (types I and II)	Legs not shaped to provide flat floor rest, or enclosed support not suitably perforated for venting.	X	
	Each leg not riveted to the body or bottom panel, or to a reinforcing strap with one or more rivets.	X	
	Cylindrical support not riveted to, or integral with the body panel, or bottom edge not reinforced as specified.	X	
	Steel reinforcing strap not riveted or spot welded to the support as specified.	X	
	Rivets or spot welds not spaced as specified.		X
Riveting (as applicable)	Rivet missing where required.	X	
	Rivet not spaced as specified.		X
	Loose, cracked or not formed properly.	X	
	Any burrs or fins.		X
Welding (as applicable)	Omitted where required, not fused, burned through, cracked, fractured, or not complete.	X	
	Spot weld broken, missing where required or not compensated for, or welds not spaced as specified.	X	
Screws and bolts (when applicable)	Not provided with lock washers, or not headed over nut in a manner that cannot work loose.	X	
	Any screw or bolt missing.	X	
Identification marking	Missing, illegible, incomplete, or not as specified.		X

4.3.3.2 *Dimensional examination.* Inspection shall be made of cans for compliance with dimensions specified. Any dimensions not within specified requirements shall constitute a defect. The inspection level shall be S-2 and the acceptable quality level (AQL) 4.0, expressed in terms of defects per hundred units.

4.3.3.3 *Testing of the end item.* Testing shall be performed for oil tightness, weight of zinc coating and tightness of coating characteristics in accordance with table IV.

TABLE IV.—*Testing of the end item*

Characteristic	Requirement paragraph	Test paragraph	Inspection level	AQL
Oil tightness	3.5.1	4.4.1	100%	—
Weight of zinc coating	3.6	4.4.2	S-1	6.5
Tightness of zinc coating ..	3.6	4.4.3	S-1	6.5

4.3.4 *Examination of preparation for delivery.* An examination shall be made to determine that packaging, packing and marking as required by section 5 of this specification unit shall be one shipping container fully prepared for delivery with exception that it need not be sealed. The lot shall be the number of containers offered for delivery at one time. The inspection level shall be S-2 and the acceptable quality level (AQL) 4.0, expressed in terms of defects per hundred units.

Examine	Defect
Markings (exterior and interior)	Omitted; incorrect; illegible; of improper size, location sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling, bulging or distortion of containers.
Content	Number per container is more or less than required.

Source: https://assist.dla.mil -- Downloaded: 2026-02-28T12:09Z
Check the source to verify that this is the current version before use.

4.4 Tests

4.4.1 *Oil tightness.* Each can to be tested shall be filled with kerosene oil or any liquid that has low surface tension comparable to that of kerosene to a height of 6 inches above the highest level of the bottom panel, and allowed to stand in an upright position for 2 minutes. Examination shall then be made to determine compliance with 3.5.1.

4.4.2 *Weight of zinc coating.* The weight of zinc coating shall be determined in accordance with method 512.1 of Fed. Test Method Std. No. 151. The coating may be tested by the magnetic testing method.

4.4.3 *Tightness of zinc coating.* The coating of each can to be tested shall be scraped in several areas with the point of a sharp knife for compliance with 3.6.

5. PREPARATION FOR DELIVERY

(Fed. Std. No. 102 shall be referred to for definitions and application of the various levels of packaging and packing for civil agency procurements.)

5.1 Packaging. Packaging shall be level A or C as specified, (see 6.2).

5.1.1 *Level A or B.* Each can shall be packaged in a snug-fitting fiberboard box conforming to type I or II, class 1, style RSC of PPP-B-636. Each fiberboard box, when required, shall be provided with scored or die-cut corrugated fiberboard sheets to immobilize the contents. The fiberboard shall be made from the same material specified herein, except that the bursting strength of the fiberboard shall be 275 p.s.i. Each fiberboard box shall be closed in accordance with the appendix of the box specification.

5.1.2 *Level C.* Each can shall be packaged in accordance with the industry's practice.

5.2 Packing. Packing shall be level A, B, or C as specified, (see 6.2).

5.2.1 *Level A.* Four cans of the same size, type I, or two cans of type II, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard container conforming to class 2, V3c or V3s, style RSC of PPP-B-636. Each shipping container shall be closed, waterproofed by means of tape and reinforced with flat steel strapping or tape banding in accordance with the appendix of the container specification.

5.2.2 *Level B.* Four cans of the same size, type I, or two cans of type II, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard container conforming to type I or II, class 1, style RSC of PPP-B-636, except that the bursting strength of the fiberboard shall be 275 p.s.i. All flaps of the fiberboard shipping container shall be securely sealed with an adhesive commercially used for the specific product being packed by application throughout the entire area of contact between the flaps, or by a combination of metal stitching the bottom flaps and sealing the top flaps with adhesive.

5.2.3 *Level C.* Cans, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.

5.3.1 *Civil agencies.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 *Military requirements.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The flammable waste cans covered by this specification are to provide safe temporary storage within buildings, of oily waste rags and other similar combustible waste materials.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(*a*) Title, number and date of this specification.

(*b*) Type and size required (see 1.2 and 3.4.1).

(*c*) When preproduction sample is required (see 3.1).

(*d*) Color required (see 3.6).

(*e*) Marking requirements if other than specified (see 3.7).

(*f*) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 Level B packaging. When level B packaging is specified for civil agency procurement, the requirements of 5.1.1 level A packaging shall apply.

6.4 Deletion data. The following types and sizes of flammable waste cans specified in RR-C-144b, dated August 25, 1953 have been deleted from this specification:

Type I—Foot operated
Size B—8 gallons
Size D—14 gallons
Size E—21 gallons
Size F—30 gallons
Type II—Hand operated
Size A—6 gallons
Size B—8 gallons
Size C—10 gallons
Size D—14 gallons
Size F—30 gallons

6.4 Transportation description. Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Cans, oiled waste, with or without covers, sheet steel.
Carload weight 14,000, 20,000 or 30,000 pounds, subject to Rule 34, Uniform Freight Classification.

Motor:

Cans, oiled waste, not otherwise indexed, with or without covers, sheet steel.
Truckload minimum weight 10,000 pounds, subject to Rule 115, National Motor Freight Classification.

MILITARY CUSTODIANS:

Army—GL

Navy—YD

Air Force—69

Interested activities:

Review

Army—GL

Navy—YD

Air Force—69

User

Army—EL, MO, MD

Navy—CG

Preparing activity:

Army—GL

Review/User information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing Of DOD Standardization Documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.