RR-C-114D
November 3, 1969
SUPERSEDING
Fed. Spec. RR-C-114C
September 21, 1964

FEDERAL SPECIFICATION

CANS, FLAMMABLE WASTE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers metal foot and hand operated flammable waste cans.

1.2 Classification.

1.2.1 Types and sizes. Flammable waste cans shall be of the following types and sizes, as specified (see 6.2).

Type I	-	Foot operated.
Size	-	6-gallon.
Size	-	10-gallon.
Type II	-	Hand operated.
Size	-	21-gallon.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-601	-	Boxes, Wood, Cleated Plywood.
PPP-B-636	-	Box, Fiberboard.

Federal Standards:

Fed. Std. No. 123	-	Marking for Domestic Shipment (Civilian Agencies).
Fed. Std. No. 595	-	Colors.

FSC 7240

Source: https://assist.dla.mil -- Downloaded: 20261O-26T12:08Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal Specification, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other Federal Specifications required by actitivies outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Fransisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications Standards and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-130	-	Identification Marking of U.S. Military Property.

(Copies of Military standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

Underwriter's Laboratories, Inc. (UL) Standards:

Standard No. 32 - Waste Cans (1954).
Accident, Automotive and Burglary Protection Equipment List.

(Copies of UL publications are available from the Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, Illinois 60611; 1285 Walt Whitman Road, Melville, L.I., New York 11746; or 1655 Scott Boulevard, Santa Clara, Californ 95050.)

National Classification Board:

National Motor Freight Classification.

(Application for copies should be addressed to the National Classification Board, 1616 P Street, N. W., Washington, D. C. 20036.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:08Z
Check the source to verify that this is the currentversion before use.

Uniform Classification Committee:

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

American Society for Testing and Materials (ASTM) Standard:

A90-Method of Test for Weight of Coating on Zinc-Coated (Galvanized) Iron or Steel Articles.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103).

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups, and using Federal agencies)

3. REQUIREMENTS

3.1 First article sample. When specified (see 6.2), before production is commenced, a sample can shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.2 Standard product. The flammable waste cans shall be standard commercial items of the manufacturers except for any changes necessary to conform to the requirements specified herein.

3.3 Safety standard. Flammable waste cans shall conform to Underwriters' Laboratories, Inc. Standard No. 32 for Waste Cans.

3.3.1 Certification. Prior to approval of the preproduction sample, if one is submitted, or prior to approval of the first shipment, the supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that the flammable waste cans he proposes to furnish under this specification meet the requirements of UL Standard No. 32. Acceptable evidence of meeting the requirements of this standard shall be the UL label, a listing in the UL "Accident, Automotive, and Burglary Protection Equipment List" or a certified test report from a recognized independent testing laboratory, acceptable to the Government indicating that the cans offered have been tested and conform to the requirements of UL Standard No. 32.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

3.4 Materials. The material for all sheet-metal members of the cans shall be zinc-coated (galvanized) sheet steel, tin-coated sheet steel, lead-coated sheet steel (terneplate), or uncoated sheet steel, unless one particular material is specified (see 6.2).

3.4.1 Material thicknesses and diameters. The thickness of sheet steel, the diameter of reinforcing wire for the can body, and the diameter of wire for bail and handles, shall be as shown in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

TABLE I. Thickness and diameter dimensions for material and various can sizes

Size (minimum capacity)		Thickness of sheet steel before coating, and equivalent U.S. standard gage, (minimum)						Reinforcements		Bails or 1/ handles, diameter of steel wire (minimum)	Leg 2/ thickness and width (minimum)
		Body		Bottom		Cover		Body wire diameter in top bead (minimum)	Thickness and width of steel straps (minimum)		
Gallons	Cubic Inches	Inch	Gage No.	Inch	Gage No.	Inch	Gage No.	Inch	Inch	Inch	Inches
6	1,386	0.0179	26	0.0179	26	0.0239	24	0.148	0.109 x 1	1/4	0.108 x 7/8
10	2,310	.0218	25	.0218	25	.0281	23	.148	0.109 x 1	1/4	0.108 x 7/8
21	4,851	.0239	24	.0239	24	.0299	22	.172	1/8 x 1	*5/16	3/16 x 1-1/4

1/ Steel forgings, if used, shall have a diameter or minimum dimensions not less than that shown; castings, if used, shall be not less than 3/16 inch thick.

2/ Cast (malleable iron) legs, if used, shall be not less than 3/16 inch thick.

* Applies to handles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

3.4.2 Screws, bolts, and tinners rivets. Screws, bolts, and tinners rivets shall conform to industry practice for use with either uncoated sheet steel or galvanized sheet steel end item fabrications, as applicable.

3.5 Design and construction. The design and construction of the flammable waste cans covered herein, shall conform to the requirements specified hereinafter. The screws, bolts, or rivets specified in 3.4.2 shall be used with washers, or be headed-over. Screw, bolt, or rivet ends with or without plain or lock washers, as applicable shall be so headed that nut or fastener ends will not work loose.

3.5.1 Seams. The vertical body panel seam and the bottom panel seam shall be formed and joined in accordance with UL Standard No. 32 for Waste Cans. Formed seams shall be not less than 1/4-inch in width, and shall have a metal overlap of not less than 1/8-inch. All seams shall be sealed with solder except where hot dipped galvanize or electric seam welding is used. The bottom and lower 6 inches of the body shall not leak when tested as specified in 4.4.1.

3.5.2 Dimensions and capacities. The capacity and height dimension shall be as shown in table II. On round cans the inside diameter shall be not less than 90 percent of the inside height of the body measured to the nearest 1/16 inch. The inside dimensions of the triangular or square can shall be proportional to the depth to maintain the proper stability of the can (see 3.5.3.10).

TABLE II. Height and capacities

Maximum inside height (inches)	Minimum capacities (gallons)
13-3/8	6
15-1/2	10
19-15/16	21

3.5.3 Details of components.

3.5.3.1 Body panel. The body panel shall be fabricated from sheet material specified in 3.4. The panel shape shall be round, trianglular with rounded corners, or square with rounded corners. The panel shall be formed from a single sheet with the ends joined as specified in 3.5.1.

3.5.3.2 Bottom panel. The bottom panel shall be fabricated from the same type material as the body panel (see 3.5.3.1). The panel shall be formed from a single sheet and joined to the body panel as specified in 3.5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

3.5.3.3 Body panel top edge reinforcement. The top edge of the body panel shall be (1) beaded or curled over the reinforcing wire specified in table I (2) curled over without wire reinforcement to form a rolled rim or curl not exceeding 1/4-inch diameter or (3) the top edge shall be reinforced with full circumferential steel strap as specified in table I. The strap shall be either riveted or spot-welded to the body. If riveted, the rivets shall be spaced on not more than 4-inch centers. If spot welded, the welds shall be spaced on not more than 2-inch centers.

3.5.3.4 Cover, single moveable type or two-section type. There shall be either a single moveable cover arranged to completely enclose the waste compartment, or a two section cover with one moveable section hinged to the other stationary section. The single moveable cover shall be reinforced by 2 steel straps as specified in table I, one of which runs parallel to the base of the cover and protects the cover when it is raised against the cover stop. The other strap shall run at right angles to the base of the cover with its length not less than 70 percent of the altitude of cover. This strap may be attached to the underside of the cover. The straps shall be attached to the cover by means of at least 5 spot welds per strap. The cover stop shall be integral with the hinge, or the metal may be embossed around a combination stop or handle and shall bear on a steel reinforcing plate permanently secured to the can body. When the cover is rapidly elevated, the impact on the stop shall not produce any deformation. For the two section cover, the width of the stationary section, measured at right angles to its straight edge shall not exceed one-third of the inside dimension of the body measured at the widest point. The stationary section shall be either (1) flanged or rolled over the outside of the body, and reinforced on the top surface with a riveted or welded steel strap, or (2) flanged and embossed to provide substantial reinforcement. The bottom surface shall be reinforced with a steel strap or embossing at right angles to the top strap. The top strap shall form a rigid stop for the moveable section and may serve as a carrying handle. Ends of the straps shall be permanently secured to the body. The rim of the moveable section shall be flanged to overlap the end of the body and the flanged edge shall be rolled or curled.

3.5.3.5 Cover hinge. The cover hinge shall be arranged to maintain the cover in alignment and permit free movement. Hinge pins shall be of the full-length type or of the rivet type. Full-length hinge pins shall have a diameter of not less than 0.156 inch on 6 and 10-gallon cans and not less than 0.172 inch on the 21-gallon can. Rivets, if used for hinge pins, shall have a body diameter of not less than 3/16-inch. Hinge pins shall be headed or mechanically secured to prevent lateral movement. The total length of the hinge pin bearings in the moveable sections and in the stationary sections of the hinge shall be not less than 1/6 of the longest inside dimension of the can. The thickness of the metal forming the hinge body shall be not less than the thickness of the metal used for the cover. Separate hinges of the two-piece cover shall have a metal thickness of not less than 3/64 inch.

Source: https://assist.dla.mil -- Downloaded: 20260-26T12:08Z
Check the source to verify that this is the current version before use.

3.5.3.6 Cover-lifting handle (type II). The type II can, shall be provided with (1) a curved or looped rigid cover-lifting handle, integral with a reinforcing steel strap of the moveable cover top and arranged for conveniently elevating the cover top, or (2) a pressed steel handle, free from sharp edges, not less than 1-inch wide at the center and with a grip length of not less than 1-1/4 inches. The pressed steel handle shall be not less than 0.0359-inch thick (No. 20 U.S. Standard gage) and shall be either riveted or spotwelded to the cover. If riveted, there shall be 2 or more rivets; if welded there shall be 4 or more spot welds.

3.5.3.7 Foot-operated, cover-lifting device (type I). The type I can shall be provided with a foot-operated cover-lifting device. The device shall consist of a foot pedal, horizontal treadle beam member, and upright lift member. Application of foot pressure on the pedal, with the heel in contact with the floor shall elevate the cover to its maximum height. The foot pedal, horizontal treadle beam member, and the upright lift member shall be steel, not less than 0.108-inch thick, and shall not visibly deform when the cover is rapidly elevated by operation of the foot pedal. The pivots of pivoted members shall have a body diameter of not less than 3/16-inch, and shall be either headed at the ends or provided with split cotter pins in a manner to insure a permanent pivoted joint.

3.5.3.8 Side and top handles or bail. The type I cans shall be provided with either a single rigid top handle, handle and stop combined, pivoted bail, or two pivoted side handles. The type II can shall be provided with two side handles. The rigid top handle shall be intergral with, and the same size as, the top reinforcing steel strap of the stationary section of the cover (see 3.5.3.4), and, at the option of the supplier, may be used to serve as the stop for the moveable cover. The bail shall be formed from zinc-coated (galvanized) wire. Bail shall be attached to the can fabricated from uncoated sheet steel after the can is coated as specified in 3.6. The bail shall be secured to the can body with metal clips. The bail, in any position, shall not interfere with the free movement of the cover. Side handles shall be castings, forgings, formed sheet steel, or formed wire rod. The opening in the top handle and side handles shall be not less than 1-1/2 inches wide and not less than 3-1/2 inches long.

3.5.3.9 Clips. Clips for attaching the bail and side handles shall be sheet steel, not less than 0.0538-inch thick (No. 18 U.S. Standard gage) and riveted or welded to the body. On 6-gallon cans, each clip shall be fastened to the body with 2 or more rivets, or with 4 or more spot welds. On 10-gallon and 21-gallon cans, each clip shall be fastened to the body with 3 rivets, or with 6 or more spot welds. Rivets shall have a nominal body diameter not less than 1/8 inch.

3.5.3.10 Supports. The cans shall have (1) three or more pressed-steel, strap-steel, or malleable-iron legs shaped to provide flat floor rests equally spaced around the bottom panel, or (2) a cylindrical support suitably perforated for venting. The support shall raise the bottom panel so as to provide a clearance between the floor and the bottom panel of not less than 3 inches and not more than 4 inches. Each leg shall be either spot welded at three or more points

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:08Z
Check the source to verify that this is the currentversion before use.

or riveted with three or more rivets to either or both the body or bottom panel. The bottom cylindrical support shall be integral with the body panel or shall be a separate steel cylindrical ring. When integral with the body, the edge of the body panel shall have a hollow rolled rim 1/4 inch diameter. When a separate steel ring is attached, it shall be (1) not less than 1/8 inch thick and not less than 1-3/4 inches wide or (2) have a hollow rolled rim or curl 1/4 inch diameter, or (3) be beaded over or curled over the reinforcing wire specified in table I. The ring shall be either riveted or spot welded to the can body panel. The rivets or spot welds of the legs or cylindrical ring, shall withstand a shear load of 500 pounds when tested as specified in 4.4.4. There shall be at least eight 1 inch diameter holes in the cylindrical support below the bottom panel or the equivalent area opening in not less than three holes. When tested as specified in 4.4.5 the empty can shall not tip over.

3.6 Finish. Unless otherwise specified (see 6.2) cans shall be sprayed with a solvent-resistant yellow enamel matching color number 13538 of Fed. Std. No.595. The zinc and terneplate surfaces shall be prepared for painting prior to application of the enamel. The finish shall be free from cracks, chips, wrinkles, blisters, and uncoated areas. If fabricated from uncoated sheet steel, completed cans, without bails attached, shall be cleaned, loose scale and rust removed, and all surfaces inside and outside, shall be completely coated with zinc by the hot dip process. Weight of the zinc coating shall be not less than 2 ounces per square foot, total on both sides, determined by the test method specified in 4.4.2.1, or the thickness of the zinc coating shall be not less than 0.002 inches (one face) when tested as specified in 4.4.2.2. The coating shall remain tight when tested as specified in 4.4.3.

3.7 Marking. Unless otherwise specified (see 6.2) the method of marking shall be in accordance with MIL-STD-130. All cans shall be permanently marked to show capacity or trade number indicating the capacity together with either the manufacturer's name or a readily identifiable trademark, and the instruction notice in large block letters "EMPTY EVERY NIGHT" located on the side of the can.

3.8 Workmanship. The zinc coating shall be smooth, continous, and thorough, and free from acid or black spots, dross, or flux. The enamel coating shall be free from cracks, chips, wrinkles, lumps, blisters, gritty, or uncoated areas. There shall be no binding or catching that will prevent the foot-operated cover-lifting device from elevating the cover. The bail shall swing freely in the clips and shall not interfere with the free movement of the cover.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. When a preproduction sample is required, it shall be examined for defects in table III and dimensions specified and shall be tested in accordance with 4.4.1 through 4.4.5. Failure to pass tests specified in 4.4.1 through 4.4.5 shall be cause for rejection of the preproduction sample. The presence of any defects listed in table III or any dimension not within specified requirement shall be cause for rejection of the preproduction sample.

4.3 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications and standards to the extent specified or, if none, in accordance with this specification.

4.3.2 In-process inspection.

4.3.2.1 In-process examination. Inspection shall be made during the manufacturing process to determine whether cleaning and removing of loose scale and rust prior to zinc coating is accomplished or galvanizing is accomplished prior to enameling as required by 3.6. Whenever nonconformance is noted, correction shall be made to affected items and lot in process.

4.3.2.2 In-process zinc-coat testing. Zinc-coat weight testing shall be performed on the end item in accordance with 4.4.2.1, or three test specimens, 2-1/4 inches square minimum, made from the same material as the can body and cover and prepared as specified in 3.6, shall be prepared on each lot or batch of hot-dip zinc, or when any change occurs in the hot-dip process. Failure to meet the zinc-coat weight requirements of 3.6 shall be cause for rejection of the process. Alternatively, the zinc coating thickness of the end item may be tested as specified in 4.4.2.2.

4.3.3 End item inspection. The lot shall consist of all complete cans of one type and size, offered for inspection at one time. The sample unit shall be one completely fabricated can.

4.3.3.1 Visual examination. The end item shall be examined for defects in accordance with table III. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects, and 6.5 for total defects expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Coating not as specified.	X	
	Coating not smooth, continous or thorough.		X
	Not free of lumps, blisters, gritty or uncoated areas, acid or black spots, dross or flux.		X
	Enamel (if applicable) not type or color.		X
	Area of no film.		X
	Not continous, not smooth, or not adherent.		X
	Cracked, blistered, chipped.		X
Construction workmanship (general)	Any component missing.	X	
	Any component not fabricated as specified.	X	
	Body panel not formed of one piece or not joined as specified.		X
	Bottom panel not joined to body as specified.		X
	Not provided with carrying handle or handles as specified.		X
	Vertical body seam, bottom panel seam and rivets with beads on inside of waste compartment, except for rivets in cover, not fabricated as specified.	X	
	Body panel ends not joined as specified.		X
	Circumferential steel-strap reinforcement missing or not attached as specified.	X	
	Any part malformed, bent, out of shape, warped, or mispositioned.	X	
	Any component not securely mounted or attached as specified.	X	
	Any component fractured or split.	X	
	Any sharp edge, projection or sliver.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects (con.)

Examine	Defect	Classification Major	Minor
Construction and workmanship (general) (cont'd)	Top edge of can body not reinforced as specified.	X	
	Wire reinforcement not completely inclosed within a rim rolled around the entire periphery of the body (if applicable).		X
	Steel-strap reinforcement not riveted or spot welded to body (if applicable).		X
Foot-operated, cover-lifting device (type I)	Not provided with foot-operated cover-lifting device.	X	
	Foot-operated lifting device does not function as specified.		X
	Application of foot pressure on foot pedal does not elevate the cover to its maximum height.		X
	Foot pedal lifting device members show deformation when cover is rapidly elevated.	X	
Cover-lifting handle (type II)	Not provided with a curved or looped rigid cover lifting handle.		X
	Handle not integral with a reinforcing steel strap of the movable cover top or not arranged for conveniently elevating the cover top.		X
	Pressed steel handle not free of sharp edges (if applicable).	X	
	Pressed steel handle not riveted or spot welded to cover (if applicable).	X	
	Not riveted with two or more rivets or four spot welds (if applicable).		X
Cover, single section types I and II (if applicable)	Cover not arranged to completely enclose waste compartment.	X	
	Cover not stiffened with straps and not spot welded as specified.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects (con.)

Examine	Defect	Classification Major	Minor
Cover, single section, types I and II (if applicable) (cont'd)	Cover stop not of substantial construction, not integral with the hinge, or does not bear on steel reinforcing plate secured to can body.	X	
Cover, two section (types I and II) (if applicable)	Cover-lifting device binds.	X	
	Stationary section of cover not flanged or rolled over the outside of the body.	X	
	Stationary section not reinforced on the top surface by a steel strap, either by riveting or welding, or not flanged and embossed.	X	
	Stationary section not reinforced on the bottom surface with a welded or riveted steel strap, or embossing at right angles to the top strap.		X
	Top reinforcing strap does not form a rigid stop for the moveable section, or does not serve as a carrying handle.		X
	Ends of strap not permanently secured to the body.	X	
	Rim of the moveable section not flanged to overlap the end of the body or the flanged edge not rolled or curled.		X
Cover hinges (types I and II)	Not arranged to maintain cover in alignment or does not permit free movement of cover.	X	
	Pins not headed or mechanically secured to prevent lateral movement.	X	
Side and top handles or bail (types I and II)	Not provided with type handles specified.	X	
	Rigid top handle not integral with, or the same size as the top reinforcing strap of the stationary section of cover.		X
	Pivoted bail or side handles not secured to can body with metal clips.	X	
	Pivoted bail in any position interferes with free movement of the cover.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects (con.)

Examine	Defect	Classification Major	Minor
Clips (types I and II)	Clips for attaching bail or side handles not riveted or welded to the body.	X	
	Not fastened to body by two or more rivets or four or more spot welds (6-gallon cans).	X	
	Not fastened to body by three or more rivets or by six or more spot welds (10- and 21-gallon cans).	X	
Legs or cylindrical support (types I and II)	Legs not shaped to provide flat floor rest, or enclosed support not suitably perforated for venting.	X	
	Each leg not riveted to the body or bottom panel, or to a reinforcing strap with one or more rivets.	X	
	Cylindrical support not riveted to, or integral with the body panel, or bottom edge not reinforced as specified.	X	
	Steel reinforcing strap not riveted or spot welded to the support as specified.	X	
	Rivets or spot welds not spaced as specified.		X
Riveting (as applicable)	Rivet missing where required.	X	
	Rivet not spaced as specified.		X
	Loose, cracked, or not formed properly.	X	
	Any burrs or fins.		X
Welding (as applicable)	Omitted where required, not fused, burned through, cracked, fractured, or not complete.	X	
	Spot weld broken, missing where required, or welds not spaced as specified.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects (con.)

Examine	Defect	Classification Major	Minor
Screws and bolts (when applicable)	Not provided with lock washers, or not headed over nut in a manner that cannot work loose.	X	
Identification marking	Missing, illegible, incomplete, or not as specified.		X

4.3.3.2 Examination for defects in dimensions. Examination shall be made of cans for defects in dimensions. Any dimensions not within the specified requirements shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

4.3.3.3 End item testing. Testing of the completely finished cans shall be performed in accordance with table IV for the characteristics shown therein. Any nonconformance shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

TABLE IV. End item testing of cans

Characteristic	Requirement paragraph	Test paragraph	Requirement applicable to individual unit	Sample unit	Inspection
Oil tightness	3.5.1	4.4.1	X	One can	Pass or fail
Thickness of zinc coating	3.6	4.4.2.1 or 4.4.2.2	X	One can	Pass or fail
Coating adhesion	3.6	4.4.3	X	One can	Pass or fail
Legs or support (steel strap)	3.5.3.10	4.4.4	X	One can	Pass or fail
Stability	3.5.3.10	4.4.5	X	One can	Pass or fail

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

4.3.4 Examination of preparation for delivery requirements. An examination shall be made to determine that packaging, packing and marking requirements of section 5 are complied with. Defects shall be scored in accordance with table V. The sample unit shall be one shipping crate or container fully prepared for delivery, with the exception that it need not be sealed. The lot shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

TABLE V. Examination of packaging, packing, and marking

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Not type, class, style, or grade container as specified.
Workmanship	Incomplete blocking or cushioning. Sealing of container flaps not effected, as applicable. Strapping not secured, as specified, when applicable.
Contents	More or less than required.

4.4 Tests.

4.4.1 Oil tightness. The can shall be filled with kerosene oil or any liquid that has low surface tension comparable to that of kerosene to a height of 6 inches above the highest level of the bottom panel, and allowed to stand in an upright position for 2 minutes. Examination shall be made to determine compliance with 3.5.1.

4.4.2 Zinc coating. If the zinc coating weight test specified in 4.3.2.2 is not performed during process, the coating thickness test shall be performed on the end item in accordance with 4.3.2.1 or 4.3.2.2 to determine conformance to 3.6.

4.4.2.1 Weight. The weight of zinc coating shall be determined to nearest 0.01 oz. in accordance with ASTM A90.

4.4.2.2 Thickness. The thickness of the zinc coating shall be checked to the nearest 0.0001 with a magnetic type gage in accordance with industry's standard commercial practice. Readings shall be taken on the inside surface of one can or cover and on the outside surface of the next can or cover tested, alternating throughout the testing of the samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

4.4.3 Tightness of zinc coating. The zinc coating on each can to be tested shall be scraped in several areas with the point of a sharp knife to determine compliance with 3.6.

4.4.4 Weld or rivet strength test. The welds or rivets on the legs or supporting ring shall be subjected to a shear load by placing a 500 pound weight on the closed lid of the can, and the weight allowed to remain for 5 minutes. Examination shall then be made to determine rivets or spot welds do not shear off (see 3.5.3.10).

4.4.5 Stability test. The empty can shall be placed in upright position on an inclined surface which forms an angle of 30° with the horizontal to determine compliance with 3.5.3.10.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified, (see 6.2).

5.1.1 Level A. Each can shall be packaged in a snug-fitting fiberboard box conforming to type CF or SF class domestic, style RSC of PPP-B-636. Each fiberboard box, when required, shall be provided with scored or die-cut corrugated fiberboard forms to immobilize the contents. The fiberboard forms shall be made from the same material as specified herein, except that the bursting strength of the fiberboard shall be minimum 275 p.s.i. Each fiberboard box shall be closed in accordance with the appendix of the box specification.

5.1.2 Level C. Each can shall be packaged to afford adequate protection against damage during shipment from the supply source to the receiving activity. The supplier's standard practice is acceptable when it fulfills these requirements.

5.2 Packing. Packing shall be level A, B, or C as specified, (see 6.2).

5.2.1 Level A. Four type I cans of the same size, or two type II cans packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard container conforming to V2s, style RSC-L of PPP-B-636. Each shipping container shall be closed, waterproofed by means of tape, and reinforced with flat steel strapping or tape banding in accordance with the appendix of the container specification. Alternatively, containers conforming to overseas type style A, B, or J of PPP-B-601 may be used.

5.2.2 Level B. Four type I cans of the same size or two type II cans packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard container conforming to type CF or SF, class domestic, style RSC of PPP-B-636, except that the bursting strength of the fiberboard shall be 275 p.s.i. Closure shall be in accordance with method II of the appendix of the container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

5.2.2.1 When specified (see 6.2) the shipping container shall be grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with appendix of PPP-B-636.

5.2.3 Level C. Cans, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification rules or National Motor Freight rules, as applicable.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The flammable waste cans covered by this specification are to provide safe temporary storage of oily waste rags and other similar combustible waste materials within buildings.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type and size required (see 1.2.1).
(c) First article. When a preproduction sample is required (see 3.1).
(d) Whether a particular material is required (see 3.4).
(e) When enameling is not required or when other than yellow color is required (see 3.6).
(f) Marking requirements if other than specified (see 3.7).
(g) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(h) When weather resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 Level B packaging. When level B packaging is specified for civil agency procurement, the requirements of 5.1.1 level A packaging shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

MILITARY CUSTODIANS:

Army - GL
Navy - YD
Air Force - 84

Review activities:

Army - MD

User activities:

Army - SM

Preparing activity:

Army - GL

CIVIL AGENCIES INTEREST:

DC
GSA
JUS
VA

Project No. 7240-0133

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.