RR-C-140
December 13, 1962

FEDERAL SPECIFICATION

CASH BOX, STEEL

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 **Scope.** This specification covers a steel cash box with a cover, handle, cantilever tray, and lock and keys, primarily intended for holding cash (see 6.1).

1.2 **Classification.**

1.2.1 *Type.* The cash box shall be of but one type.

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

Federal Specifications:

QQ-C-320—Chromium Plating (Electrodeposited).
QQ-N-290—Nickel Plating (Electrodeposited).
QQ-S-698—Steel, Sheet and Strip, Low-Carbon.
QQ-W-461—Wire, Steel, Carbon, (Round, Bare and Coated).
TT-C-490—Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.
PPP-B-636—Box, Fiberboard.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).
Fed. Std. No. 595—Colors.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards and Handbooks from established distribution points in their agencies.)

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.
MIL-STD-130—Identification Marking of U. S. Military Property.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 **Materials.** Materials used in the cash box shall conform to the applicable specifications and requirements specified hereinafter. When materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice.

3.1.1 *Steel sheet.* The steel sheet shall be 24-gage (Manufacturers' Standard; 0.0239 inch, nominal) and shall conform to cold-rolled, commercial or drawing quality (as applicable), of QQ-S-698.

3.1.2 *Steel wire.* The steel wire shall conform to finish 1, annealed or annealed in process, Steel Number 1020 of QQ-W-461.

3.2 **Construction.**

3.2.1 *Cash box.* The cash box shall be not less than 11 inches long by 7¼ inches wide by 4¼ inches deep. The box shall be fabricated of sheet steel and shall be of seamless deep-drawn; seam weld; or lap and spot-weld construction, having rounded corners, a hinged cover, handle, a cantilever tray containing not less than five nor more than seven compartments, and lock with keys. The body of the box shall have a blunt lip or returned edge at a proper distance from the top-edge to serve as a stop for the cover. The cover shall be fitted to the body of the box by means of two fast pin hinges or a continuous piano-type hinge which extends to approximately 1¾ inches from each end of the box and cover. Hinges shall be securely spot welded to the cover and body. The cover shall contain a recessed handle receptacle in the center, attached to a riveted flat plate.

3.2.1.1 *Handle.* The handle shall be of not less than 3/16-inch-diameter steel wire and shall be inserted underneath the flat plate in such manner as to allow a pivot on a 180 degree radius from the front to the rear of the cover.

3.2.1.1.1 *Flat plate.* The flat plate used to hold the handle in the recessed part of the cover shall be fabricated of sheet steel. The plate shall be finished as specified in 3.3.1.

3.2.1.2 *Cantilever tray.* The cantilever tray shall be fabricated of sheet steel and shall be attached to the body of the box by two arms, one located at each end of the box, and by riveting the rear of tray securely to the cover, to permit tray to pivot, smoothly and without friction, when the cover is raised. The tray shall have a round or flat bottom, and the front and rear lips of tray shall be rolled.

3.2.1.2.1 *Cantilever arms.* The two arms for the cantilever tray shall be fabricated of sheet steel except that the thickness shall be 18-gage (Manufacturers' Standard; 0.0478 inch, nominal).

3.2.1.3 *Lock and keys.* Each cash box shall be equipped with a spring snap-type lock and two milled keys. The two milled keys shall be taped in place inside one of the compartments of the cantilever tray. The lock shall be designed so as to secure the box cover, making it unnecessary to lock the box when being carried. The lock shall be finished as specified in 3.3.1.

3.2.1.4 *Rivets.* The rivets used for attaching the cantilever tray, arms, and the flat plate for the handle shall be of the type used in standard commercial practice.

3.3 **Finish.** All interior and exterior exposed surfaces, except plated hardware of cash boxes, shall be cleaned and pretreated for final finishing in accordance with TT-C-490. Enamel or lacquer, or enamel with top coat of lacquer, shall be used for the final coating of such surfaces and shall be of a material and applied in accordance with standard commercial practice. The minimum total dry finished film thickness shall be not less than 1.0 mil when tested in accordance with 4.3.1. The finish shall be smooth and uniform, without runs, wrinkles, blisters, grit, or foreign matter, lumpy

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T12:09Z
Check the source to verify that this is the currentversion before use.

areas, areas of thin or no film, or separation of color.

3.3.1 *Hardware.* All hardware, if not finished as specified in 3.3, shall be provided with a plated finish in accordance with class 1, type III of QQ-N-290, or in accordance with class 1, type I of QQ-C-320.

3.3.2 *Color.* The color of the finish shall be gray, conforming to color chip No. 26134 of Fed. Std. No. 595 (see 6.3).

3.4 **Workmanship.** Edges of all parts and sheets of cash boxes shall be protected by folding, beading, flanging, or grinding, as necessary, to eliminate possible injury from burrs or raw edges. Cash boxes shall be free from any defects which affect the appearance or which might affect the durability and serviceability of the items.

3.5 **Identification marking.** Unless otherwise specified (see 6.2), each cash box shall be permanently marked on the inside in a plain and legible manner with the specification number, Federal stock number, date of manufacture (month and year), contractor's name or trademark, and the contract or order number. When specified (see 6.2), identification marking shall be in accordance with MIL-STD-130.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 **Inspection responsibility.** Unless otherwise specified (see 6.2), the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order (see 6.2). The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 **Sampling and inspection for acceptance.** Sampling and inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter. For purposes of sampling, an inspection lot for acceptance inspection and tests shall consist of all cash boxes submitted for inspection and delivery at one time.

4.2.1 *Inspection of components and materials.* In accordance with 4.1, the supplier is responsible for insuring that components and materials used were manufactured, inspected and tested in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or, if none, in accordance with this specification. In the event of conflict, this specification shall govern.

4.2.2 *Inspection of the end item.*

4.2.2.1 *Examination of the end item.* Examination of the end item shall be accordance with the classification of defects set forth below and the inspection levels and acceptable quality levels (AQL's) as specified in 4.2.2.1.3. The lot size, for the purpose of determining the sample size in accordance with MIL-STD-105, shall be expressed in units of cash boxes for examination under 4.2.2.1.1 and 4.2.2.1.2, and in units of shipping containers for examination under 4.2.3.

4.2.2.1.1 *Examination of the end item for defects in appearance, construction, and workmanship.* The sample unit for examination specified in table I shall be one cash box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE I.

Examine	Defects
Construction and appearance:	
Cash box.	Cash box not of seamless deep-drawn; seam weld; or lap and spot-weld construction.
	Corners not rounded.
	Body of box does not have blunt lip or returned edge (see 3.2.1) to serve as stop for cover.
	Hinges not securely spot-welded to the cover and body.
	Cover not provided with recessed handle receptacle and not fitted to body as specified (see 3.2.1).
	Handle missing or not as specified (see 3.2.1.1); does not pivot through a 180 degree arc.
	Not provided with spring snap-type lock; lock does not have two milled keys; keys not in specified location; lock not designed to secure box cover in unlocked position.
Cantilever tray.	Cantilever tray not constructed as specified (see 3.2.1.2); not attached to body of box by two arms; rear of tray not riveted to cover.
	Tray does not pivot when cover is raised; does not pivot smoothly and without friction.
	Front and rear lips of tray not rolled.
Finish and workmanship.	Finish not as specified (see 3.3); not smooth and uniform; areas of thin or no film; separation of color.
	Runs, wrinkles, blisters, lumpy areas, grit, or foreign matter in finish.
	Edges of all parts and sheets not protected as specified (see 3.4).
	Raw metal edge or burr not removed.
Color.	Color of finished box not as specified (see 3.3.2).
Marking for identification.	Identification marking missing, incomplete, incorrect, or not otherwise in accordance with requirements.

4.2.2.1.2 *Examination of the end item for dimensional defects.* The sample unit for this examination shall be one cash box. Any dimension not within established tolerances shall be classified as a defect.

4.2.2.1.3 *Inspection levels and acceptable quality levels (AQL's) for examinations.* The inspection levels for determining the sample size and the acceptable quality levels (AQL's), expressed in defects per hundred units, shall be as specified in table II.

TABLE II.

Examination paragraph	Inspection level	AQL
4.2.2.1.1	I	2.5
4.2.2.1.2	L-4	4.0
4.2.3	L-4	4.0

4.2.2.1.4 *Testing of the end item.* The end item shall be tested in accordance with 4.3.1 for thickness of final coating (see 3.3). The sample unit shall be one cash box from each lot presented for examination. Five sample units, randomly selected, shall be tested from each lot with no evidence of failure to meet the requirements of 3.3.

4.2.3 *Examination of preparation for delivery.* The sample unit for examination specified in table III shall be one shipping container, fully packed, selected just prior to the closing operation. Shipping containers fully prepared for delivery shall be examined for closure defects.

4.3 **Test.**

4.3.1 *Thickness of final coating.* The thickness of final coating of cash box shall be determined to the nearest 0.0001 inch by standard commercial methods for compliance with 3.3. Five determinations shall be made on each cash box.

5. PREPARATION FOR DELIVERY

Fed. Std. No. 102 shall be referred to for definitions and application of the various levels of packaging and packing specified hereinafter for civil agency procurement.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE III.

Examine	Defects
Marking for shipment.	Omitted, incomplete, incorrect, illegible; of improper size, location, sequence, or method of application.
Material.	Component missing, damaged, or otherwise defective.
Closure and workmanship.	Closure not as specified; inadequate application of components such as incomplete closure of container flap, loose or missing strapping or tape, as applicable; bulging or distortion of containers.
Content (quantity).	Number of cash boxes per package and shipping container not as required.

5.1 **Packaging.** Packaging shall be level A, B or C, as specified (see 6.2).

5.1.1 *Level A or B.* Each cash box, with keys secured as specified in 3.2.1.3, shall be individually packaged in a snug-fitting fiberboard box conforming to type I or II, class 1, style RSC of PPP-B-636, except that the minimum bursting strength of the fiberboard shall be 175 p.s.i. and closure of the box shall be in accordance with the appendix thereto.

5.1.2 *Level C.* Unless otherwise specified (see 6.2), cash boxes shall be packaged in accordance with the industry's standard practice.

5.2 **Packing.** Packing shall be level A, B or C, as specified (see 6.2).

5.2.1 *Level A.* Six cash boxes, packaged as specified in 5.1.1, shall be packed flat in the most compact manner in a snug-fitting fiberboard shipping container conforming to class 2, V3c or V3s, style RSC of PPP-B-636. Each shipping container shall be waterproofed by means of tape, closed and reinforced with flat steel strapping or tape banding in accordance with the appendix to the container specification.

5.2.2 *Level B.* Six cash boxes, packaged as specified in 5.1.1, shall be packed in a snug-fitting, new fiberboard shipping container conforming to type I or II, class 1, style RSC of PPP-B-636. Containers shall have a minimum bursting strength of 200 p.s.i. and shall be closed in accordance with the appendix to the box specification.

5.2.3 *Level C.* Unless otherwise specified (see 6.2), cash boxes, packaged as specified in 5.1.2, shall be packed in accordance with standard commercial practice and in a manner to insure carrier acceptance and safe delivery at destination. Shipping containers shall comply with the carrier rules and regulations applicable to the mode of transportation.

5.3 **Marking.**

5.3.1 *Civil agencies.* In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked as follows:

5.3.1.1 *Unit packages.* Unit packages shall be marked on one end or side with applicable Federal Stock Number; Federal Item Identification, quantity contained (e.g., 1-EACH); the name or trademark of the manufacturer; and applicable contract or order number, in accordance with Fed. Std. No. 123.

5.3.1.2 *Shipping containers.* Shipping containers shall be marked in accordance with Fed. Std. No. 123, including gross weight.

5.3.2 *Military agencies.* In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

5.4 **Standard pack (civil agencies).** The standard pack requirements, including marking for shipment, for the commodity covered by this specification shall be as specified in 5.1.1 (level B), 5.2.2, and 5.3.1. (See 6.2.1.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Cash boxes covered by this specification are intended to be used in offices or mail rooms for the storage of cash, stamps, and unclassified papers. It is not intended that the cash boxes afford any degree of protection against unauthorized entry or pilferage.

6.2 Ordering data. Purchasers should exercise any desired options offered herein (see 3.5, 5.1.2, and 5.2.3) and procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) Identification marking required if other than as specified (see 3.5).

(c) Inspection responsibility *(for civil agencies only)* if other than as specified herein; and administrative provisions for inspection records, when applicable (see 4.1).

(d) Packaging and packing levels and any special marking for shipment required (see 5.1, 5.2, and 5.3).

6.2.1 *Standard pack (civil agencies).* The standard pack for cash boxes, including marking for shipment, shall be as specified in 5.1.1 (level B), 5.2.2, and 5.3.1. The standard pack provisions are intended for use in procurement of Stores Stock replenishments. Procuring officers should use the standard pack provisions when it is known that the material will be shipped from a supplier to a domestic warehouse, supply depot, or immediate storage point for temporary storage, subsequent issue, and/or shipment to eventual user (see 5.4).

6.3 Availability of color chips. Individual 3- by 5-inch color chips (Fed. Std. No. 595) are available from the Business Service Center, Federal Supply Service, General Services Administration, Washington 25, D. C., or from the Business Service Center of the nearest GSA Regional Office. (Price, 5 cents each.)

6.4 Transportation data. Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Boxes, tool, steel, not otherwise indexed by name. Carload minimum weight 20,000 pounds, subject to Rule 34, Uniform Freight Classification.

Motor:

Boxes, tool, steel, truckload minimum weights — 10,000, 14,000, 20,000, 30,000 and 36,000 pounds, subject to Rule 115, National Motor Freight Classification.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

MILITARY INTEREST:

Army—Q
Air Force—MOA

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.