RR-C-00140A (GSA-FSS)
December 29, 1969
INTERIM REVISION OF
Fed. Spec. RR-C-140
December 13, 1962

INTERIM FEDERAL SPECIFICATION

BOX, CASH, STEEL

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D.C. 20406, based upon currently available technical information It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to Federal Specification RR-C-140, dated December 13, 1962.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a steel cash box primarily intended for holding cash. The cash box shall be of one type.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

L-P-395 - Plastic Molding, Polystyrene.
L-P-1105 - Plastic Molding Material, Acrylonitrile-Butadiene-Styrene (ABS) Rigid.
QQ-C-320 - Chromium Plating (Electrodeposited).
QQ-N-290 - Nickel Plating (Electrodeposited).
QQ-S-698 - Steel, Sheet and Strip, Low-Carbon.
QQ-W-461 - Wire, Steel, Carbon, (Round Bare and Coated).
TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.
PPP-B-636 - Box, Fiberboard.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed. Std. No. 187 - Identification of Pressed Bends, Forms, Seams and Joints (Sheet Metal).
Fed. Std. No. 595 - Colors.

(Activities outside the Federal Government may obtain copies of Federal Specification, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specification procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Classification Board:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, N.W., Washington, D. C. 20036.)

Uniform Classification Committee:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Material. The material used in the manufacture of the cash box shall conform to the applicable specifications and requirements specified hereinafter. When the material is not definitely specified, it shall be suitable for the intended purpose and of the quality normally used in commercial practices.

3.1.1 Sheet steel. The base, cover, cantilever arms, hinges, and flat plates shall be manufactured from cold, or hot rolled commercial quality sheet steel conforming to QQ-S-696. At the option of the contractor, the cantilever tray shall be fabricated from cold, or hot rolled commercial quality sheet steel conforming to QQ-S-698, or plastic (see 3.1.3).

3.1.2 Steel wire. The handle shall be manufactured from 3/16 inch diameter steel wire, plus or minus 1/64 inch, and shall conform to finish 1, annealed or annealed in process, American Iron and Steel Institute (AISI), Number 1020 of QQ-W-461.

3.1.3 Plastic. When plastic cantilever trays are used, the material shall meet or exceed the property values established for type I or III of L-P-396, or type I or IV of L-P-1183.

3.2 Design. The cash box shall consist of a base, cover, cantilever tray, handle, and lock. The cash box shall be so designed and constructed to withstand heavy usage.

3.3 Construction.

3.3.1 Base, cover and hinges. The base and cover shall be fabricated from sheet steel as specified in 3.1.1 with a minimum thickness of 0.021 inch, and shall be of seamless deep-drawn, seamweld, or lap and spot-weld construction, at the option of the manufacturer. The hinges shall be fabricated from sheet steel as specified in 3.1.1 with a minimum thickness of 0.032 inch. Bends, forms, seams and joints required in the fabrication of the cash box shall conform to Fed. Std. No. 187. The base shall have a blunt lip, or returned edge to serve as a stop for the cover. Two or more fast pin hinges with at least four knuckles each, or a continuous hinge shall be spot-welded to the base and cover. The knuckles shall have a minimum width of 0.1875 inch each. The hinge(s) shall be so attached to insure that the cover lands evenly and squarely on the lip or edge of the base, when tested as specified in 4.4.1.1. When the cash box is suspended by the handle no vertical opening greater than 1/16 inch shall be visible between the base and cover. The cover shall open a minimum of 90 degrees, and not more than 115 degrees. All corners of the base and cover shall be rounded, and all corners and edges shall be smooth. The rounded corners shall be formed at a 90° angle with a minimum 1/8 inch radius at the bend.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

3.3.1.1 Cantilever tray and arms. At the option of the manufacturer the cantilever tray shall be fabricated from sheet steel or plastic. The metal cantilever tray and arms shall be fabricated from sheet steel as specified in 3.1.1, with a minimum thickness of 0.021 inch for the tray and 0.044 inch for the arms. The plastic cantilever tray shall be fabricated from plastic as specified 3.1.3, and shall be of such thickness, design and construction to withstand the test requirements as specified in 4.4.2 without shattering, chipping, cracking, crazing or breaking. The cantilever tray shall have not less than five, nor more than seven compartments. The bottom edges and corners of the tray shall be rounded, and the front shall have a minimum slope of 15 degrees to the vertical. The tray shall be securely attached to the base by two riveted arms, and to the cover by rivets only. The tray shall be so installed to permit the tray to pivot smoothly and without friction when the cover is opened or closed and tested as specified in 4.4.1.1.

3.3.1.2 Handle and flat plate. The handle shall be manufactured from steel wire, as specified in 3.1.2. The flat plate shall be fabricated from sheet steel as specified in 3.1.1 with a minimum thickness of 0.021 inch, and finished as specified in 3.6.1. The handle and flat plate shall be so fabricated and installed to permit the handle to pivot on a 180 degree radius, and shall be located at center point of cover to permit proper balance when carried. The flat plate shall be securely riveted to the cover in the recessed handle receptacle. The handle receptacle shall be sufficiently recessed to insure that handle and flat plate are flush with, or slightly below, the surface of the cover.

3.3.1.3 Lock and keys. Each cash box shall be equipped with a spring, snap-type lock and two milled or stamped keys. The lock shall be so designed to secure the base and cover, making it unnecessary to lock the box when being carried. The lock shall be finished as specified in 3.6.1. The two keys shall be taped inside the cash box to prevent their loss during shipment.

3.3.1.4 Rivets. The rivets shall be suited for the intended purpose, and shall be of good commercial quality.

3.4 Dimension. The outside dimensions of the cash box shall be not less than 11 inches wide, 7-1/4 inches deep, and 4-1/4 inches high, exclusive of any protruding lip, or returned edge which serves as a stop for the cover.

3.5 Color. The color of the base, cover, and metal cantilever tray shall be gray, conforming to Color Chip No. 26152 of Fed. Std. No. 595, or commercial gray. The color of the plastic cantilever tray shall conform to the above stated color requirements, or commercial black.

3.6 Finish. All metal interior and exterior surfaces, except plated hardware, shall be cleaned and pretreated for final finishing in accordance with TT-C-490. Enamel or lacquer, or enamel with top coat of lacquer shall be used for the final coating of the surface. The material and application of the finish shall be in accordance with standard commercial practice. The minimum total dry finished film thickness shall be not less than 1.0 mil, when tested in accordance with 4.4.1.2. The finish shall be smooth and uniform, without runs, wrinkles, blisters, grit, or foreign matters, lumpy areas, areas of thin or no film or separation of color.

3.6.1 Hardware. The lock, handle and flat plate shall be finished in accordance with class 1, type III of QQ-N-290, or in accordance with class 1, type I of QQ-C-320.

3.7 Identification marking. Unless otherwise specified, each cash box shall be legibly and permanently marked with the name or trademark of the manufacturer. When specified, any additional marking specified in the invitation for bids, contract, or order, shall be included in the marking.

3.8 Workmanship. All cash boxes shall be free from defects and imperfection which may affect appearance or serviceability, or may constitute a personal hazard to the user. The cash box shall be free from sharp edges, burrs, dents, cracks, chips, blisters, gouges, uneven finish, rust, and faulty construction.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Inspection and testing of materials. The supplier is responsible for insuring that materials are manufactured, examined and tested in accordance with this specification or referenced subsidiary specifications, standards and other documents.

4.1.2 Evidence of compliance. In lieu of using his own facilities, the contractor may submit a report of analysis of materials from a laboratory acceptable to the Government, whether an independent test facility or laboratory of raw material supplier, as evidence of compliance with the specification requirements. The report of analysis shall include, in addition to the actual test data, the manufacturer's name, the name and address of the testing laboratory, date of test(s) and quantity of material represented by the test report. When a report of analysis is submitted, the Government reserves the right to check test to determine the validity of the analysis.

4.2 Sampling.

4.2.1 Size of lot. All cash boxes presented for delivery at one time shall be considered a lot for the purpose of inspection and tests.

4.2.2 Sampling and inspection for acceptance. Sampling and inspection shall be performed in accordance with MIL-STD-105.

4.2.3 Sampling for visual and dimensional examination. Random sample of cash boxes shall be taken from each lot in accordance with MIL-STD-105. The sample unit shall be one cash box. The cash boxes shall be examined for defects listed in table I. The Inspection Level shall be S-3 and the Acceptable Quality Level (AQL) shall be 4.0 percent defective.

4.2.4 Sampling for preparation for delivery. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. The sample shall be examined for defects listed in table II. The lot size shall be the number of shipping containers in the end-item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defect per hundred units.

4.2.5 Sampling for end-item tests. Random sample of cash boxes for each test shall be taken from each lot in accordance with MIL-STD-105. The sample unit shall be one cash box. The cash boxes shall be tested as specified in 4.4. The inspection level shall be S-2 and the AQL shall be 4.0 percent defective.

4.3 Examination.

4.3.1 Visual and dimensional examination. Samples taken in accordance with 4.2.3 shall be examined for defects listed in table I. Any cash box having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for that sample the lot represented by the sample shall be rejected.

TABLE I. Visual and dimensional defects

Examine	Defects
Material	Material not as specified (see 3.1, 3.1.1, 3.1.2, and 3.1.3). Material thickness not as specified.
Construction	Cash box not of seamless deep drawn, seamweld, or lap and spot-weld construction (see 3.3.1). Corners not smooth and not formed at a 90° angle with a minimum 1/8 inch radius (see 3.3.1). Base of cash box does not have blunt lip or returned edge to serve as stop for cover (see 3.3.1). Hinges not as specified (see 3.1.1).

Source: https://assist.dla.mil -- Downloaded: 20261O-26T12:09Z
Check the source to verify that this is the currentversion before use.

TABLE I. Visual and dimensional defects (con.)

Examine	Defects
Construction (con.)	Hinge(s) not securely attached to base and cover (see 3.3.1). Cover of cash box not provided with recessed handle receptacle (see 3.3.1.2). Cantilever tray not constructed as specified (see 3.3.1.1). Tray not attached to base and cover as specified (see 3.3.1.1). Handle does not pivot as specified (see 3.3.1.2). Handle not fitted to cover as specified (see 3.3.1.2). Lock not designed as specified (see 3.3.1.3). Lock does not have two milled or stamped keys (see 3.3.1.3).
Dimension	Cash box not of the dimensions specified (see 3.4).
Color	Color not as specified (see 3.5).
Finish	Finish not as specified (see 3.6 and 3.6.1).
Identification marking	Not as specified (see 3.7).
Workmanship	Not in accordance with 3.8.

4.3.2 Examination of preparation for delivery. Samples selected in accordance with 4.2.4 shall be examined for defects listed in table II to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Marking for shipment	Omitted, incomplete, incorrect, illegible; of improper size, location, sequence, or method of application.
Material	Component missing, damaged, or otherwise defective.
Closure and workmanship	Closure not as specified; inadequate application of components such as incomplete closure of container flaps, loose or missing strapping or tape, as applicable; bulging or distortion of containers.
Content (quantity)	Number of cash boxes per package and shipping container not as specified.

4.4 Test.

4.4.1 End item test. Samples selected in accordance with 4.2.5 shall be subjected to the following tests. Any cash box in the sample failing one or more tests shall be considered defective. If the number of defective cash boxes exceeds the acceptance number for the sample, the lot represented by the sample shall be rejected.

4.4.1.1 Operational test. Open and close cash box ten times to assure compliance with the requirements stated in 3.3.1.1.

4.4.1.2 Thickness of final coating. The thickness of the final coating of the cash box shall be determined to the nearest 0.0001 inch by standard methods for compliance with 3.6. Five determinations shall be made on each cash box. Any thickness determination of less than 1.0 mil shall constitute failure of the test sample unit.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the current version before use.

4.4.2 Impact test (for cash boxes with plastic cantilever trays only). One cash box shall be selected at random and subjected to the following test to insure compliance with the requirements stated in 3.3.1.1. Noncompliance shall be cause for rejection of the entire lot. Five rolls of U. S. quarters, or five units of equivalent weight shall be placed in five compartments, oneroll or unit per compartment. The weighted cash box shall be placed on a table thirty inches high, plus or minus five inches, and pushed off the table to a concrete floor six times. Position the box so that it will hit the floor at different angles at each drop.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Each cash box, with keys secured as specified in 3.3.1.3, shall be individually packaged in a snug-fitting fiberboard box conforming to PPP-B-636, class domestic, style RSC, except that the minimum bursting strength of the fiberboard shall be 175 p.s.i. and closure of the box shall be in accordance with the appendix thereto.

5.1.2 Level B. Each cash box, with keys secured as specified in 3.3.1.3, shall be individually packaged in a snug-fitting folding paperboard box of the type normally used in industry practice.

5.1.3 Level C. Unless otherwise specified (see 6.2), cash boxes and keys (3.3.1.3) shall be packaged in accordance with standard industry practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Six cash boxes, packaged as specified in 5.1.1, shall be packed in a close-fitting box conforming to PPP-B-636, V3c or V3s. The box shall be closed, waterproofed, and strapped in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Six cash boxes, packaged as specified in 5.1.2 shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The boxes shall be closed in accordance with the appendix to PPP-B-636.

5.2.3 Level C. The cash boxes packaged in accordance with 5.1 shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, unit packages and shipping container shall be marked as follows:

5.3.1.1 Unit packages. Unit packages shall be marked on one end or side with applicable Federal Stock Number; Federal Item Identification, quantity contained (e.g., 1-EACH); the name or trademark of the manufacturer; and applicable contract or order number, in accordance with Fed. Std. No. 123.

5.3.1.2 Shipping containers. Shipping containers shall be marked in accordance with Fed. Std. No. 123, including gross weight.

5.3.2 Military agencies. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The cash box covered by this specification is intended to be used in offices or mail rooms for the storage of cash, stamps, and unclassified papers. It is not intended that the cash box afford protection against unauthorized entry or pilferage.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in the procurement documents:

(a) Title, number and date of this specification.
(b) Identification marking required if other than specified.
(c) Packaging and packing levels and any special marking for shipment required.

6.3 Sample color chips. Sample color chips are available from the Regional Business Service Centers, Federal Supply Service, General Services Administration, Washington, D.C. 20407.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the currentversion before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, fold, staple, and mail.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

RR-C-00140A(GSA-FSS) Box, Cash, Steel

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*
11. NAME AND TITLE OF SUBMITTER	12. DATE

FORM GSA FEB 69 2200

GSA DC 70-8030

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the current version before use.

FOLD

GENERAL SERVICES ADMINISTRATION

OFFICIAL BUSINESS



POSTAGE & FEES PAID
GENERAL SERVICES ADMINISTRATION

General Services Administration
Federal Supply Service (FMSO)
Washington, D. C. 20406

FOLD

GSA FORM FEB 68 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.