RR-P-125B
September 16, 1975
SUPERSEDING
Fed. Spec. RR-P-125A
October 5, 1961

FEDERAL SPECIFICATION

PARTS CLEANING CAN, SAFETY, BENCH

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers bench-type safety cans for containing flammable or solvent liquids used in the cleaning or swabbing of small parts.

1.2 Classification. The cans shall be of the following sizes, as specified (see 6.2):

Sizes:

1 - quart
2 - quart
2 - gallon
3 - gallon

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

QQ-P-416	-	Plating, Cadmium (Electrodeposited)
QQ-W-428	-	Wire, Steel, Carbon (High Carbon, Round for Mechanical Springs, General Purpose)
QQ-Z-325	-	Zinc Coating, Electrodeposited Requirements for
TT-C-490	-	Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings

FSC 4940

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the currentversion before use.

TT-E-489	-	Enamel, Alkyd, Gloss (for Exterior and Interior Surfaces
PPP-P-130	-	Pails, Cans and Waste Receptacles, Packing of

Federal Standard:

FED-STD-595	-	Colors

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers, at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of US Military Property

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

American Society for Testing Materials (ASTM) Standards

A 227 - Steel Wire, Hard Drawn for Mechanical Springs
A 308 - Steel, Sheet, Cold Rolled, Long Terne Coated

(Application for copies may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Factory Mutual (FM) Research Corporation

Approval Requirements for Bench Cleaning Cans

(Application for approval should be addressed to Factory Mutual Engineering and Research Corporation, 1151 Providence Highway, Norwood, MA 02062.)

3. REQUIREMENTS

3.1 Standard product. The parts cleaning cans delivered under this specification shall be the manufacturer's commercial product, except for any changes necessary to comply with the specification requirements. All like items furnished on any one contract, including parts and subassemblies thereof, shall be new and interchangeable.

3.2 Codes and standards. The parts cleaning cans shall comply with the applicable Factory Mutual requirements for bench cleaning cans.

3.2.1 Compliance. Prior to delivery of the first shipment, the supplier shall submit to the contracting officer, or his authorized representative, satisfactory evidence that the parts cleaning can he proposes to furnish under this specification meet the applicable Factory Mutual (FM) requirements for bench cleaning cans. Acceptable evidence of meeting these FM requirements shall be the FM identification mark or a certified test report from a recognized independent testing laboratory, acceptable to the government, indicating that the parts cleaning can has been tested and meets the applicable FM requirements for bench safety cans.

3.3 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial can provided the completed item complies with all provisions of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

3.3.1 Long terne plate. The long terne plate shall conform to ASTM A 308; commercial, drawing, or drawing special killed quality; coating designation LT25. The nominal plate thickness shall be 0.0179 for the one and two quart sizes and 0.0239 for the two and three gallon sizes.

3.3.2 Spring wire. The steel spring wire shall be formed from copper-coated hard drawn steel wire conforming to ASTM A 227 or from zinc-coated or cadmium-plated (see 3.6.2) steel wire conforming to type II of QQ-W-428.

3.4 Design and construction.

3.4.1 Design. The cans shall have a cylindrical body with a removable retainer ring, a hinged cover, and a perforated metal dasher (fire baffle), which is mounted on a coil spring. The two quart, two gallon and three gallon sized cans shall have two handles spot or projection welded to the body and shall have a support stand spot or projection welded to the cover. The carrying handles shall be located directly opposite each other and ninety degrees from the cover hinge. The cover support stand shall position the cover horizontal within ± 5 degrees of the top of the body. The carrying handles and cover stand are not required on one quart size cans. The cans shall show no leakage when tested as specified in 4.4.1. The dasher shall not touch the surface of the liquid when the can is filled to capacity, (see 4.4.2).

3.4.2 Dimensions. The dimensions of the cans shall be as shown in table I for the size specified (see 6.2). The thickness of metal shall be as specified in 3.3.1. The height and diameter of the cans may vary between the limiting dimensions shown.

TABLE I. Can dimensions

Size (minimum capacity)	Height 1/	Diameter	Coil spring wire diameter (nominal) 2/ - 3/
	Inches	Inches	Inch
1-quart	3-1/4 to 4-1/4	5-1/2 to 6-1/2	0.092
2-quart	3-3/4 to 5-3/4	7-1/4 to 8-1/2	.106
2-gallon	6-3/4 to 7-3/4	11-1/4 to 13-1/4	.162
3-gallon	6-3/4 to 7-1/2	13-7/16 to 15-1/2	.192

1/ The height of the can is defined as the distance from the bottom edge to the top of crown portion of the cover.

2/ A 25 percent larger diameter wire is acceptable.

3/ Commercial tolerances apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

3.5 Construction.

3.5.1 Body and bottom. The body and bottom shall each be fabricated from one piece of plate specified in 3.3.1. The seam in the body shall be lapped and welded. The bottom shall be attached to the body by seam-welding or lockseamed and soldered or compounded and lockseamed with the edge rolled over the side to eliminate sharp edges. Alternatively, the body and bottom may be drawn from one sheet of seamless plate. At least two clips, opposite each other, shall be spot or projection welded to the body for engagement with the retainer ring and the clips shall be so positioned for proper retention and release of the retainer ring. The clips shall be fabricated from plate specified in 3.3.1 or from uncoated steel having a thickness not less than that specified for the body.

3.5.2 Retainer ring. The retainer ring shall be formed from one piece of plate specified in 3.3.1. The retainer ring, when assembled to the body, shall be designed to maintain equal and positive pressure on the dasher and coil spring assembly. The ring shall have a discontinued, rolled, outer lip and the ring shal be notched to fit inside the body. The ring shall be retained on the body by the body clips engaging the rolled outer lips of the ring. The ring shall be removable by rotating, thereby disengaging the lips of the retainer ring from the body clips.

3.5.3 Cover. The cover shall be formed from one piece of flat sheet specified in 3.3.1. The cover shall have a flanged rim with a tightly rolled edge with a minimum inside height of one-quarter inch and it shall be dished or crowned at the center for reinforcement. The cover shall be attached to the body by a metal hinge which shall be spot or projection welded to the body and the cover. There shall be at least two welds of 1/4 inch minimum diameter in each hinge half for the one and two quart size cans and at least three welds of 1/4 inch minimum diameter in each hinge half for the two and three gallon size cans. The hinge shall be located astride or beside any body seam. The hinge shall be fabricated of plate as specified in 3.3.1 or from zinc-coated or cadmium-plated (see 3.6.2) sheet steel. The cover shall have a handle (see 3.5.6) spot or projection welded to it. When the can has a cover support stand that may be used as a handle, a separate handle is not required.

3.5.4 Dasher. The dasher shall be formed from one piece of zinc-coated or cadmium-plated (see 3.6.2) sheet steel. The dasher shall be perforated over the entire surface with 0.040 inch $\pm$ .005 diameter holes (150 $\pm$ 50 holes per square inch). The dasher shall have a flanged rim of sufficient depth to enclose the coil spring, and shall be concave at the center to provide a recessed area.

3.5.5 Coil spring. The coil spring shall be formed of one piece of wire as specified in 3.3.2. The spring shall be coiled to an outside diameter which will provide engagement within the dasher.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

3.5.6 Handles and cover support stand. The cover handle, the two carrying handles and the cover support stand shall each be made from one piece of plate specified in 3.3.1, or from uncoated steel having a thickness not less than that specified for the body. The carrying handles and the retaining clips (see 3.5.1) may be fabricated as a carrying handle with two retaining clips from the same piece of material.

3.6 Finish.

3.6.1 Painting. The exterior of the complete assembly shall be cleaned and painted in accordance with 3.6.1.1 thru 3.6.1.2.

3.6.1.1 Pretreatment. The assembly shall be cleaned in accordance with TT-C-490.

3.6.1.2 Outercoat. The cleaned assembly shall have the exterior coated with enamel in accordance with TT-E-489, color red, approximating color number 11105 of FED-STD-595. A yellow band, approximating color number 13655 and one-half inch minimum width, shall be applied at the approximate mid-point of the body.

3.6.2 Plating. Plating shall be class 3, any type, in accordance with QQ-P-416 for cadmium plating and QQ-Z-325 for zinc coating.

3.7 Marking. Each can shall be permanently marked on the body or cover using 1/4 inch minimum characters, showing "US", size, and manufacturer's code identification number, name, or trade mark in accordance with MIL-STD-130.

3.8 Workmanship. All cans shall be free of burrs; slivers; rough die, tool, and grind marks; dents; cracks; dirt; and other extraneous material. Painted and plated areas shall be adherent, smooth, uniform, not tacky, and free of flaking, crinkling, blisters, sags, runs, and areas of no finish. Welds and solder shall be adherent and free from craters.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:09Z
Check the source to verify that this is the currentversion before use.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Material inspection. In accordance with 4.1 above, materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards, unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 In-process inspection.

4.2.2.1 Process examination. Examination shall be made of the following fabrication processes to establish conformance with specified requirements. Whenever nonconformance is noted, correction shall be made to the process and all items processed.

(a) Welding of the body seam and assemblies (see 3.5.1, 3.5.3, and 3.5.6).
(b) Painting of the assembly (see 3.6.1).
(c) Plating of components (see 3.6.2).

4.2.3 End item inspection. The inspection lot shall consist of all bench safety parts cleaning cans of the same size offered for inspection at one time. The sample unit shall be one complete bench safety parts cleaning can.

4.2.3.1 Visual examination. The parts cleaning cans shall be examined for the defects in table II. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for minor defects, expressed in terms of defects per hundred units.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Not painted	X	
	Colors not as specified	X	
	Not painted with yellow band and band not properly located	X	
	Blisters, runs, sags, overspray, not smooth, not uniform, or not continuous film		X
	Tacky (not dry to touch)		X
	Any burrs or slivers	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Design, construction and workmanship	Not specified size	X	
	Any dirt or extraneous material on the interior or exterior		X
	Any dents or cracks	X	
	Any burns or slivers	X	
	Rough die, tool or grind marks		X
	Loose handle or cover stand	X	
	Component missing	X	
Welds	Contains crack or fracture	X	
	Not number specified	X	
	Contains burn hole, splatter, or discoloration	X	
	Evidence of poor fusion	X	
	Any missing weld	X	
Solder	Evidence of poor fusion	X	
Retainer ring	Not notched to fit inside body	X	
	Not retained on ring lip by body clips	X	
	Not removable by rotating	X	
	Does not have rolled edge	X	
	Not dished or crowned		X
Dasher	Not perforated	X	
	Does not enclose coil spring	X	
	Not concave at center	X	
	Will not move freely	X	
Marking	Missing, incomplete, not legible, not specified size, not in proper location		X

4.2.3.2 Dimensional examination. The parts cleaning cans shall be examined for dimensions. Any dimension not within specified limits shall be classified as a defect. The inspection level shall be II with an AQL of 4.0, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the current version before use.

4.2.3.3 Testing of the end item. Each sample parts cleaning can shall be tested as specified in 4.4.1 and 4.4.2. Failure of any sample can to pass any test shall be cause for rejection of the lot. The inspection level shall be S-4.

4.2.4 Inspection of preparation for delivery. Inspection of preparation for delivery shall be performed in accordance with the inspection requirements of PPP-P-130.

4.3 Certificate of compliance. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of conformance with the specification requirements, shall be examined and validated.

4.4 Test methods.

4.4.1 Leak test. The sample can shall be leak tested by filling with the required amount of liquid. The filled can shall remain stable for a minimum of two (2) hours and then examined for leakage. In accordance with 3.4.1, any leakage shall constitute failure and shall be cause for rejection of the lot.

4.4.2 Capacity test. The sample can shall be filled with the specified minimum volume of liquid. Inability of the can to contain the volume, without the liquid touching the dasher, shall constitute failure of the can and shall be cause for rejection of the lot.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.1.1 Levels A, B and C. Cans shall be packed in accordance with the applicable requirements specified for type XIII safety cans of PPP-P-130.

5.1.2 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with the applicable requirements of PPP-P-130.

6. NOTES

6.1 Intended use. The parts cleaning cans covered by this specification are intended for use on work benches for cleaning and draining small parts.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size required (see 1.2).
(c) Selection of the applicable level of packing (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - YD
Air Force - 82

Review activity:

Army - WC

User activities:

Army - CE
Navy - MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA - FSS
HEW - NIH
Interior - BOR
Postal - POS
VA - DMS

Project No. 4940-0357

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 35 cents each.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the current version before use.