RR-P-89G
April 26, 1977
SUPERSEDING
Fed. Spec. RR-P-89F
August 12, 1970

FEDERAL SPECIFICATION

PANS, FRYING, STAINLESS STEEL

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers stainless steel frying pans.

1.2 Classification. The frying pans shall be of the following sizes, as specified (see 6.2).

Size 1 - 6-inch (152 mm) diameter.
Size 2 - 12-inch (305 mm) diameter.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

UU-P-268	-	Paper, Kraft, Wrapping.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing.

Federal Standard:

FED-STD-123	-	Marking for Shipment (Civil Agencies).

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-147	-	Palletized and Containerized Unit Loads, 40" x 48" Pallets, Skids, Runners, or Pallet-Type Base.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Sanitation Foundation (NSF)

Standard No. 2 - Food Service Equipment

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, PO Box 1468, Ann Arbor, MI 48106.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

American Society for Testing and Materials (ASTM) Standard

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The frying pans shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved.

3.2 Codes and standards. The frying pans shall comply with the applicable requirements of NSF Standard No. 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

3.2.1 NSF compliance. Prior to approval of first shipment, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the frying pans he proposes to furnish under this specification meet the applicable requirements of NSF Standard No. 2. Satisfactory evidence of this compliance shall be any of the following:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished frying pan, or

(2) A certification for the frying pans issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the frying pans are procurred, indicating that the frying pans have been tested and conform to NSF Standard No. 2.

3.3 Materials. Materials shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial frying pans provided the completed item complies with all provisions of this specification.

3.3.1 Steel, sheet and strip, stainless. The stainless steel sheet and strip shall conform to type 302 or 304 of ASTM Standard A 167.

3.4 Construction. The frying pans shall be constructed as specified herein and shall conform to the dimensions shown in table I.

TABLE I. Dimensions

Size	Inside diameter at top of body	Outside diameter at bottom of body	Vertical inside depth	Length of handle
	Inches	Inches	Inches	Inches
1	6 to 6-3/4 (152 to 171 mm)	4-1/8 to 4-3/4 (105 to 121 mm)	1-1/8 to 1-1/2 (29 to 38 mm)	5-1/2 to 7-1/2 (140 to 190 mm)
2	12 to 12-3/4 (305 to 324 mm)	8-3/4 to 9-7/8 (222 to 251 mm)	2 to 2-3/8 (51 to 60 mm)	10-1/4 to 12-1/4 (260 to 311 mm)

3.4.1 Body. The body shall be formed seamless from a single piece of material specified in 3.3.1. The body shall have a minimum bottom thickness of 0.072-inch (1.83 mm) for the 6-inch (152 mm) and 12-inch (305 mm) frying pans, after forming.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

3.4.2 Handle. The handle shall be made from a single piece of material specified in 3.3.1. The handle shall have minimum thicknesses of 0.105 inch (2.67 mm) for the 6-inch (152 mm) frying pan and 0.120 inch (3.05 mm) for the 12-inch (305 mm) frying pan, after forming. The handle shall be made slightly concave in cross section and shall be attached to the body by at least three spot welds or continuous welding. When spot welding is used the crevice between the handle end and the body shall be sealed by welding or brazing. A hole shall be provided at the end of the handle for hanging the frying pan. The handle, when tested as specified in 4.3.1, shall not bend from original shape nor separate or show evidence of separation from the body.

3.5 Identification marking. The frying pans shall bear the manufacturer's name, trade name, or trademark of such known characters as to be easily identifiable with the manufacturer. Marking shall be indented on the outside bottom of the pan so as not to be visible on the opposite surface.

3.6 Finish. All rust, dirt, grease, graphite, sharp edges, burrs, or slivers shall be removed.

3.7 Workmanship. The finished frying pans shall be clean and free from any cracks, fractures, or malforming. Welding shall be accomplished in a manner that will prevent the occurrence of pits or flashes. All scale or flux deposits shall be removed from finished welds.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

4.2.2 End item inspection. Frying pans selected in accordance with 4.2 shall be examined in accordance with 4.2.2.1 and 4.2.2.2 and tested in accordance with 4.2.2.3. The sample unit shall be a completely fabricated frying pan.

4.2.2.1 Visual examination. The pans shall be examined for the defects in table II. The inspection level shall be II with an acceptable quality level (AQL) of 2.5, expressed in terms of defects per hundred units.

TABLE II. Classification of defects

Examine	Defect
Finish	Sharp edge, burr, or sliver. Grease, rust, dirt, or other foreign matter embedded in finish.
Design	Any component missing.
Construction and workmanship (general)	Any component cracked, fractured, or malformed. Welding pits or flashes. Scale or flux deposits not removed.
Handle	Handle not attached by spot welding in at least three places or not attached by continuous welding. Hole missing or is not located at end of handle. Crevices not sealed by welding or brazing when handle is spot welded to body.
Body	Not one piece construction.
Marking for identification	Missing, not legible, incomplete. Wrong location or method of application.

4.2.2.2 Dimensional examination. The pans shall be examined for compliance with dimensions specified. Any dimension not within the specification tolerance shall be a defect. The inspection level shall be S-1 with an AQL of 4.0, expressed in terms of defects per hundred units.

4.2.2.3 End item testing. The finished pans shall be tested as specified in 4.3.1. Failure of the test shall be recorded as a defect. The inspection level shall be S-2 with an AQL of 2.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

4.2.3 Packaging inspection. An examination shall be made to determine that preservation-packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be as indicated in table III. The sample unit shall be one shipping container fully prepared for delivery, except it need not be closed. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

TABLE III. Packaging inspection

Examine	Defect
Materials	Component missing, damaged, or not as specified.
Marking	Missing; incorrect; not legible; of improper size, location, sequence, or method of application.
Contents	Number per container is more or less than required.

4.2.3.1 Examination of shipping container. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and strapping shall be in accordance with appendix of PPP-B-636.

4.2.4 Palletization inspection. An examination shall be made to determine that palletization is in compliance with section 5 of this specification. Defects shall be as indicated in table IV. The sample unit for this examination shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads submitted for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5 expressed in terms of defects per hundred units.

TABLE IV. Palletization inspection

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement.
Palletization	Not as specified. Pallet pattern not as specified. Load not banded with straps specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

TABLE IV. Palletization inspection (cont'd)

Examine	Defect
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

4.2.5 Code and standard compliance. Proof of compliance with the requirements of NSF (see 3.2 and 3.2.1) shall be submitted to the Government representative.

4.3 Test.

4.3.1 Handle test. Uniformly distributed weights totaling 1.75 lb (.79 kg) shall be placed on the size 1 pan and 10.75 lbs (4.88 kg) shall be placed on the size 2 pan. The pan shall be supported by the last 3 inches (76.2 mm) of the handle for 5 minutes and subsequently examined to determine conformance with requirements of 3.4.2. Inability to comply with these requirements shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each frying pan shall be completely form-wrapped with minimum 40 pound basis weight kraft paper conforming to type I, grade B of UU-P-268. The wrapping shall be secured in place with gummed paper tape conforming to type III, grade B of PPP-T-45.

5.1.2 Level C. Each frying pan shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Thirty size 1 frying pans or twenty-four size 2 frying pans, packaged as specified in 5.1, shall be nested and packed in the most compact manner in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Each fiberboard container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. Twenty-four size 1 frying pans or twelve size 2 frying pans, packaged as specified in 5.1, shall be nested and packed in the most compact manner in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF, variety SW, or type SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Level C. Frying pans, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall be in accordance with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Palletization (Military requirements). When specified (see 6.2), frying pans packed as specified in 5.2 shall be palletized in accordance with Load Type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. Marking shall be in accordance with 5.4.1 or 5.4.2, as specified (see 6.2).

5.4.1 Civil agencies. Shipping containers shall be marked in accordance with FED-STD-123.

5.4.2 Military requirements. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The frying pans covered by this specification are intended for frying small quantities of food.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Size of frying pan required (see 1.2).
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for Level B packing (see 5.2.2.1).
(e) When palletization is required (see 5.3).
(f) Marking required (see 5.4).

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD
Navy - MS

User activity:

Navy - MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

DMS-VA
GSA-FSS

Project No. 7330-0501

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 35 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.