NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.


MIL-PRF-27/26
4 September 1975


PERFORMANCE SPECIFICATION SHEET

TRANSFORMER, POWER, 3.0 VOLT-AMPERES, 400 HZ, TF5T03ZZ313

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the transformers described herein shall consist of this document and the latest issue of Specification MIL-T-27.




CIRCUIT DIAGRAM AND MARKINGS

| INCHES | MM |
|---|---|
| .030 | 0.76 |
| .032 | 0.81 |
| .138 | 3.51 |
| .250 | 6.35 |
| .600 | 15.24 |
| .750 | 19.05 |
| .800 | 20.32 |
| 1.062 | 26.97 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Tolerance on terminal position dimensions is ±.015 (0.40 mm).
4. Marking shall be on the top of the case.



FSC 5950

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:12Z
Check the source to verify that this is the current version before use.

REQUIREMENTS (When numbers in parentheses, i e , (1-2) are used, they indicate the extreme terminals of the winding)

Electrical ratings

Primary voltage -
(1-2) 115 volts, 400 Hz ±1 percent
Secondary current -
(3-4) 52 mA rms
Secondary voltage -
(3-4) 57 5 volts
Working voltage -
(3-4) 325 volts peak
VA ratings - 3 0 volt-amperes

Design and construction
Dimensions and configuration - See figure
Duty cycle - Continuous
Case - Molded
Material - Diallyl -phthalate (GDI-30F)

Terminals - Pin type, brass-hot solder dip
Terminal height - 25 inch maximum
Weight - 47 grams maximum
Operating temperature range - -55°C to +170°C
Altitude - 70,000 feet maximum

Terminal strength MIL-STD-202, method 211, test condition A, 2 pounds

Dielectric withstanding voltage
At sea level - 910 volts rms
At reduced barometric pressure (70,000 feet) - 407 volts rms

Electrical characteristics
No load - With 115 volts, 400 Hz across (1-2), the current in (1-2) shall not exceed 6 0 mA maximum
Rated load - With 115 volts, 400 Hz across (1-2) and a 52 mA load in (3-4), the voltage across (3-4) shall be 57 5 volts ±3 percent
Efficiency - 75 percent minimum at rated load

Temperature rise 20°C maximum

Marking location See figure

Military part number M27/26-01

Custodians
Army - EI
Navy - EC
Air Force - 85

Review activities
Army - EL, MU
Navy - EC
Air Force - 11, 17, 85
DSA - ES

User activities
Army - ME
Navy - MC, AS
Air Force - 19

Preparing activity
Army - EI

Agent
DSA - ES

(Project 5950-0487)



Source: https://assist.dla.mil -- Downloaded: 202610-16T03:12Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U S.Army Electronics Command
ATTN AMSEL-RD-TS
Fort Monmouth, New Jersey 07703

To detach this form, cut along this line

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:12Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

## SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 22-R255

INSTRUCTIONS This sheet is to be filled out by personnel either Government or contractor involved in the use of the specification in procurement of products for ultimate use by the Department of Defense This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost Comments and the return of this form will be appreciated Fold on lines on reverse side staple in corner and send to preparing activity Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements

SPECIFICATION MIL-T-27/26 TRANSFORMER, POWER, 3.0 VOLT-AMPERES, 400 HZ, TF5T03ZZ313

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
DIRECT GOVERNMENT CONTRACT ( ) SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

( ) YES ( ) NO *(If "yes" in what way?)*

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification If there are additional papers attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

ESC-FM 1068-68

Source: https://assist.dla.mil -- Downloaded: 202610-16T03:12Z
Check the source to verify that this is the current version before use.