INCH-POUND

MIL-PRF-27/37D
AMENDMENT 1
13 November 2015
SUPERSEDING
MIL-PRF-27/37D
5 December 2013

PERFORMANCE SPECIFICATION SHEET

# TRANSFORMERS, POWER, 1.5 VOLT AMPERES, 400 HZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the transformer described herein shall consist of this specification sheet and the latest issue of MIL-PRF-27.




FIGURE 1. Dimensions and configurations

AMSC N/A

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:14Z
Check the source to verify that this is the current version before use.

| Dim | Inches | Millimeters |
|---|---|---|
| A | 1.09 Max | 27.2 |
| B | .800 | 20.32 |
| C | .600 | 15.24 |
| D | .032 ±.002 DIA | 0.81 ±0.05 DIA |
| E | .25<br>.13 | 6.4<br>3.3 |
| F | .47 Max | 15.0 |
| G | .03<br>.02 | 0.8<br>0.5 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Tolerance on terminal position dimensions is ±.005 (0.13 mm).
4. Marking shall be on the side of the case.
5. A white dot shall be marked on the side opposite the terminals, over terminal 1, in addition to the terminal marking shown.
6. Secondary electrical values shall be marked as specified in table I, as applicable.

FIGURE 1. Dimensions and configurations – continued.

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings: See table I.

Primary voltage (1-2): 115 volts ±10 percent, 400 Hz ±5 percent.

Design and construction:

Dimensions and configuration: See figure 1.

Weight: .85 ounce, maximum.

Duty cycle: Continuous.

Case: Plastic encapsulated.

Material: Plastic.

Altitude: 70,000 feet, maximum.

Operating temperature range: -55°C to +130°C.

Terminals: Printed circuit pins - tinned brass.

Terminal strength: MIL-STD-202, method 211, test condition A, 2 pounds.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:14Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage:

At sea level: 2.8 times the maximum working voltage specified in table I.

At reduced barometric pressure: 1.25 times the maximum working voltage specified in table I.

Electrical characteristics:

No load: With 115 volts rms, 400 Hz across (1-2): Current in (1-2) shall not exceed 1.5 mA rms.

Rated load: With 115 volts rms, 400 Hz across (1-2) and a resistive load with current as specified in table I in (3-5), the voltage across (3-5) shall be as specified in table I.

Efficiency: 70 percent minimum at rated load.

Polarity: Additive with terminals 2 and 3 connected.

Regulation: $\frac{\text{Voltage (no Load) - Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100$

shall not exceed 23 percent.

Phase shift: 1.0 electrical degree between primary and secondary voltage at rated load, maximum.

Temperature rise: 17°C, maximum.

Vibration: MIL-STD-202, method 204, test condition D.

Marking location: See figure 1.

VERIFICATION

Extent of qualification

Qualification testing and approval to M27/37-44 A or B, M27/42-44 A or B, and M27/46-44 A or B shall be sufficient to grant qualification approval to MIL-PRF-27/37 through MIL-PRF-27/47 inclusive, all parts.

Qualification testing and approval to M27/37-44 shall be sufficient to grant qualification approval to M27/37-01 through M27/37-44.

Part or Identification Number (PIN): M27/37-01 A or B.






Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:14Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings.

| Dash No. | Secondary voltage (3-5) (V rms) ±3% | Secondary current (3-5) (amps rms) | Working voltage (V rms) (MAX) |
|---|---|---|---|
| 01 A or B | 6 | 0.250 | 325 |
| 02 A or B | 6.3 | 0.238 | 325 |
| 03 A or B | 7 | 0.214 | 325 |
| 04 A or B | 7.5 | 0.200 | 325 |
| 05 A or B | 8 | 0.188 | 325 |
| 06 A or B | 9 | 0.167 | 325 |
| 07 A or B | 10 | 0.150 | 325 |
| 08 A or B | 11 | 0.136 | 325 |
| 09 A or B | 12 | 0.125 | 325 |
| 10 A or B | 12.6 | 0.119 | 325 |
| 11 A or B | 13 | 0.115 | 325 |
| 12 A or B | 15 | 0.100 | 325 |
| 13 A or B | 16 | 0.094 | 325 |
| 14 A or B | 18 | 0.083 | 325 |
| 15 A or B | 20 | 0.075 | 325 |
| 16 A or B | 22 | 0.068 | 325 |
| 17 A or B | 24 | 0.063 | 325 |
| 18 A or B | 26 | 0.058 | 325 |
| 19 A or B | 28 | 0.053 | 325 |
| 20 A or B | 30 | 0.050 | 325 |
| 21 A or B | 33 | 0.045 | 325 |
| 22 A or B | 36 | 0.042 | 325 |
| 23 A or B | 39 | 0.038 | 325 |
| 24 A or B | 43 | 0.035 | 325 |
| 25 A or B | 47 | 0.032 | 325 |
| 26 A or B | 51 | 0.029 | 325 |
| 27 A or B | 56 | 0.027 | 325 |
| 28 A or B | 62 | 0.024 | 325 |
| 29 A or B | 68 | 0.022 | 325 |
| 30 A or B | 75 | 0.020 | 325 |
| 31 A or B | 82 | 0.018 | 325 |
| 32 A or B | 91 | 0.016 | 325 |
| 33 A or B | 100 | 0.015 | 325 |
| 34 A or B | 110 | 0.014 | 325 |
| 35 A or B | 115 | 0.013 | 325 |
| 36 A or B | 120 | 0.0125 | 325 |
| 37 A or B | 130 | 0.0115 | 325 |
| 38 A or B | 150 | 0.010 | 325 |
| 39 A or B | 180 | 0.0085 | 325 |
| 40 A or B | 200 | 0.0075 | 440 |
| 41 A or B | 220 | 0.007 | 440 |
| 42 A or B | 240 | 0.006 | 440 |
| 43 A or B | 270 | 0.0055 | 580 |
| 44 A or B | 300 | 0.005 | 580 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:14Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-STD-202.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5950-2015-027)

Review activities:
Army - CR4, MI
Navy - AS, MC, OS
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:14Z
Check the source to verify that this is the current version before use.