INCH-POUND

MIL-PRF-27/41D
26 April 2013
SUPERSEDING
MIL-PRF-27/41C
25 September 2009

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 6 VOLT AMPERES, 400 HZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the transformer described herein shall consist of this specification sheet and MIL-PRF-27.





MAX W.V. , "X"V"
MAX ALT 70 .000

(SEE TABLE I FOR VALUE OF "X")

CIRCUIT DIAGRAM AND MARKING

Inches	mm
.002	0.05
.02	0.5
.03	0.8
.032	0.81
.13	3.3
.138	3.51
.25	6.4
.600	15.24
.75	19.1
.78	19.8
.800	20.32
1.09	27.2

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Tolerance on terminal position dimensions is ±.005 (0.13 mm).
4. Marking shall be on the side of the case.
5. A white dot shall be marked on the side opposite the terminals, over terminal 1, in addition to the terminal marking shown.
6. Secondary electrical values shall be marked as specified in table I, as applicable.

FIGURE 1. Dimensions and configurations

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:15Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When numbers in parentheses, such as (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings: See table I.

Primary voltage (1-2): 115 volts ±10 percent, 400 Hz ±5 percent.

Design and construction:

Dimensions and configuration: See figure 1.

Weight: 1.65 ounces, maximum.

Duty cycle: Continuous.

Case: Plastic encapsulated.

Material: Plastic.

Altitude: 70,000 feet, maximum.

Operating temperature range: -55˚C to +130˚C.

Terminals: Printed circuit pins - tinned brass.

Terminal strength: MIL-STD-202, method 211, test condition A, 2 pounds.

Dielectric withstanding voltage:

At sea level: 2.8 times the maximum working voltage specified in table I.

At reduced barometric pressure: 1.25 times the maximum working voltage specified in table I.

Electrical characteristics:

No load: With 115 volts rms, 400 Hz across (1-2): Current in (1-2) shall not exceed 6 mA rms.

Rated load: With 115 volts, 400 Hz across (1-2) and a resistive load with current as specified in table I in (3-5), the voltage across (3-5) shall be as specified in table I.

Efficiency: 81 percent minimum at rated load.

Polarity: Additive with terminals 2 and 3 connected.

Regulation: $\frac{\text{Voltage (no Load) - Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100$

shall not exceed 12 percent.

Phase shift: 1.0 electrical degree between primary and secondary voltage at rated load, maximum.

Temperature rise: 25˚C, maximum.

Vibration: MIL-STD-202, method 204, test condition D.

Marking location: See figure 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:15Z
Check the source to verify that this is the current version before use.

VERIFICATION

Extent of qualification

Qualification testing and approval to M27/37-44 A or B, M27/42-44 A or B, and M27/46-44 A or B shall be sufficient to grant qualification approval to MIL-PRF-27/37 through MIL-PRF-27/47 inclusive, all parts.

Qualification testing and approval to M27/41-44 shall be sufficient to grant qualification approval to M27/41-01 through M27/41-44.

Part or Identification Number (PIN): M27/41-01 A or B.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:15Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings.

Dash No.	Type designation	Secondary voltage (3-5) (V rms) ±3%	Secondary current (3-5) (amps rms)	Working voltage (V rms) (MAX)
01 A or B	576	6	1.100	325
02 A or B	577	6.3	0.953	325
03 A or B	578	7	0.857	325
04 A or B	579	7.5	0.800	325
05 A or B	580	8	0.750	325
06 A or B	581	9	0.667	325
07 A or B	582	10	0.600	325
08 A or B	583	11	0.545	325
09 A or B	584	12	0.500	325
10 A or B	585	12.6	0.476	325
11 A or B	586	13	0.462	325
12 A or B	587	15	0.400	325
13 A or B	588	16	0.375	325
14 A or B	589	18	0.333	325
15 A or B	590	20	0.300	325
16 A or B	591	22	0.272	325
17 A or B	592	24	0.250	325
18 A or B	593	26	0.230	325
19 A or B	594	28	0.214	325
20 A or B	595	30	0.200	325
21 A or B	596	33	0.182	325
22 A or B	597	36	0.167	325
23 A or B	598	39	0.154	325
24 A or B	599	43	0.140	325
25 A or B	600	47	0.128	325
26 A or B	601	51	0.118	325
27 A or B	602	56	0.107	325
28 A or B	603	62	0.097	325
29 A or B	604	68	0.088	325
30 A or B	605	75	0.080	325
31 A or B	606	82	0.073	325
32 A or B	607	91	0.066	325
33 A or B	608	100	0.060	325
34 A or B	609	110	0.055	325
35 A or B	610	115	0.052	325
36 A or B	611	120	0.050	325
37 A or B	612	130	0.046	325
38 A or B	613	150	0.040	325
39 A or B	614	180	0.033	325
40 A or B	615	200	0.030	440
41 A or B	616	220	0.027	440
42 A or B	617	240	0.025	440
43 A or B	618	270	0.022	580
44 A or B	619	300	0.020	580

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:15Z
Check the source to verify that this is the current version before use.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-PRF-27/37	MIL-PRF-27/38	MIL-PRF-27/39	MIL-PRF-27/40
MIL-PRF-27/42	MIL-PRF-27/43	MIL-PRF-27/44	MIL-PRF-27/45
MIL-PRF-27/46	MIL-PRF-27/47	MIL-STD-202	

Custodians:
Army - CR
Navy - EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5950-2013-026)

Review activities:
Army – AV, CR4, MI
Navy - AS, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:15Z
Check the source to verify that this is the current version before use.