
MILITARY SPECIFICATION SHEET

SOCKETS (LEAD, ELECTRONIC COMPONENTS) (TYPE 1, SOLDERLESS WRAP)
LOW INSERTION FORCE (LIF)

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-S-83505



Inches	mm
.025	0.64
.028	0.71
.030	0.76
.035	0.89

FIGURE 1 Socket, lead, (type 1) solderless wrap

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.


Dash number	A ± 010 inch	B ±.010 inch	C Dia inch	D Dia ±.002 inch	E Dia inch
-001 -002	.703	.475	.072	.060	.052
-003 -004	.563	.335	.072	.060	.052
-005 -006	.453	.225	.072	.060	.052
-007 -008	.812	.475	.085	.082	.073
-009 -010	.703	.475	.063 ±.003	.060	.052
-011 -012	.563	.335	.063 ± 003	060	.052
-013 -014	453	.225	.063 ±.003	.060	.052

Inches	mm	Inches	mm	Inches	mm
.002	0.05	.072	1 83	453	11.50
.003	0.08	.073	1.85	.475	12.07
.010	0.25	082	2.08	.563	14 30
052	1.32	.085	2.16	.703	17.86
.060	1 52	.225	5 71	.812	20.62
.063	1.60	.335	8 51		

NOTES:
1. Dimensions are in inches
2. Metric equivalents are given for general information only
3. Unless otherwise specified the tolerance for three place decimals is ± 005 inch (0 13 mm).
4. Part is to be free of burrs or sharp edges except as noted.
5. Dimensions apply after plating
6. For retention design requirements see MIL-S-83505, figure 2.

FIGURE 1 Socket, lead, (type I) solderless wrap, LIF Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.



Minimum wrappable length, -B, inches (see note 5)

Number of wrapped connections	Wire gauge (AWG)						
	30	28	26	24	22	20	18
1	.185 (4 70)	.219 (5.56)	.226 (5.74)	.258 (6.55)	.303 (7.70)	.327 (8.31)	.391 (9.93)
2	.320 (8.13)	.388 (9.86)	402 (10.21)	.466 (11.84)			
3	455 (11.56)						

NOTES
1. Dimensions are in inches
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses
4. Unless otherwise specified the tolerance is ± 005 (0 13 mm)
5. Minimum wrappable length shall have the wrappost geometry in accordance with table IA of MIL-STD 1130

FIGURE 2 Wrapppost configurations and wire gauge length

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.

REQUIREMENTS.

Qualification

Group qualification. Shall be as specified in table I.

Dimensions and configuration Shall be in accordance with MIL-STD-1130, figures 1 and 2 and table II.

TABLE I. Group qualification.

Dash number	Qualification tests
-001, -002, -009, and -010 (as applicable)	Require all qualification tests of MIL-S-83505
-003 through -006 and -011 through -014 (as applicable)	Visual an mechanical tests of MIL-S-83505 and qualification of -001, or -002, or -009, or -010.
-007 and -008 (as applicable)	Groups 1, 2, and 5 of qualification table of MIL-S-83505 and qualification of -001, or -002, or -009, or -010.

TABLE II. Interface dimensions and finish. 1/

Dash number	Recommended mounting hole dia ±.001 inch (.025 mm)	Accepts pin		Sleeve plating
		Length	Diameter	
-001 and -009	.055 (1.40)	175 (4.44)	021 (0.53)	Gold
-002 and -010		.125 (3.18)	.016 (0.41)	Tin/lead
-003 and -011	055 (1.40)	.175 (4 44)	021 (0.53)	Gold
-004 and -012		125 (3.18)	.016 (0 41)	Tin/lead
-005 and -013	.055 (1.40)	.175 (4 44)	.021 (0.52)	Gold
-006 and -014		.125 (3.18)	.016 (0.41)	Tin/lead
-007	076 (1.93)	.281 (7.14)	.030 (0.76)	Gold
-008		156 (3.96)	.020 (0.51)	Tin/lead

1/ Metric equivalents are in parenthesis.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.

Engagement (mating) and separation (unmating) forces shall be in accordance with MIL-S-83505 except as specified in table III.

TABLE III Engagement (mating) force

Dash numbers	Test gauge B (inches/mm)	Mating force (max) (oz/gram)
-001 and -009	.125/3.175	2.00/56.7
-002 and -010		
-003 and -011	.125/3.175	2.00/56.7
-004 and -012		
-005 and -013	.125/3.175	2.00/56.7
-006 and -014		
-007	156/3 96	4 00/113 4
-008		

Terminals: Type I (solderless wrap)

Mounting: Use .046 inch (1.16 mm) minimum thickness mounting board.

Test mounting:

Use glass epoxy board, type G10 material for mounting sockets.

Part or Identifying Number (PIN): M83505/8 - (dash number from table II).

CONCLUDING MATERIAL

Custodians.
Army - CR
Navy - EC
Air Force - 85

Review activities:
Air Force - 17, 99
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5935-3926-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.