METRIC

MIL-DTL-83527/3C
13 January 2004
SUPERSEDING
MIL-C-83527/3B
8 June 1992

DETAIL SPECIFICATION SHEET

CONNECTOR, PLUS, ELECTRICAL, RECTANGULAR, MULTIPLE INSERT TYPE, RACK TO PANEL, ENVIRONMENT RESISTING, 150°C CONTINUOUS OPERATING TEMPERATURE, SHELL SIZE 3

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83527.




FIGURE 1. Connector, plug.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:38Z
Check the source to verify that this is the current version before use.




FIGURE 1. Connector, plug – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:38Z
Check the source to verify that this is the current version before use.




FIGURE 1. Connector plug – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:38Z
Check the source to verify that this is the current version before use.

Datum T	Datum S		
	100.66 (3.963)	100.64 (3.962)	100.61 (3.961)
69.93 (2.753)	0.30 (.012)	0.30 (.012)	0.30 (.012)
69.90 (2.752)	0.30 (.012)	0.30 (.012)	0.30 (.012)
69.88 (2.751)	0.30 (.012)	0.30 (.012)	0.30 (.012)
69.85 (2.750)	0.28 (.011)	0.28 (.011)	0.28 (.010)
69.82 (2.749)	0.25 (.010)	0.25 (.010)	0.25 (.010)
69.80 (2.748)	0.23 (.009)	0.23 (.009)	0.23 (.009)
69.77 (2.747)	0.20 (.008)	0.20 (.008)	0.20 (.008)
100.58 (3.960)	100.56 (3.959)	100.53 (3.958)	100.51 (3.957)
Datum S			
0.28 (.011)	0.25 (.010)	0.23 (.009)	0.20 (.008)
0.28 (.011)	0.25 (.010)	0.23 (.009)	0.20 (.008)
0.28 (.011)	0.25 (.010)	0.23 (.009)	0.20 (.008)
0.25 (.010)	0.23 (.009)	0.23 (.009)	0.20 (.008)
0.23 (.009)	0.23 (.009)	0.20 (.008)	0.18 (.007)
0.23 (.009)	0.20 (.008)	0.18 (.007)	0.18 (.007)
0.20 (.008)	0.18 (.007)	0.18 (.007)	0.15 (.006)

mm	Inches	mm	Inches	mm	Inches	mm	Inches
0.15	.006	3.07	.120	13.54	.533	40.39	1.590
0.18	.007	3.71	.146	14.05	.553	41.02	1.615
0.20	.008	3.88	.153	16.10	.634	41.88	1.649
0.25	.010	3.91	.154	17.91	.705	42.14	1.659
0.30	.012	3.96	.156	18.67	.735	45.14	1.777
0.38	.015	3.99	.157	19.18	.755	45.24	1.781
0.58	.023	4.67	.184	20.70	.815	54.79	2.236
0.76	.030	4.70	.185	21.08	.830	57.30	2.256
1.02	.040	4.78	.188	24.76	.975	60.96	2.4
1.45	.057	4.93	.194	27.69	1.090	80.90	3.185
1.70	.067	5.13	.202	27.74	1.092	100.51	3.957
1.78	.070	5.18	.204	28.24	1.112	100.61	3.961
1.83	.072	5.44	.214	32.64	1.285	100.66	3.963
1.80	.074	5.46	.215	32.79	1.291	100.71	3.965
2.03	.080	5.84	.230	33.27	1.310	100.84	3.970
2.16	.085	5.94	.234	33.76	1.329	109.88	4.326
2.54	.1	8.26	.325	33.96	1.337	110.13	4.336
2.62	.103	10.80	.425	34.06	1.341	120.09	4.728
2.67	.105	12.78	.503	34.46	1.357	120.19	4.732
		13.28	.523			130.81	5.15
						131.32	5.170

NOTES:
1. Dimensions are in millimeters.
2. Inch equivalents are in parentheses.
3. Inch equivalents are given for general information only.

FIGURE 1. Connector, plug – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:38Z
Check the source to verify that this is the current version before use.

REQUIREMENTS


Dimensions and configuration: Shall be in accordance with figure 1.

Contacts: See MIL-C-39029/93, /94, /98, and /100.

Inserts: See DOD-STD-1842 and MIL-C-83527/7.

Mating connector: See MIL-DTL-83527/4.

Part or Identifying Number (PIN) example:



1/ "A" designator for insert with contacts, "B" designator for insert without contacts.

Reference documents. In addition to MIL-DTL-83527, this document references the following:

MIL-C-39029/93
MIL-C-39029/94
MIL-C-39029/98
MIL-C-39029/100
MIL-C-83527/7
MIL-DTL-83527/4
DOD-STD-1842

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:38Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy - AS
Air Force – 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4509-003)

Review activities:
Army - AR, MI
Navy - EC, MC, OS
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online data at http://www.dodssp.daps.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:38Z
Check the source to verify that this is the current version before use.