INCH-POUND


MIL-DTL-83528/3F
w/AMENDMENT 1
21 July 2025
SUPERSEDING
MIL-DTL-83528/3F
13 August 2019

DETAIL SPECIFICATION SHEET

GASKETING MATERIAL, CONDUCTIVE, SHIELDING GASKET, ELECTRONIC, ELASTOMER, EMI/RFI, SOLID "D" SHAPED STRIP

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the gasketing material described herein shall consist of this specification sheet and the latest issue of MIL-DTL-83528.



NOTES:
1. Dimensions are in inches; metric equivalents are given in parenthesis and are for general information only.
2. Tolerance on flash shall be ± .008 (0.20 mm) on the extension and ± .005 (0.13 mm) on the thickness.
3. Length shall be as specified on the purchase order.

FIGURE 1. EMI/RFI "D" shaped strip gasket.

AMSC N/A FSC 5999

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:39Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and interface: See figure 1 and table I.

Material: Type A, B, C, D, E, F, H, J, K, L, or M.

Part or Identifying Number (PIN): See table I.

Supersession information: See table II.

TABLE I. Dimensions.

PIN 1/ M83528/003X	Dimension A ± .005 2/	Dimension B ± .005 2/ 3/	Dimension C ± .005 2/ 3/	Cross section 4/ area (cm^2)
001	.031 (0.78)	.062 (1.57)	.068 (1.73)	.025
002	.047 (1.19)	.094 (2.39)	.078 (1.98)	.041
003	.039 (0.99)	.078 (1.98)	.089 (2.26)	.041
004	.047 (1.19)	.094 (2.39)	.094 (2.39)	.050
005	.031 (0.78)	.062 (1.57)	.100 (2.54)	.037
006	.075 (1.91)	.150 (3.81)	.110 (2.79)	.091
007	.061 (1.55)	.122 (3.10)	.135 (3.43)	.097
008	.059 (1.49)	.118 (3.00)	.156 (3.96)	.109
009	.078 (1.98)	.156 (3.96)	.156 (3.96)	.140
010	.089 (2.26)	.178 (4.52)	.175 (4.45)	.179
011	.094 (2.39)	.188 (4.78)	.188 (4.78)	.203
012	.125 (3.18)	.250 (6.35)	.250 (6.35)	.360

1/ "X" in the PIN shall be replaced by the applicable material type. Complete PIN example: M38528/003A001.
2/ Dimensions are in inches; metric equivalents are given in parenthesis and are for general information only.
3/ For dimensions over .200 the tolerances shall be ± .008.
4/ For calculation of volume resistivity (for reference only).

TABLE II. Supersession information.

PIN 1/ M83528/003X	Superseded DLA Land and Maritime Drawing PIN 85104X 1/
001	002
002	003
003	004
004	010
005	005
006	006
007 /2	007
008	008
009	N/A
010	009
011	012
012	013

1/ "X" in the PIN indicates the applicable material type.
2/ Dimensions of this part are not identical to the superseded part. However, this is an authorized substitution.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:39Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced document. This document references MIL-DTL-83528.

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Preparing activity:
DLA – CC

(Project 5999-2025-002)

Review activities:
Air Force – 19
NSA – NS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:39Z
Check the source to verify that this is the current version before use.