COMMERCIAL ITEM DESCRIPTION

ENVELOPE, MAILING

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification UU-E-525, Style I.

The X-ray mailing envelope shall consist of a large envelope with two inserts and a small envelope glued on the lower right outside.

Salient characteristics:

Both envelopes shall be 100 percent sulfate pulp.

Basis weight (17 x 22-500), ± 5 percent, pounds	32
Bursting strength, minimum, lb/in^2	50
Color and finish - Shall conform to standard sample	

The sealed seams of both envelopes shall be wide enough to ensure strength and sealed to affect permanent adhesion. The seams shall not adhere to the inside of the envelope. Envelopes shall be free from cuts, folds, tears, machine marks, foreign matter, dirt, ink smears, and adhesive stains. Sealing flap adhesive of both envelopes shall be the water-activated type of such a consistency to prevent premature sealing of the flap and curling of the envelope after drying. The flap adhesive shall be uniformly applied and have a minimum thickness of 0.0006 inch. Flaps shall be capable of being quickly and securely sealed using reasonable pressure after moistening of the adhesive. When opened 15 to 20 seconds after sealing, the flap shall pull fibers from the body of the envelope over the entire adhesive area. All adhesive shall be clean and free from offensive odor and ingredients that would discolor the paper.

Both envelopes shall accept printing and ink writing without feathering, smearing, or penetrating to the reverse side.

Large envelope: The large envelope shall be 15 x 18 (±1/8) inch with a sealing flap that shall be a minimum of 2-1/4 inches wide and extend the full width of the 15 inch end of the envelope. A button and cord fastener shall be provided for closing the envelope. The printing shall be in black ink and as follows: "X-RAY FILM-DO NOT BEND OR FOLD" in letters 3/8 inch in height located across the center of the face. And, for the return address there shall be printed in the upper left-hand corner of the envelope the following:

(a) The word "FROM" in suitable size.
(b) Three horizontal lines below the word "FROM" spaced approximately 3/8-inch apart and 3-1/2 inches long.
(c) Below the three lines in suitable type the legend "Postmaster--Return in Ten Days if not Delivered. --Return Postage Guaranteed."

Small envelope. The small envelope shall be 3-7/8 ± 3/8 inch by 8-7/8 ± 1/8 inch, and shall have a gummed flap on one long side. The legend "This envelope contains a letter" shall be printed in black on the small envelope.

Chipboard inserts. Two chipboard inserts, 14-1/2 x 17-1/2 (± 1/8) inch shall be placed in each large envelope. Each chipboard insert shall have a thickness of 0.040 ± 0.005 inch, a minimum pH 5.0, and shall be without liner or coating. The chipboard inserts shall have smooth edges and shall be free from surface lumps, chip indentations, creases, wrinkles, cracks, blisters, or foreign material which may mar or scratch film.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15Z
Check the source to verify that this is the current version before use.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

Note: Standard samples may be obtained from the contracting officer.

Preparing activity:

GSA-FSS

GSA DC-01103045

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15Z
Check the source to verify that this is the current version before use.