COMMERCIAL ITEM DESCRIPTION

TROUSERS, MAN'S AND WOMAN'S (WINTER WEIGHT)

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers requirements for winter weight uniform trousers to be worn by male and female personnel of the Federal Protective Service.

Salient characteristics:

The trousers shall be made using uniform patterns from 55 percent polyester/45 percent wool, 2-ply, navy blue serge fabric (Raeford 3917-8107 or equal). The fabric shall meet the minimum performance requirements and test methods in Table I. The issue of the test method in effect on the date of the solicitation shall be used to determine compliance with the stated requirements.

TABLE I

CHARACTERISTICS	REQUIREMENT	TEST METHOD
Weight	13.0 oz/linear yard-60 inches wide	ASTM D 1910 - method 38
Breaking strength (warp/filling)	120 lbs/100 lbs	ASTM D 1682 - method 16
Yarns per inch	70 ± 5 warp 65 ± 5 filling	ASTM D 1910
Colorfastness to dry cleaning	Step 5	AATCC 132

Style. The trousers shall have a plain front with two quarter top pockets, and two back hip pockets. The left back hip pocket shall have a tab to button. The trousers shall have regular width (not flared) bottoms. The men's trousers shall be available in waist sizes 28 through 54 with even sizes only between 38 and 54. Men's trousers shall be available with finished or unfinished bottoms, as specified. When finished bottoms are specified, the trousers shall be hemmed in accordance with normal commercial practice to finished inseam lengths of 29 through 36 inches. The women's trousers shall be available in sizes 6 through 24.

Pockets. For pockets, any dimension enclosed in parentheses ( ) applies to women's trousers only. The front pockets shall have a minimum opening of 6-1/2 (5-1/2) inches, and be at least 6 (5-1/4) inches deep from the bottom of the opening. The front pockets shall be stitched, turned, and topstitched, and for reinforcement, shall be bartacked at the top and bottom of the openings. The back hip pockets shall be the double welt type manufactured on a Reece PW machine, with interlined welts and bartacks at the ends of the welts. The back pockets shall measure at least 6 (5) inches from bartack to bartack and at least 6 inches deep. The pocketing fabric shall be a plain or twill weave fabric of at least 50 percent polyester and the remainder cotton or rayon, and shall harmonize with the color of the trouser fabric.

Waistband and belt loops. The finished waistband shall be 2 ± 1/8 inches wide so as to accomodate a 1-5/8 inch belt, and shall close with a crush-proof hook and eye with the eye stitched or bartacked for added strength. The waistband shall be the continuous closed type and shall contain waistband stiffener to prevent roll over. The waistband curtain shall be a plain or twill weave fabric of at least 50 percent polyester and the remainder cotton or rayon, compatible in color with the trouser fabric, and shall have a 3-strand rubberized stitch insert to insure that shirts remain tucked in. The waistband curtain shall be attached to the trousers with a zig-zag stitch. There shall be at least seven belt loops measuring 3/4 + 1/8 inch wide, made from a double thickness of trouser fabric. All loops except the center back loop shall be sewn into the bottom of the waistband and shall be caught in the zig-zag seam which attaches the waistband curtain. The center back belt loop shall be bartacked.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

Fly and zipper. The right fly lining shall be the same fabric as the waistband curtain, and shall be sewn to the left fly below the zipper. The zipper shall be a heavy metal memory lock zipper with a brass bottom stop, and shall be bartacked at the bottom through the zipper tape. There shall be a french fly closure made from the trouser fabric on the inside of the right fly.

Trouser stripes. The trousers shall have colored braid sewn on top of the outside seam from the bottom of the front pocket opening to the bottom of the trouser leg. The braid shall be 1/2 ± 1/16 inch wide, blue (A.H. Rice #2880685 or equal), or 1 ± 1/16 inch wide, gold (A.H. Rice #4620107-6 or equal), as specified.

Workmanship. The trousers shall be free from any defects such as holes, tears, misweaves, spots, uneven dyeing, loose or skipped stitches, etc., that would affect appearance or serviceability. Thr trousers shall be seamed with matching polyester thread with all exposed inside seam edges to be serged. The seat seam shall be stitched with a tandem needle seat seaming machine. The trousers shall be pressed completely with the side seams and inseams pressed open.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable. The trousers shall be labeled in accordance with the Rules and Regulations under the Textile Fiber Products Identification Act. The trousers shall be labeled in accordance with the Trade Regulation Rule concerning Care Labeling of Textile Wearing Apparel.

Packaging, packing, and marking. The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

Notes: For men's trousers, purchasers should specify the waist size, the trouser braid color, and whether finished or unfinished bottoms are required. If finished bottoms are required, the inseam length must be specified. For women's trousers, purchasers should specify the size and the trouser braid color.

ASTM methods are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

AATCC methods are available from the American Association of Textile Chemists and Colorists, P.O. Box 12215, Research Triangle Park, NC 27709.

Preparing activity:

GSA-FSS

GSA DC-01104421

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:16Z
Check the source to verify that this is the current version before use.