A-A-2304
November 9, 1984

COMMERCIAL ITEM DESCRIPTION

WALLBOARD, GYPSUM

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification SS-L-30, Type III, Grades R and X, Class 1, Form a, Styles 1 and 3.

This description covers gypsum wallboard that is designed to be used for walls, ceilings, or partitions and affords a surface suitable to receive decoration. The wallboard shall be available in the following types, styles and sizes, as specified:

Type R - Regular core
Type X - Fire retardant core
Style 1 - Square edge
Style 2 - Tapered or recessed edge
Size a - 3/8-inch thick
Size b - 1/2-inch thick
Size c - 5/8-inch thick

Salient characteristics.

Material. Wallboard shall consist of an incombustible core, essentially gypsum, surfaced with paper firmly bonded to the core.

Type X. Designates gypsum wallboard complying with ASTM C36 that provides at least one hour fire-retardant ratings for boards 5/8 inch thick or 3/4 hour fire-retardant rating for boards 1/2 inch thick, applied to a partition in single layer nail application on each face of loadbearing wood framing members, when tested in accordance with the requirements of ASTM Methods E119.

Flame Spread Rating. When tested in accordance with ASTM E84 the wallboard shall have a maximum flame spread rating of 25.

Dimensions. The wallboards shall be 4 feet wide and 4 to 16 feet long, as specified. These are nominal dimensions.

Prohibitions. The wallboards shall contain no asbestos.

Finish. The surfaces shall be true and free from imperfections that would render the wallboard unfit for use with or without decorations. The edges and ends shall be straight. The corners shall be square.

Conformance. Wallboards shall meet or exceed the requirements of ASTM C36. The issue in effect of the date of the solicitation shall be used to determine compliance with this requirement.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

FSC 5640

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

A-A-2304

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Note. Purchaser should specify type, style, size, and length of wallboard desire.

When this commercial item description is used for procurement the commercial item certification clause must appear in the solicitation.

ASTM standards are available from the American Society for Testing Materials, 1916 Race Street, Philadelphia, PA 19103.

Military Coordinating Activity
None. DoD has waived coordination on this commercial item description until further notice.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.