A-A-2318
September 27, 1985

COMMERCIAL ITEM DESCRIPTION

FILE, HAND (AMERICAN PATTERN), ROUND, REGULAR

The General Services Administration has authorized the use of this commercial item description in preference to Type XVI, Class 1, Styles A, B, and C of Federal Specification GGG-F-325.

This commercial item description covers hand files used for enlarging circular openings, elongating holes, and similar purposes.

Salient characteristics:

Material:	Carbon alloy steel.
Taper:	At least one-third of the length to the point.
Design:	Furnished in bastard-cut, second-cut, or smooth-cut as shown in table. Bastard-cut files in lengths 4 inches through 10 inches shall be single-cut (one set of parallel cuts on the surface) or double-cut (two sets of parallel cuts on the surface, one set crossing the other); lengths 12 inches through 16 inches shall be double-cut. Second-cut files shall be single-cut, except for the 14 inch length which shall be double-cut. Smooth-cut files shall be single-cut.
Tang:	Of a conventional shape and size suitable for attachment to a wood handle. Tempered to a maximum hardness of 45 on the Rockwell C scale at a point approximately midway of its length and width.
Teeth:	Uniformly cut or etched and of uniform height throughout the fully cut portion. Cutting surfaces hardened to a uniform hardness. The distance between the heel and point of the file, excluding the tang, shall be hardened to not greater than 68 nor less than 64 on the Rockwell C scale. Free from decarburization and brittleness.
Marking:	Marked with the country of origin and the name of the manufacturer or with a trademark of such known character that the source of manufacture may be readily determined.
Workmanship:	The teeth of the file shall be well-defined, sharp, and uniform in height and form. There shall be no evidence of rust or other defect which may impair serviceability, durability, or appearance.



FSC 5110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

National Stock Number	Length Inches	Diameter at largest section A Inch	Number of teeth per inch Min.	Max.	Allowable distortion (maximum) Inch
		Bastard-cut			
5110-00-234-6545	4	3/16	37	44	0.010
5110-00-234-6548	6	1/4	26	31	.010
5110-00-234-6551	8	5/16	21	25	.020
5110-00-234-6554	10	3/8	19	21	.025
5110-00-234-6557	12	1/2	16	19	.025
5110-00-234-6560	14	5/8	15	18	.030
5110-00-239-6898	16	3/4	15	17	.040
		Second-cut			
5110-00-806-1000	4	3/16	46	53	.010
5110-00-234-6549	6	1/4	34	39	.010
5110-00-234-6552	8	5/16	28	32	.020
5110-00-234-6555	10	3/8	26	29	.025
5110-00-203-4692	14	5/8	21	23	.030
		Smooth-cut			
5110-00-203-4647	4	3/16	58	65	.010
5110-00-234-6550	6	1/4	46	51	.010
5110-00-234-6553	8	5/16	39	43	.020
5110-00-234-6556	10	3/8	36	39	.025
5110-00-234-6559	12	1/2	32	35	.025
5110-00-234-6562	14	5/8	30	33	.030

Length dimension: Measured from the point (free or front end) to the heel (junction of the tang with the body of the file) and have a tolerance of plus or minus 1/8 inch.

Tolerance: Diameter (A) - plus or minus 1/32 inch.

Regulatory requirements. In accordance with the section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.