[INCH-POUND]
A-A-2609A
November 19, 1990
SUPERSEDING
A-A-2609
February 24, 1989

COMMERCIAL ITEM DESCRIPTION

SHREDDING MACHINE, PAPER, OFFICE (STRAIGHT CUT, HIGH VOLUME)

The General Services Administration has authorized the use of this commercial item description in preference to Interim Federal Specification FF-S-001169.

This description covers high volume, straight cut paper shredders which are intended for use on letter size paper and computer printout forms.

Salient characteristics.

Description. Throat width -16 inches, min.; shred width - 11/32 inch max.; capacity - 50 sheets, min.

Speed. Shredders shall have a minimum speed of 60 feet/minute while engaged in shredding operations.

Capacity. Capacity is defined as the number of sheets of 20-lb. bond paper, 8-1/2 by 11 inches in size, than can be fed simultaneously into the machine without jamming.

Controls. Shredders shall be provided with either automatic shut-off and reverse controls or manual shut-off and forward and reverse flow controls.

Power requirements. Shredders shall be capable of operating on 220 vo;t, 60 Hz AC electric current. Alternately, shredders operating on 115 volt, 60 Hz AC electrical current will be acceptable provided that each shredder is furnished with a transformer to convert 220 to 115 volt current.

Identification. Each shredder shall have the manufacturer's serial number permanently and legibly stamped or affixed on a major component in a readily accessible location. In addition, each shredder shall be permanently marked in a conspicuous location with the manufacturer's name or trademark.

Paper clips, etc. All shredders shall be capable of shredding material containing regular metal paper clips and staples without jamming.

Instruction manual. An instruction manual shall be furnished with each machine. The manual shall contain complete instructions necssary for operation, maintenance and minor repair of the machine.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 7490

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:24Z
Check the source to verify that this is the currenversion before use.

Workmanship. The machine, including all parts and accessories, shall be fabricated and finished in accordance with good workmanship standards. The machine shall be free from any defect which affects the appearance, durability or serviceability or which might cause personal injury.

Safety. All units shall have either a self-closing feed door design or have a feed throat or hopper design that protects any operator(s) from flying debris that may be ejected from the shredder due to rotor/cutter damage, etc.

Conformance. Shall comply with the requirements of UL Standard 478. Test reports or labels from a testing laboratory recognized by OSHA under Appendix A to 29 CFR 1910.7 are acceptable as evidence of compliance.

QUALITY ASSURANCE PROVISIONS.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein.

Lot acceptance inspection. The finished items shall be visually inspected and functionally tested in order to establish acceptability based on conformance to the following requirements.

Sampling. Sampling for visual inspection and testing of shredding machines shall be performed in accordance with the provisions of MIL-STD-105. Inspection levels and acceptable quality levels shall be as follows: Visual inspections, level II, AQL 2.5%.; Performance testing, level S-2, AQL 1.5%.

Visual inspection. Samples of the finished machines selected in accordance with the requirements herein shall be visually inspected to verify compliance with the salient characteristics of the CID. Compliance with the above shall be determined based upon the presence or absence of defects as classified below.

Defects
Machine class/type, not as specified.
Throat width less than specified minimum.
Machine controls not as specified.
No evidence of conformance to UL Standard 478
Machine identification not as specified, missing, illegible,
Not permanently stamped/affixed.
Not in conformance with workmanship paragraph.
Instruction manual not available, inadequate, illegible.

Performance testing. Samples selected in accordance with the requirements herein shall be tested to verify conformance with requirements of the CID for machine capability to operate under the specified/rated power, capacity, shredding speed and pattern, single feed capacity and durability. Nonconformance with any of the above shall be regarded as a test failure and grounds for rejection.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:24Z
Check the source to verify that this is the current version before use.

Shredding speed. A measured length of 8-1/2" wide, 20-lb bond paper shall be fed into the cutters of the machine. The time required to shred the paper shall be recorded. The speed shall then be calculated on the basis of feet per minute.

Single feed capacity. The shredder shall be fed a series of test sets consisting of 8-1/2" wide, 20-lb. bond paper. The number of sheets in each succeeding test shall be increased by one. The maximum number of sheets accepted in a single pass without jamming the machine shall be noted.

Durability test. The machine under test shall be manually fed an assortment of paper sizes at its maximum rated capacity for 60 minutes. The rate of feed shall be that which can normally be accomplished by an average adult. The machine shall then be evaluated to the stated requirements listed in the Workmanship paragraph. Periodically, samples of the shredded material shall be taken and measured for compliance with the shred size requirement.

Cutters. After completion of tests, cutters shall be examined for nicks, wear or other evidence of damage that could affect the normal shredding operation.

Regulatory requirements. In accordance with Section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Copies of MIL-STD-105 may be obtained from the Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

UL standards may be obtained from the Underwriters Laboratories, 333 Pfingsten Road, Northbrook, IL 60062.

The Code of Federal Regulations (CFR) is for sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

Note: Purchaser shall specify NSN 7490-01-288-0448

(MAS 36-II, SIN 51-125)

MILITARY INTERESTS:

DoD has no interest in this document.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.