A-A-2611
December 1, 1989

COMMERCIAL ITEM DESCRIPTION

PUNCH; BINDER AND PUNCH/BINDER MACHINES (FOR SPIRAL-BOUND BINDERS)

The General Services Administration has authorized the use of this commercial item description in preference to Military Specification MIL-B-43308.

This description covers bench mounted punch and binder machines and accessories for assembling spiral bound books or binders. They shall be furnished in the following classes, types and sizes, as specified:

Class I - Punches
Class II - Binders
Class III - Punch/Binder Combination
  Type A - Mechanical
  Type B - Electrical
    Size 1 - Handles paper up to 12" wide.
    Size 2 - Handles paper up to 16" wide.

Salient characteristics.

Class I and III punches. Shall be designed to punch a single row of 1/8 by 5/16 inch (± 0.005 inch) holes on 9/16 inch (± 1/64 inch non-cumulative) centers.

Adjustable hole punch capability for between 1 and 21 holes for Size 1 and between 2 to 28 holes for Size 2.

Using paper having an average thickness of 0.003 inches the lift capacity of the machines shall be:

Type A - 15 sheet minimum.
Type B - 20 sheet minimum.

Side and back guides shall be incorporated with manual adjustment, to insure the required margin adjacent to the punched holes for various binding elements from 3/16 to 2 inch diameter, and equal margins at each end of any sheet within the limits of the machine.

Manually operated punch releases shall also be incorporated to deactivate and reactivate any number of hole punches as may be desired, within the limits of the machine, without the need of tools for removal of any components or parts of the machine.

The operating mechanism shall be designed so that all of the desired holes are punched in one cycle.

A removable receptacle shall be provided to catch the punch clippings.

FSC 3610

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

Class II and III binding machines. Shall be designed for installing plastic strip binding elements in material having punched holes as specified in the preceding paragraph.

The machines shall be capable of installing binding elements of various sizes from 3/16 thru 2 inch inside diameter, in material of pile heights commensurate with the binding element used.

Class III punch/binder combination. Shall consist of a single unit, combination machine, consisting of a punching and a binding section.

Electrical characteristics. All Type B machines shall operate on 60 hertz, 120 volt AC power supply.

Instructions. An instruction card or manual shall be furnished with each machine.

Conformance. All Type B machines shall be in accordance with Underwriters Laboratories (UL) Standard 478. Test reports or labels from a testing laboratory recognized by OSHA under Appendix A to 29 CFR 1910.7 are acceptable.

Workmanship. The machine, including all parts and accessories shall be fabricated and finished in accordance with good workmanship standards and the machine shall be free from any defect which affects the appearance, durability or serviceability or which might cause personal injury.

Quality Assurance Provisions

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection and test requirements specified herein.

Failure to meet all provisions of the requirements as specified, shall provide reason for rejection.

Sampling. Unless otherwise specified, sampling for inspection and testing shall be in accordance with the MIL-STD-105 requirement, inspection level II, AQL - 2.5 percent defective for visual inspection, and S-2 with AQL 1.5 percent defective for performance testing.

Visual inspection. Samples of the finished product selected in accordance with the requirement of the CID, shall be visually inspected to verify compliance with the item description, salient characteristics and workmanship requirements. Any nonconformance shall constitute grounds for rejection.

Performance testing. The paper used in the testing shall have an average thickness of 0.003 inch per sheet. Sheet size for testing Size 2 machines shall be 11 by 17 inches. Sheet size for testing Size 1 machines shall be 8-1/2 by 11 inches.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:24Z
Check the source to verify that this is the currentversion before use.

Class I and III Punching machines. Shall be tested using a minimum lift of 20 sheets of paper. With all the hole punches activated, the lift of paper shall be placed under the punches and against the back and side guides. The machine shall then be cycled through one complete punching stroke.

The machines shall punch clean, sharp, distortion free, equally spaced holes, with no localized marginal or size variation between holes.

Samples of the finished product shall be removed and examined per the requirements of this document. Failure to satisfy the stated requirements shall be regarded as a test failure and grounds for rejection.

Class II and III Binding machines. A 25 sheet lift of paper, punched along the long dimension in the corresponding size punching machine, shall be bound in the machine using a 5/16 inch inside diameter plastic binding element. In addition, a 425 sheet lift of paper, similarly punched, shall be bound in a 2 inch inside diameter plastic binding element.

After binding, the elements shall be examined, and each page of each group shall be laid open, one sheet at a time, to determine if the installed binding element, with a binding element ring through each hole and free of visible evidence of distortion, tears, or cutting of the binding element. Individual pages of bound material shall have complete freedom when turned over, page after page, and without tearing or pulling away from the binding.

Failure to satisfy the stated requirements shall be regarded as a test failure and grounds for rejection.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

NOTE: Purchaser shall order machines by the following NSNs.

Class I,	Type A, Size 1	3610-01-299-1006
Class I,	Type A, Size 2	3610-01-299-1005
Class I,	Type B, Size 1	3610-01-299-1004
Class I,	Type B, Size 2	3610-01-299-1001
Class II,	Type A, Size 1	3610-01-299-1008
Class II,	Type A, Size 2	3610-01-299-1007
Class III,	Type A, Size 1	3610-01-299-1003
Class III,	Type B, Size 1	3610-01-299-1002

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

Copies of MIL-STD-105 can be obtained from the Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

(MAS 36 Pt II, SIN 51-99, 106)

MILITARY INTERESTS:

No DoD Interest

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.