A-A-2625
May 1, 1989

COMMERCIAL ITEM DESCRIPTION

PLATE, ELECTROSTATIC

The General Services Administration has authorized the use of this commercial item description.

This description covers offset printing plates receptive to image transfer through electrophotography and shall be available in rolls in the following size, as specified.

Size 1 - 9 inch x 400 feet
Size 2 - 9-3/8 inch x 400 feet
Size 3 - 10 inch x 400 feet
Size 4 - 11 inch x 400 feet
Size 5 - 12 inch x 400 feet

Salient characteristics

The electrostatic plate shall consist of a photo-conductive receptive zinc oxide coating with an electro-conductive substrate.

Core size shall be 3 inches.

Thickness - 0.005 inches.

For use on 3M models 1165, 1175 and MR 417.

Coated side out.

Minimum run - 3000 impressions.

Capable of 100 lines with prescreened halftones.

1/2 percent stretch, maximum.

The sensitized coating shall be uniform and free from coating streaks, pinholes, dirt, abrasion marks, spots and mottling which may affect the printing quality of the plates.

The expiration date shall be not less than 24 months from the date of manufacture.

Workmanship. The sensitized rolls shall be free from any defects which may affect the durability, appearance or serviceability.

QUALITY ASSURANCE PROVISIONS

Responsibility for inspection and testing. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein.

FSC 3610

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

Sampling. Sampling for visual inspection and print quality testing shall be in accordance with the provisions of MIL-STD-105. Unless otherwise specified, Level II with AQL 2.5 percent defective for visual inspection, and S-2, AQL 1.5 percent defective for testing shall apply.

Inspection. Samples selected in accordance with the requirements specified herein shall be visually inspected to verify conformance to dimensional and workmanship requirements of the CID. Any departure from the specified requirements may be grounds for rejection.

Print quality test. A randomly selected plate, with adequate printed and solid copy, shall be used in a simulated production run and not less than the number specified herein shall be printed. A comparison of the first and last sheets shall show no deterioration of the image. Failure of this test may be cause for rejection.

These plates shall meet the stated requirements when used with the appropriate dry toner, and without adjustments to the manufacturer's operating specifications of the machines specified in this CID. Failure may be cause for rejection.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Copies of MIL-STD-105 can be obtained from the Naval Publications and Forms Center, Philadelphia, PA 19120.

Note. Purchaser shall specify NSN when ordering.

Size 1	3610-01-298-5586
Size 2	3610-01-298-3611
Size 3	3610-01-298-3612
Size 4	3610-01-298-3613
Size 5	3610-01-298-6670

(MAS 36 II, SIN 51-2002a)

MILITARY INTERESTS

NONE

PREPARING ACTIVITY

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.