A-A-407C
August 28, 1989
SUPERSEDING
A-A-407B
July 17, 1985

COMMERCIAL ITEM DESCRIPTION

FASTENER, PAPER (COMPRESSOR TYPE)

The General Services Administration has authorized the use of this commercial item description as a replacement for Federal Specification FFF-F-311E which has been cancelled.

This commercial item description covers paper fasteners, compressor type, which are intended for use in binding papers and similar printed matter together, especially when necessary to make frequent additions or removals.

1. Salient Characteristics

Fasteners, compressors and prongs shall be made of metal suitable for the purpose intended. Metal shall be 0.011 inch thick (+ 0.001, -0.0015 inch).

The base shall be 11/32 to 5/8 inch wide and shall have at least two reinforcing ribs.

The prongs shall be 3/16 to 7/32 inch wide. The length shall be such as to provide sufficient holding strength for the capacity specified. The spacing, as specified, between the prongs shall be measured from center to center. When the prongs of the fasteners offered are separate pieces, they shall be designed for positive fastening to the base piece.

The compressor shall be 11/32 to 5/8 inch wide and designed to receive the base prongs and hold them securely so as not to allow vertical or horizontal movement of the prongs.

The center to center spacing shall have a tolerance of ± 1/32 inch.

The fasteners shall have a finish in accordance with commercial practice to prevent corrosion.

Performance. The prongs shall be inserted through perforated sheets of paper having a total thickness of at least one half capacity of the fasteners. The fasteners shall be assembled with a compressor in a manner that each prong can be bent down flat to the closed position and back to the original (vertical) position 50 times within two minutes. Upon completion of this test, the prongs shall show no evidence of fracture.

Workmanship. The finished paper fastener shall exhibit no evidence of jagged or rough work. The fastener shall be free from defects which may affect serviceability, durability, and appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.

2. Quality Assurance

Each lot of fasteners shall be inspected for conformance to the requirements herein. Sampling for inspection shall be in accordance with MIL-STD-105 using the plans specified below.

Visual, dimensional and performance characteristics - Inspection Level S-2 with an Acceptable Quality Level (AQL) of 4.0 percent defective. The sample unit shall be one fastener.

Packaging, Packing, and Marking - Inspection Level S-2 with an AQL of 4.0 percent defective. The sample unit shall be one fully prepared shipping container.

3. Preparation for delivery

Packaging, packing and marking shall be as specified in the contract or purchase order.

4. Application for copies of technical documents referenced herein:
The issue date in effect on date of invitation for bids or request for proposal shall be apply.

MIL-STD-105 is available from Naval Publications and Forms Center; 5801 Tabor Avenue; Philadelphia, PA 19120.

5. Recovered materials

The manufacturer shall utilize recovered materials to the maximum extent practicable.

6. Ordering Data

Purchasers should specify the center to center spacing and capacity desired.

7. Notes

Instructions for assembly shall be provided with each unit container (box) of three-piece fasteners.

No Official DOD Interest
Has Been Registered

Preparing Activity:

GSA/FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.