A-A-65A
November 14, 1986
SUPERSEDING
A-A-65
May 14, 1980

# COMMERCIAL ITEM DESCRIPTION

## PUNCH, PAPER (OFFICE TYPE), LIGHT DUTY

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification GGG-P-846A, Type I.

This commercial item description covers hand-held paper punches intended for punching holes in paper and shall be furnished in two sizes, as specified.

| Size | Diameter (± 1/64) (inches) |
|---|---|
| 1 | 5/32 |
| 2 | 1/4 |

### Salient characteristics

The punch shall utilize a plier-type design and be activated by squeezing the handle together.

Handles and punch mechanism shall be spring loaded so that they return to the open position once compression on the handles is removed. The spring shall withstand repeated compressions without losing its resilience.

Handles shall fit the hand comfortably.

The punch and die shall be made of steel which is hardened to Rockwell C50 or higher. If case hardened, they shall be carburized, cyanided or nitrided. The case shall not be less than 0.005 inch in thickness and shall be file hard.

Punched holes shall have the diameter indicated for each size as applicable.

The throat depth or reach shall be not less than 1 inch, as measured from the center of the hole to the edge of the material being punched.

The punch shall experience no damage and continue to operate properly after punching through four (4) sheets of 133 pound (9.5 point) manila folder 100 times. Punched holes shall be neither torn nor ragged when the punch is used on single sheets of (17 x 22 - 1000) 18 pound manifold paper after the 100 punching operations previously described are completed.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:04Z
Check the source to verify that this is the current version before use.

All metal parts shall resist rust and corrosion.

The punch shall be marked with the name or trademark of the manufacturer.

Surface plating shall be nickel or chromium plated 0.00003 to 0.00005 inch in thickness.

Workmanship. The punch shall be free of any defects which affect durability, appearance or serviceability.

Quality Assurance Provisions

Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise in the contract, the contractor may use his own or an other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Sampling of end item for testing and visual examination. Sampling for inspection shall be in accordance with MIL-STD-105. The sample unit shall be one paper punch. The inspection level shall be S-3, and the Acceptable Quality Level (AQL) shall be 4.0 percent defective.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the order or contract.

Note. Purchaser shall specify size of paper punch desired.

MILITARY INTEREST:

None

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:04Z
Check the source to verify that this is the current version before use.