[Metric]
A-A-1020C
March 08, 1996
Superseding
A-A-1020B
December 9, 1994

COMMERCIAL ITEM DESCRIPTION
PERFORATOR, PAPER, TWO HOLE, DESK

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. Scope: This commercial item description covers perforators which are used for punching two holes simultaneously in paper.

2. **Classification:**

Type: I - Standard Duty
II - Heavy Duty

3. **Salient Characteristics:**

3.1 Perforators shall have a base, punches, dies and plates, handle, punch operating shaft (optional for standard duty, mandatory for heavy duty), springs, and an adjustable extension guide made of a commercially acceptable metal.

3.2 Perforators shall have a removable receptacle or a stationary receptacle (for collecting punched paper waste). If a stationary receptacle is used, it shall have a removable cap made of metal or plastic.

3.3 Perforators shall have a spring loaded handle and punches. Perforators shall have a paper guide attached to the base, which has not less than 12.7 cm (5") of useful length and locks into place for common paper sizes, including, but not limited to 20.3 cm (8"), 20.83 cm (8.2"), 26.67 cm (10.5"), and 27.9 cm (11").

3.3 Perforators shall be designed so the underside will provide stability and not mar the surface on which it rests. Perforators shall be finished in beige, black or gray color, as specified in the contract or ordering document.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

3.4 Perforators shall be permanently marked with the manufacturer's name or trademark. Placement of these permanent markings shall be at the option of the manufacturer, provided they are prominently displayed.

3.5 Handles and punches shall automatically return to the upward position after each punching operation under normal use. When the handle does not automatically return to the upright position, it can be retracted from the dies by pulling up on the handle.

3.6 Perforators shall meet the test requirements as specified in 5.2. All metal parts shall be corrosion resistant. Individual parts shall be either corrosion resistant stainless steel or anodized, plated, finished with baked enamel, epoxy powder coated, subjected to a bluing process, or what ever is commercially appropriate for the specific function of the part. The contractor shall provide a manufacturer's certification of corrosion resistance upon request by the Government.

3.7 Dimensions. Hole punches shall have a 6.7 mm ± .79 mm (.3" ± .003") diameters with center to center distance of 69.85 mm ± .79 mm (2.7" ± .003"). The centers of the punched holes shall be 11.5 mm ± 1 mm (.5" ± .001") from the edge of the material being punched.

3.8 Workmanship. Except for the cutting edge of the punch, the perforator shall be free of sharp edges. The perforator shall be free of superfluous coatings of any kind, burrs, scratches, cracks, discoloration, loosened parts, warping, or visible stress marks. The handle shall not bind in use. The perforator shall not exhibit any evidence of deformity and shall be free of any defects which affect appearance or impairs serviceability.

4. Regulatory Requirements: The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with Paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.1 Certification: The contractor shall certify that if polystyrene is used in the manufacture of the item, it shall contain a minimum of 25 percent Postconsumer Recovered Materials in accordance with Title 40 Code of Federal Regulations Part 247, Comprehensive Guideline for Procurement of Products Containing Recovered Materials; final rule. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provision of the contract.

5. Quality Assurance Requirements:

5.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and therefore as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

5.2 Examination and Testing

5.1.1 Suppliers are encouraged to use quality control (QC) techniques that exhibits control over their processes (e.g. Statistical process Controls) SPC Techniques) as defined in American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3 / American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. If used, objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in the applicable technical document or herein.

5.1.2 End item inspection / testing may be used by the offerer, or the government representative, as a means to determine the effectiveness of the inprocess quality controls. While inprocess controls shall not be substituted for end item performance testing, they may be instituted for visual and dimensional inspection / testing.

5.1.3 For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection / shall be required. The sample unit shall be one perforator Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society of Quality Control (ASQC) ANSI/ASQC Z1.4 1993, Sampling Procedures and Tables for Inspection by Attributes.

5.1.4 For Visual and Dimensional inspections, the level shall be S-3 with an Acceptable Quality Level (AQL) of 4.0 Percent Defective. The inspection level for performance testing shall be S-1 with an Acceptable Quality Level of 4.0 percent defective. The supplier must provide objective evidence (test and inspection records) that the presented material meets the requirements of this commercial item description.

5.2 Performance Test. Each operation shall be performed 100 times. These operations shall leave holes entirely punched out, without torn or ragged edges

(A) Type I - Standard Duty:

5.2.1 Durability Test. The perforator shall be tested using Kraft or manila paperboard - Basis Weight 66.7 kg (147 lb.), 60.96 cm (24") x 91.44 cm (36") - 500 sheets, 11 pt. The perforator shall be capable of consistently perforating 5 paperboard sheets at one time.

5.2.3 Normal Use Test. The perforator shall be tested using bond paper - Basis Weight 7.26 kg (16 lb.), 43.18 cm (17") x 55.88 cm (22") - 500 sheets. The perforator shall be capable of consistently perforating at least 12 sheets of bond paper at one time. Each operation shall use both punches

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

(B) Type II - Heavy Duty:

5.2.4 Durability Test. The perforator shall be tested using Kraft or manila paperboard - Basis Weight 66.7 kg (147 lb.), 60.96 cm (24") x 91.44 cm (36") - 500 sheets, 11 pt. The perforator shall be capable of consistently perforating 8 paperboard sheets at one time.

5.2.5 Normal Use Test. The perforator shall be tested using bond paper - Basis Weight 7.26 kg (16 lb.), 43.18 cm (17") x 55.88 cm (22") - 500 sheets. The perforator shall be capable of consistently perforating at lease 25 sheets of bond paper at one time.

6. Packaging:

6.1 Preservation, Packing and marking shall be specified in the contract or order

7. Notes:

7.1 Reference Documents Issues of the following documents, in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein

7.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington DC 20402

7.1.2 Application for copies of (ANSI) Z1.1, Z1.2 and Z1.3 and (ASQC) B.1, B.2 and B.3 may be obtained from the American Society for Quality Control, PO Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201-4606.

7.1.3 Title 40, Code of Federal Regulations, Protection of Environment, Part 247 copies may be obtained from the U.S. Government Printing Office Washington, DC 20402, phone (202) 783-3238.

7.2 National Stock Number Listing (NSNs The following is a list of NSNs assigned which correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID

7520-00-139-3902
7520-00-224-7589
7520-01-338-9397

MILITARY INTERESTS

NONE DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice

Preparing Activity

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.