[METRIC]
A-A-1709H
March 28, 1996
SUPERSEDING
A-A-1709G
December 3, 1991

COMMERCIAL ITEM DESCRIPTION

FILE CABINETS, LATERAL, STEEL

The General Services Administration has authorized the use of this commercial item description.

Scope. This Commercial Item Description covers the minimum requirements for medium duty, lateral files

Salient characteristics. These characteristics concisely describe the essential physical and functional/performance characteristics of the commercially available item.

Design. The lateral file cabinets shall be contemporary style designed for office use.

Sizes. Nominal overall width dimensions·

Size 1 - 910 mm wide
Size 2 - 1070 mm wide
Size 3 - 760 mm wide

Case. Construction shall be welded, completely setup; closed bottom; 4 adjustable glides (minimum 25 mm diameter).

Laminated plastic tops. When specified, the file shall have a particleboard top with a self-edged, high pressure plastic laminate face and a backing sheet. The plastic laminate shall be walnut grain per GSA Standard Sample No. FSS-L-01002, light oak grain per GSA Standard No. FSS-01015 or matte, parchment laminate within the limits of the parchment enamel. Alternatively, the manufacturer may provide his commercial walnut or light oak grain high pressure plastic laminate, subject to approval of the contracting officer. Overall thickness of the top shall be 25 mm, minimum.

Drawers and shelves. Drawers and shelves shall be of welded construction Drawers and shelves shall have suspensions which extend far enough to allow unobstructed insertion and removal of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

hanging files and their contents. Standard height drawers shall be equipped with hanging folder frames to support both legal and letter size material filed laterally and front to back and adjustable dividers (3 per tier) to support legal and letter size material filed laterally. means to convert the drawer to legal or letter size depth Standard height shelves shall be the roll out type with receding doors and equipped for filing material the same as the standard height drawers (front to back filing is not required) Standard height drawers and shelves shall have a minimum clear inside height of 257 mm.

Pulls. Pulls shall be a recessed type which includes a label holder The finish shall be bright or satin polished anodized aluminum; satin or polished chrome plating on steel or die cast zinc, brass, bronze, satin finish stainless steel or painted to match the cabinet finish. The exposed surfaces of all face hardware used on a single unit shall be finished to match each other.

Interlock mechanism. The interlock mechanism shall be a positive, automatic mechanism (cords are not allowed). When one drawer or shelf is open, the remaining drawers and/or shelves shall be locked in the closed position.

Locking mechanism. The locking mechanism shall be the ganged type, which locks both sides of all drawers and doors. The locks shall be of the disk or pin tumbler type, having not less than four disks or pin tumblers, and shall be operated by a grooved key The locks shall have not less than 125 key changes No one key shall open more than one lock on one unit up to a minimum of 125 units consecutively produced Two keys shall be supplied with each cabinet The locking mechanism and lock shall operate easily and smoothly

Finish. The finish shall be semi-gloss baked enamel or electrostatic powder coat paint Unless otherwise specified, colors shall match Fed. Std. No. 595 black (27040) and parchment within the range delimited by (26586) and (26405). Alternatively, the manufacture may provide his commercial, black, baked enamel finish and commercial colors, subject to approval of the contracting officer.

Caution label and instruction label A caution label shall be affixed to the face of the cabinet, at the top, advising users that excessive force to extend drawers and shelves could cause tipping of the cabinet. An instruction label shall be affixed in

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

the top compartment advising users to; level the cabinets from side to side with the front higher than the back, (where applicable); load the bottom compartment first; read the instruction sheet for installation and conversion of accessories from letter to legal size filing. These labels shall not be removable by hand without defacement after being affixed for 4 hours

Identification label. The label shall have the contractor's name or trademark, contract number, National Stock Number (if specified), month and year of manufacturer legibly marked in permanent dark ink. The label shall be located in the top compartment and shall not be removable by hand without defacement after being affixed for 4 hours.

Workmanship. The workmanship shall be of the quality to produce finished cabinets acceptable in appearance, function and serviceability and to prevent potential hazard to personnel or their clothing Welding and brazing shall be neat, uniform, free of burrs and adequate to assure rigidity and strength.

Quality assurance provisions. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Sampling for inspection shall be performed in accordance with ANSI/ASQC Z1.4, unless an equal or better plan is approved by the contracting officer or his/her representative. A lot shall consist of units of one size and color. The sample shall be one each Inspection levels and AQL's shall be as follows

For fit, finish and all other workmanship - Level II, AQL 4.0 defects per hundred units.

For packaging, packing and marking - Level S-2, AQL 4.0 percent defective

Any failure to meet the dimensions, color, identification label or performance requirements shall cause rejection of the lot

Performance. Each unit shall comply with the following requirements. Failure of any cabinet to comply with these requirements shall be cause for rejection

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

ANSI/BIFMA. American National Standard Test for Lateral Files X5.2-1989 The test shall be performed on a hard level surface The drawer or roll-out shelf retention test shall be performed after successful completion of the drawer or rollout shelf cycle test on the same cabinet.

Rigidity. The cabinet shall be placed on a hard level surface in its operating position and the base shall be restricted from vertical and lateral movement All compartments shall be empty and the top drawer or shelf shall be fully extended. A force of 178 N shall be applied perpendicular to the side of the cabinet within 25 mm of the top front corner. The cabinet shall have failed the test if the deflection is in excess of 6.4 mm for the 762 mm and 914 mm widths and 6 mm for the 1067 mm widths while the force is being applied. The deflection measurement shall be taken along the top front edge of the cabinet

Shock The glides shall be removed, and the cabinet placed on a level carpeted surface (maximum 12.7 mm thick including pad) in its operating position. All drawers and shelves shall be loaded as specified in 8.2 of the ANSI/BIFMA Standard and the cabinet locked with tne key removed. The cabinet shall be tilted on side until the opposite side is 203 mm from the floor. A 203 mm long block shall be placed under the center of tne raised sided and then knocked loose, allowing the cabinet to free fall to the floor. The test shall be repeated once on each side. The cabinet shall have failed the test if any drawer or door opens; any damage to the lock or interlock mechanisms; failure of welds; damage or loosening of components (except superficial damage to case); or failure of the drawers and shelves to pass the pull test specified in 9.2 2 of the ANSI/BIFMA Standard.

Interlock safety. Perform the test after completion of the ANSI/BIFMA tests and the Rigidity and Shock tests. The cabinet shall be placed on a level surface in its operating position with all drawers/shelves empty. Simultaneously, exert a force perpendicular and outward from tne face of the cabinet on the two top drawers, two top shelves or drawer and shelf, whichever is applicable. The force shall be at the center of a drawer pull or the bottom center of a shelf, as appropriate, and shall be approximately 26.7 N for each compartment. Repeat this test on all combinations of two compartments. (Example: top and third compartments; top and fourth compartments, etc) The cabinet shall have failed

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

the test if any two-compartment combination extends in excess of 150 mm

Shipping Shock Test. The test equipment shall comply with ASTM D-880. A complete fully assembled unit (cartoned) shall be submitted for test. Prior to cartoning, the unit shall be inspected for visual or functional damage and documented. The cartoned unit shall be placed onto the impact machine dolly flush against the back stop and parallel to the leading edge of the dolly The catch mechanism located on the side of the dolly shall be tripped to allow the dolly to move up the incline at a 10^{0} angle. Once the dolly hits the automatic trip mechanism, the dolly will freely roll down the incline at a distance of four feet and impact the back stop. This procedure shall be performed on the remaining 3 sides of the cabinet. The carton shall have failed the test if there is visual, structural or functional damage to the unit.

Shipping vibration test. The test equipment shall comply with ASTM D-999 1) A complete fully assembled unit shall be submitted for test. Prior to cartoning, the unit shall be inspected for visual and functional damage The packaged product shall be placed on the vibration platform in its normal shipping position. Set the vibration frequency at a minimum speed sufficient to cause the packaged product to leave the platform momentarily so that a 2mm shim may be inserted at least 100mm between the packaged product and the surface of the platform. Vibrate the packaged product for a total of one hour. A single 90^{0} horizontal rotation should be accomplished after the first one half hour of the vibration, (if the size of the product makes a 90^{0} rotation impractical, a 180^{0} horizontal rotation is permissible) 2) Place the packaged product on the platform in its normal shipping position Using the same vibration frequency, vibrate the packaged product for one half hour on each of its four sides, (three hours total). Inspect the carton for visual, structural or functional damage. Remove the product from the carton and inspect it for visual, structural or functional damage to the unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

Regulatory requirement. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or order An impact detection device with companion device or warning label shall be affixed to all cartons in a location that is clearly visible Known sources for these devices are Media Recovery, 1195 Empire Central, Dallas TX 75247, 1-800-527-9497, Impact-O-Graph, 20710 Lassen Street, Chatsworth CA 91311-4598, (818) 341-3000 and Uline, Inc., 950 Albrecht Drive, Lake Bluff, IL. 60044, (708) 295-5510.

Notes.

Ordering options Purchasers should specify the following:

a Number of tiers
b. With or without laminate plastic tops
c With or without locks
d. Color of finish
e. Grain or color of laminate
f. Size

Plastic laminate panel A sample panel of the decorative plastic laminate sheet is available from the General Services Administration, Federal Supply Service, National Furniture Center, Engineering Division, Washington, DC 20406

Sample color panel A sample of the baked enamel finish referenced in Fed. Std. No 595 is available from the General Services Administration Business Service Centers in Boston, MA, New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL, Kansas City, MO; Fort Worth, TX, Houston, TX; Denver, CO, San Francisco, CA, Los Angeles, CA; and Seattle, WA.

ANSI/BIFMA Standard. The ANSI/BIFMA Standard is obtainable from American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

ANSI/ASQC Standard. is obtainable from the American Society For Quality Control, 611 East Wisconsin Avenue, Milwaukee, Wisconsin 53202.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.