MIL-B-0036076B (DM)
13 March 1967
SUPERSEDING
MIL-B-0036076A (DM)
21 October 1964
USED IN LIEU OF
MIL-B-36076 (BuMed)
14 July 1961

MILITARY SPECIFICATION

BAG, SOILED CLOTHES, SELF-CLOSING, ROPELESS

This limited coordination Military specification has been prepared by the Defense Personnel Support Center based upon currently available technical information, but it has not been approved for promulgation as a coordinated revision of Military Specification MIL-B-36076 (BuMed). It is subject to modification. However, pending its promulgation as a coordinated Military specification, it may be used in procurement.

1. SCOPE

1.1 This specification covers a cotton duck bag.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Federal

V-T-276	Thread, Cotton.
CCC-C-419	Cloth, Cotton, Duck, Unbleached, Plied-Yarns, (Army and Numbered).
CCC-C-443	Cloth, Cotton, Duck, (Single and Plied Filling Yarns, Flat).
DDD-L-20	Label, for Clothing, Equipage, and Tentage, General Use.
PPP-B-636	Box, Fiberboard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

Military

MIL-W-530 Webbing and Tape, Textile, Cotton, General Purpose, Natural or in Colors.

STANDARDS

Federal

Fed. Std. No. 751 Stitches, Seams and Stitchings.

Military

MIL-STD-105 Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 Marking for Shipment and Storage.
MS 16686 Medical Services Symbol.

DRAWING

Defense Personnel Support Center

20208 Bag, Soiled Clothes, Self-Closing, Ropeless.

(Copies of specifications, standards and drawing required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Except as specified herein, materials shall conform to the applicable portions of the specifications, standards, and drawing listed in section 2, and be subjected to the requirements specified therein. When materials to be specified are not specifically designated, those used shall be of the highest quality, and suitable for the purpose intended.

3.1.1 Cloth cotton duck. The cloth shall be grey (natural), ply yarn cotton duck, type I, No. 10, hard texture, of CCC-C-419; or grey (natural) double filling 14.53 ounces per square yard, type II, table II, of CCC-C-443.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

3.1.2 Thread, cotton. Except as specified herein, the thread shall conform to V-T-276 and shall be type IB1, machine thread, 4-ply, ticket No. 12, as shown in table II for needle thread, and type IA1, machine thread, 4-ply, ticket No. 12, as shown in table I for bobbin thread. All references to "approved shade standard", "approved standard shade sample", and "approved standard shade" made in V-T-276 shall not apply. Paragraph titled "Certification" in V-T-276 shall not apply (see 4.1.2).

3.1.3 Webbing. The webbing shall conform to type II, class 1, 3/4 inch wide of MIL-W-530.

3.2 Construction. The construction shall conform in all respect to drawing 20208 and as specified herein.

3.2.1 Stitching. All stitching, except overedge stitching, shall be stitch type 301, conforming to Fed. Std. No. 751. The number of stitches per inch shall be a minimum of six and a maximum of nine. Thread breaks shall be overstitched not less than 1/2 inch beyond the ends of each break. The ends of seams and stitching when not caught in other seams or stitching shall be backstitched not less than 1/2 inch. Thread tension shall be maintained so that there will be no loose stitching and that the lock will be embedded in the sewn material.

3.2.1.1 Overedge stitching. Stitch type 504 or 505 of Fed. Std. No. 751 shall be used where overedge stitching is specified in the drawing.

3.3 Identification marking. The identification marking shall conform to type IV, class 9 of DDD-L-20. The fastness requirements shall be as specified for the class 5 label. Each bag shall be permanently and legibly marked in black as shown in the drawing.

3.4 Workmanship. Workmanship shall be first class throughout. Completed bags shall be well made and free from defects which detract from their appearance or may impair their serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual, and investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.2 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test result obtained, may be furnished in lieu of actual performance of such testing by the contractor.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105. Inspection levels and acceptable quality levels (AQL) are indicated in table I.

Table I. Inspection and acceptable quality levels.

For visual examination	Inspection level	AQL percent defective
Major defects.	II	2.5
Total (major and minor combined) defects.	II	8.0
For dimensional examination.	S-3	4.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

4.2.2 Component materials. Sufficient samples of the component materials shall be selected from each lot of material used in the manufacture of the bags to perform tests as required by the applicable subsidiary specifications. When sample size for component materials covered by subsidiary specifications is not specified, the sample size shall be as indicated for inspection level S-1 of MIL-STD-105. The acceptable quality level shall be zero. The unit product for testing shall be the quantity necessary to perform all required tests one time each. Not less than three samples shall be taken regardless of lot size. Lot sizes are expressed as follows:

Duck.....Yard.
Webbing.....Yard.
Thread.....Cones or Spools.

4.3 Examination of the end item. The defects found during examination of the end item shall be classified in accordance with 4.3.1 and 4.3.2. The applicable inspection levels and acceptable quality levels (AQL's) shall be as indicated in 4.2.1. The sample unit for these examinations shall be one completely fabricated bag.

4.3.1 Classification of defects. All defects shall be classified as indicated in table II.

Table II. Classification of defects.

Defect	Classification Major	Minor
Material defects and damages.		
a. Any hole.	X	
b. Any weakening defect such as a smash, multiple float or loose slub.	X	
c. Shade bar or slub on outside.		X
d. Needle chew, cut, tear, mend, burn.	X	
Cleanness.		
a. Any spot or stain, clearly noticeable:		
on outside.	X	
on inside.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

Defects	Classification Major	Minor
Cutting.		
a. Any part not cut in conformance with specified requirement.	X	
Component and assembly.		
a. Any component part or required operation omitted.	X	
Seams and stitching.		
a. Accuracy of seaming.		
1. Seam twisted, puckered, or pleated, affecting appearance.		X
2. Ends of seams and stitching, when not caught in other seams or stitching, backstitched less than 1/2 inch.		X
3. Thread break overstitched less than 1/2 inch beyond each end of break.		X
4. Skipped or broken stitches:		
up to 1/4 inch, inclusive.		X
more than 1/4 inch.	X	
b. Raw edges.		
1. On outside:		
up to 1/2 inch.		X
more than 1/2 inch.	X	
2. Any raw edge caused by the omission of overedge stitching more than 1/2 inch.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

Defects	Classification Major	Minor
c. Seam and stitch type.		
1. Not specified seam or stitch type.		X
d. Stitch Tension.		
1. Loose tension resulting in a loose seam.	X	
2. Tight tension (stitches break when normal strain is applied to seam or stitching).	X	
e. Stitches per inch.		
1. Two or more less than specified.	X	
2. One or more in excess of maximum specified.		X
Marking (identification).		
a. Omitted, misplaced, illegible, incorrect or size of characters not as specified.		X
Bag Construction		
a. Not as shown in drawing and as specified herein.	X	

4.3.2 Dimensional examination. Any measurement deviating from the dimensions and tolerances specified in the drawing shall be scored as a dimensional defect.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. One bag, as specified, constitutes one unit of issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

5.1.2 Packaging quantities. The number of units of issue indicated in table III shall be packaged in each intermediate and exterior container, as applicable, for the required level of protection specified in procurement document.

Table III. Packaging quantities

Unit package	Intermediate package	Exterior container
Not required	12 units	24 units

5.1.2.1 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Intermediate package. Each unit shall be neatly folded, and packaged in a carton of appropriate size constructed in accordance with PPP-B-636, class Weather-resistant, compliance symbol W5c, style RSC. Closure by taping as specified in 30.3.2.1.2 of PPP-B-636 is permitted.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose within the continental limits of the United States.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be a box of appropriate size constructed in accordance with PPP-B-636, class Weather-resistant, compliance symbol V3c, style RSC. Waterproofing shall be as specified in 30.4 of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall be constructed in accordance with PPP-B-636, type CF, class Domestic, fabricated from not less than 275-pound test fiberboard.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Intermediate packages. Each intermediate package shall be marked in accordance with MIL-STD-129. Contract or purchase order number and name of contractor shall be shown.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The clothes bag covered by this specification is used by the Military Medical Services for the collection and transportation of soiled clothes.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title , number and date of this specification.
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

6.3 This specification does not include all types, classes, grades, or sizes of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the items which are normally procured to meet Military requirements.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Review activities:
Army - MD
Navy - MS
Air Force - 03

Review information is current as of the date of this document. For future coordination of change to this document, draft circulation should be based on the information in the current DODISS.

CATEGORY: N

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-B-0036076B (DM)

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 68 1426 REPLACES EDITION OF 1 OCT 64, WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.