MILITARY SPECIFICATION

BAG, SOILED CLOTHES, SELF-CLOSING, ROPELESS

1. SCOPE

1.1 This specification covers a cotton duck bag, 46 inches long by 40 inches wide when closed, suitable for the collection and transportation of soiled clothes.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

V-T-276	Thread, Cotton.
UU-T-116	Tape, Paper, Gummed, Water-Resistant.
CCC-C-419	Cloth, Cotton, Duck, Unbleached, Plied-Yarns (Army and Numbered).
CCC-C-443	Cloth, Cotton, Duck (Single and Plied Filling Yarns, Flat).
PPP-B-636	Box, Fiberboard.
PPP-T-45	Tape, Gummed, Paper, Reinforced.
PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper, Water Resistant (for Carton Sealing).

Military

MIL-W-530	Webbing, Textile, Cotton, General Purpose, Natural or in Colors.

FSC 8105

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

Fed. Std. No. 751 Stitches, Seams, and Stitchings.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MS16686	Medical Services Symbol.

DRAWINGS

Military Medical Supply Agency

20208 Bag, Soiled Clothes, Self-Closing, Ropeless.

(Copies of specifications, standards, and drawing required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Except as specified herein, materials shall conform to the applicable portions of the specifications, standards, and drawing listed in section 2, and be subjected to the tests and requirements specified therein. When materials to be specified are not specifically designated, those used shall be of the highest quality, and suitable for the purpose intended.

3.1.1 Cloth, cotton duck. The cloth shall be grey (natural) ply yarn cotton duck conforming to Specification CCC-C-419, for type I, No. 10, hard texture, as shown in table I of the same specification, or grey (natural), double filling, 14.53 ounces per square yard, conforming to the requirements for type II, table II of Specification CCC-C-443.

3.1.2 Thread, cotton. Except as specified herein, the thread shall conform to Specification V-T-276 and shall be type IB1, machine thread, 4-ply, ticket No. 12, as shown in table II for needle thread, and type IA1, machine thread, 4-ply, ticket No. 12, as shown in table I for bobbin thread. All references to "approved shade standard", "approved standard shade sample", and "approved standard shade" made in Specification V-T-276 shall not apply. Paragraph titled "Certification" in Specification V-T-276 shall not apply (see 4.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

3.1.3 Webbing. Webbing shall conform to the requirements of Specification MIL-W-530, and shall be type II, medium weight, 3/4 inch wide, class 1, of the same specification.

3.2 Construction. Except as specified herein, construction shall conform to the requirements as shown on Drawing 20208.

3.2.1 Construction details. All seams and stitching shall be straight, conform to Federal Standard 751, and consist of stitch type 301 stitches formed by machine, evenly spaced, with not less than six nor more than nine stitches to the inch. The ends of each continuous row of stitches (including ends due to threads break), shall be anchored by backstitches for a length of not less than one inch, except where anchorage is provided by another seam or stitching. Thread tension shall be properly maintained so that there will be no loose stitching and the lock will be imbedded in the middle of the material sewed.

Stitch type 504 or 505 shall be used where overedge stitching is specified in the drawing.

3.3 Identification marking. Each bag shall be permanently and legibly marked in black as shown in the drawing.

3.4 Workmanship. Workmanship shall be first class throughout. Completed bags shall be well made and free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier responsibilities for inspection. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual, etc., investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

4.1.2 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

4.1.3 Government furnished material. Government furnished material shall not be sampled or tested unless specifically requested by the Government (see 6.1).

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with Standard MIL-STD-105.

4.2.2 For tests. Sampling for tests shall be conducted in accordance with Standard MIL-STD-105.

	Inspection level	AQL (percent defective)	Minimum sample size
Component material testing	L2	*	3

*Acceptance number shall be zero (0) for all sample sizes.

4.2.3 Component materials. Sufficient samples of the component materials shall be selected from each lot of material used in the manufacture of the bags to perform tests as required by the applicable subsidiary specifications or by tests specified herein. When sample size for component materials covered by the subsidiary specifications is not specified, the sample size for each test shall be as indicated in 4.2.2. The unit of product for testing shall be the qualtity of material necessary to perform all required tests one time each, taking into consideration the fact that, where possible, the same material may be used to perform two or more tests. Lot sizes are expressed in multiples of the following:

Duck ---Yards or fractions of a yard.
Webbing --- Yards or fractions of a yard.
Thread - Cones or spools.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

4.3 Examination. The bags shall be examined to determine compliance with all requirements contained in this specification.

4.4 Tests shall be conducted, as necessary, to determine compliance with specification requirements.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. One (1) bag, as specified, constitutes one unit.

5.1.2 Packaging quantities. The number of units of issue indicated in table I shall be packaged in each intermediate and exterior container, as applicable, for the required level of protection specified in procurement document.

Table I. Packaging Quantities

Unit package	Intermediate package	Exterior container
Not required	12 units	24 units

5.1.2.1 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which will insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Unit preparation. Each unit shall be neatly folded.

5.1.3.2 Intermediate package. Intermediate package shall be a carton of appropriate size constructed in accordance with Specification PPP-B-636, class 2, compliance symbol W5c, style RSC, except that the manufacturer's joint shall be effected by sealing as specified in 3.3.3.3 of Specification PPP-B-636, or by means of metal stitches. When metal stitches are used, they shall be covered by means of a suitable tape over the stitches on the interior surface of the box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

5.1.3.2.1 Closure. Closure shall be effected by means of tape conforming to the requirements of Specification UU-T-116, PPP-T-45, or PPP-T-76. The tape shall be not less than 2 inches wide, and shall be applied to both top and bottom so that the center seams are covered their full length. Tape shall extend at least 2 inches onto each of the end panels. Tape will not be required on manufacturer's joint.

5.1.4 Level B.

5.1.4.1 Unit preparation. Each unit shall be neatly folded.

5.1.4.2 Intermediate package. Intermediate package shall be a carton of appropriate size, constructed in accordance with Specification PPP-B-636. Box shall conform to type I, class 1, and shall be fabricated from not less than 200-pound test fiberboard. Closure shall be adequate to prevent spillage of contents under normal handling.

5.1.5 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose within the continental limits of the United States of America.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be a box of appropriate size constructed in accordance with Specification PPP-B-636, class 2, compliance symbol V3c, style RSC.

5.2.1.1.1 Closure. Closure shall be as specified in 30.3.2.1 of Specification PPP-B-636, and in addition, the top and bottom center seams shall be closed by means of tape conforming to the requirements of Specification UU-T-116, PPP-T-45, or PPP-T-76. The tape shall be not less than 2 inches wide and shall extend at least 2 inches onto each of the end panels. Strapping will not be required.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall be constructed in accordance with Specification PPP-B-636, type I, class 1, fabricated from not less than 275-pound test fiberboard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

5.2.2.1.1 Closure. Closure shall be in accordance with 30.3.1 of Specification PPP-B-636.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Intermediate packages. Each intermediate package shall be marked in accordance with 5.2 of Standard MIL-STD-129. Contract number and name of contractor shall be shown.

5.3.2 Exterior container. Exterior container shall be marked in accordance with Standard MIL-STD-129, except as follows: The letter "L" shall precede the Federal stock number. One space shall be allowed between the letter "L" and the first digit of the stock number. The terms "Stock number" or "FSN" shall not be indicated. Service color and service symbol markings are required only on direct shipments from the contractor's plant to overseas activities.

6. NOTES.

6.1 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification.
(b) When sampling or testing of Government supplied material is required (see 4.1.3).
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(1) Level B preservation and packaging is intended to provide economical but limited protection, and should be specified only when it is determined the bag will be held in covered storage for not more than 12 months from date of initial packaging.

6.2 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Military requirements.

6.3 Transportation description. Transportation description applicable to this item is:

Bags, cotton, clayed, or other than clayed, NOIBN.
Carload minimum weight 30,000 pounds in accordance with Uniform Freight Classification.
Truckload minimum weight 30,000 pounds in accordance with National Motor Freight Classification (A Series).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

Notice. When Government, drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Army-Med
Navy-BuMed
Air Force-AFCSC

Preparing activity:
Navy-BuMed
(MMSA)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

☆ U S GOVERNMENT PRINTING OFFICE 1973—714-868/3983 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Defense Personnel Support Center
Attn: DPSC-ATTS
2800 South 20th St
Philadelphia, Pa. 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:04Z
Check the source to verify that this is the current version before use.