MIL-I-36050A
7 December 1972
SUPERSEDING
MIL-I-36050
17 May 1961

MILITARY SPECIFICATION

INSERT CABINET, MEDICAL INSTRUMENT AND SUPPLY

SET CHEST (PLASTIC DRAWERS)

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers a metal frame with plastic drawers, intended to fit into a medical field chest to form a multicompartment cabinet suitable for the storage, transport, and distribution of spare parts for hospital unit assemblies (see 6.3).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-S-698	Steel, Sheet and Strip, Low Carbon.
TT-C-490	Cleaning Method and Pretreatment of Ferrous Surfaces for Organic Coatings.
TT-E-527	Enamel, Alkyd, Lustreless.
TT-P-636	Primer Coating, Alkyd, Wood and Ferrous Metal.
PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:01Z
Check the source to verify that this is the current version before use.

Military

MIL-L-10547	Liners, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible.
MIL-P-15328	Primer (Wash), Pretreatment, Blue (Formula No. 117-B for Metals).

STANDARDS

Federal

FED-STD-151	Metal, Test Methods.
FED-STD-595	Colors.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MS16686	Medical Services Symbol

DRAWINGS

Defense, Personnel Support Center (DPSC)
2085 Insert Cabinet, Medical Instrument and Supply Set Chest.

(Copies of specifications, standards, drawings and publications required by supplier in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Component parts. The insert shall consist of a rigid frame, including top, bottom, uprights, and shelves, made of metal, which is resistnt to corrosion or protected against corrosion; twenty-one (21) drawers made of shatter-resistant and abrasion-resistant plastic, each divided by removable partitions made of the same plastic into twelve (12) equal compartments; and one drawer made of metal with a removable plastic front window. The sizes of the drawers and their general arrangement shall be as shown in the drawing. The top of the frame is provided with metal reinforcing channels; the bottom with a single metal reinforcement channel.

3.2 Materials. Except as specified herein, materials shall conform to the applicable portions of the specifications, standards, and drawing listed in section 2, and be subjected to the tests and meet the requirements specified therein. When materials to be used are not specifically designated, those used shall be entirely suitable for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:01Z
Check the source to verify that this is the current version before use.

3.2.1 Carbon steel. Carbon steel strips and sheets shall conform to QQ-S-698, and shall be cold-rolled. Cold-rolled strip steel shall be condition No. 2, half-hard temper. Cold-rolled sheets shall have an approximate 65B Rockwell hardness.

3.2.2 Plastic.

3.2.2.1 Drawers, partitions, and drawer front. Plastic for drawers and partitions shall be super high impact polystyrene plastic (see 6.4) Color shall be natural. Plastic for the front window of drawer "E" (see drawing) shall be clear, transparent, colorless, cellulose acetate butyrate.

3.2.2.2 Tab pulls. Plastic for the tab pulls shall be made of a clear, transparent, colorless, polymerized or copolymerized flexible vinyl sheet suitable for the purpose intended.

3.2.3 Rivets. Rivets shall be brass, flathead tubular rivets with caps. Rivets shall have the following dimensions; shank diameter, 0.125 inch $\pm$ 0.005 inch, head diamter, 0.312 inch $\pm$ 0.010 inch; height of head, 0.32 inch $\pm$ 0.005 inch; and the length shall be suitable to accomplish secure riveting for the purpose intended. Rivets and caps shall be given a black oxidized finish.

3.2.4 Primer. Primer shall conform to TT-P-636.

3.2.5 Enamel. Enamel shall conform to TT-E-527. The color of the enamel shall conform to color 34087 (lusterless olive drab) of FED-STD-595, except that for marking, as specified in 3.5.1, the color shall be 37038 (lusterless black) of the same standard (see 6.5).

3.2.6 Screws. Screws for securing the insert in the chest when used as intended, shall be steel, cadmium-plated. Each insert shall be provided with two screws.

3.3 Construction. Construction shall conform to the requirements specified herein and as shown in the drawing. Each drawer shall fit in its designated location and shall slide freely when tested as specified in 4.3.1.

3.3.1 Frame. The frame shall be constructed from carbon steel as specified in 3.2.1. Shelves and uprights shall be properly located to accommodate the drawers as shown on the assembly drawing. The spaces between the upper edges of the drawers and the under surfaces of the shelves above the drawers shall be kept at a minimum commensurate with the requirements of this specification. The steel frame and channels shall be assembled by spot welding.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:01Z
Check the source to verify that this is the current version before use.

3.3.2 Drawers and partitions.

3.3.2.1 Drawers. The drawers, except drawer "E", as specified in 3.3.2.3, shall be injection molded of plastic as specified in 3.2.2.1.

3.3.2.2 Partitions. Partitions shall be removable, and shall be made from plastic as specified in 3.2.2.1. Each drawer, except drawer "E" (see drawing), shall be provided with removable partitions. Drawers shall be provided with ribs to form slots to accommodate the partitions.

3.3.2.3 Drawer "E". Drawer "E" shall be made from steel as specified in 3.2.1, except for the removable front window which shall be made from plastic as specified in 3.2.2.1. The four vertical corners of the metal drawer "E", shall be either welded with a continuous bead which shall be ground smooth, be clean, nonporous, and sound, or shall be formed by having the two sides or two ends formed with tabs 4 13/16 inches high and 1/2 inch wide at each end, bent 90° and spot welded on the inside with at least four spot welds, to the adjoining sides or ends. The tabs of the front of the drawer, if tabs are involved in the construction of the front of the drawer, may be cut out to allow for the placement of the angle brackets. No tabs shall appear on the outside of the drawer. All sharp or rough edges and corners shall be broken.

3.3.3 Tab pulls. Tab pulls for drawers shall be made from vinyl sheet as specified in 3.2.2.2, and shall be firmly and securely attached to the drawers by means of rivets as specified in 3.2.3. Rivets shall be smoothly finished on the inside of the drawers, and shall have no rough or sharp edges, etc., which might create a hazard to personnel using the cabinet and shall not interfere with easy insertion and removal of partitions.

3.3.4 Welding. Welding shall be done by qualified welders using appropriate equipment in a qualified process. Spot welds shall be capable of developing the tensile strength of the parent metal. All exposed spot welds shall be smoothed sufficiently so as to present a uniformly smooth surface with the surrounding area.

3.4 Finish. All carbon steel parts, after thorough cleaning and chemical degreasing, shall be treated with phosphate coating conforming to Type I or Type II of TT-C-490, or a primer pretreatment coating conforming to MIL-C-15328, then, all accessible surfaces of the steel parts, after thorough cleaning and chemical degreasing, shall be given one coat of primer as specified in 3.2.4 and two coats of lusterless olive drab enamel as specified in 3.2.5. The final coat of enamel shall level out to produce a smooth and uniform film free of brush marks, orangepeel, runs, wrinkles, drops, areas of thin film and any trace of grit or coarse particles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:01Z
Check the source to verify that this is the current version before use.

3.5 Marking for Identification.

3.5.1 Marking of frame and back of drawer "E". The steel frame and back of drawer "E" shall be legibly and permanently marked with black enamel as specified in 3.2.5, and as shown in the drawing.

3.5.2 Marking of the drawers. The drawers, except as specified in 3.5.1, shall be permanently and legibly marked with a Medical Services Symbol molded into the plastic drawer bottoms, as shown in the drawing. The Medical Services Symbol shall conform to type I or III of MS16686.

The numbers shown on the front of the drawers (see drawing) shall be legibly and permanently marked in a bright orange color.

3.5.3 Decalcomania. No decals shall be used for markings for identification.

3.6 Workmanship. Workmanship shall be first class throughout. Completed inserts shall be free from defects which detract from their appearance or may impair its serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:01Z
Check the source to verify that this is the current version before use.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the steel sheet and strip, primer and enamel, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the FSN, the item identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Quality conformance inspection. The examinations and tests required to assure conformance of those items or lots of items to be offered for acceptance are classified as specified in tables I and II (see 4.2.1 and 4.2.2) and 4.2.3.

4.2.1 Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105. The inspection levels and acceptable quality levels shall be as indicated in table I. Unit of product for examination purposes shall be one insert cabinet, complete with 22 drawers.

Table I. Sampling for Examination

Examination	Inspection level	AOL (percent defective)
For visual examination		
Major	I	2.5
Minor	I	6.5
For dimensional examination	S-1	2.5

4.2.2 Examination. The insert cabinet shall be examined for defects including, but not limited to, those listed in table II.

Table II. Classification of Defects

Major	
101	Any component missing.
102	Frame not spotwelded in accordance with drawing.
103	Screw holes not threaded.
104	Plastic window not transparent.
105	Plastic window does not fit in place.
106	Drawer tabs not installed as specified.
107	Marking on frame missing or incomplete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:01Z
Check the source to verify that this is the current version before use.

Table II. Classification of Defects (con't)

Minor	
201	Frame and metal drawer not completely enameled (thin or bare spots).
202	Frame and metal drawer not free of scratches, nicks, and burrs.
203	Plastic window not free of scratches.
204	Marking on frame not completely legible.
205	Marking on drawers missing, incorrect, or illegible.

4.2.2.1 Dimensional examination. The inserts, complete with drawers, shall be examined for defects in dimensions.

4.2.3 Sampling for tests. Sampling for tests shall be conducted in accordance with MIL-STD-105, Inspection Level S-1, Acceptable Quality Level 1.0, except that the minimum sample size shall be 3 inserts. Unit of product for test purposes shall be one insert cabinet complete with 22 drawers in numerical sequence. The same drawers shall not be used in other test frames.

4.3 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.3.1 Assembly and operation test. The insert shall be assembled in accordance with the drawing. Each of the 22 numbered drawers shall be completely withdrawn and then inserted in its proper location.

5. PREPARATION FOR DELVERY

5.1 Packaging.

5.1.1 Unit package. One insert cabinet, as specified, constitutes one unit of issue.

5.1.2 Level A. The drawers shall be secured in a closed position in such a manner as to prevent movement or damage during transit or handling. The unit shall be further protected by use of corrugated fiberboard or other suitable cushioning material to insure against marring, scratching, or damage to the unit. The cushioning material shall be secured by the use of tape, non-metallic strapping or other suitable material.

5.1.3 Level C. Units shall be packaged in accordance with the contractors standard commercial practice which will afford the degree of protection required for shipment and use of the product for its intended purpose.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:01Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level A. Each unit packaged as specified in 5.1.2 shall be packed in an exterior container designed for a type 1 load and constructed in accordance with PPP-B-585, class 3, style 3; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-636, class weather-resistant. Fiberboard boxes shall conform to the special requirements as specified in Table II of PPP-B-636. The unit shall be blocked, braced and cushioned within the container in such a manner as to prevent movement or damage during shipment and handling.

5.2.1.1 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes.

5.2.1.2 Closure. Closure of wood boxes shall be in accordance with appendix of applicable box specification. Closure of each fiberboard box shall be as specified in the appendix, and waterproofing shall conform with 30.4 of PPP-B-636.

5.2.1.3 Strapping. Strapping, when required, shall be in accordance with appendix of applicable box specification.

NOTE: Strapping shall not be required for shipments forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.

5.2.2 Level B. Each unit packaged as specified in 5.1.2 shall be packed in an exterior container designed for a type 1 load and constructed in accordance with PPP-B-601 domestic type or PPP-B-636, class domestic. Fiberboard boxes shall conform to the special requirements specified in table 1 of PPP-B-636. The unit shall be blocked, braced and cushioned within the container in such a manner so as to prevent movement or damage during shipment and handling. Closure of wood boxes shall be as specified in the appendix of the box specification. Closure of fiberboard boxes shall conform to method II as specified in PPP-B-636.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking. Exterior containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:01Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. This insert cabinet is listed as a component of the 6545-919-1500 Medical Instrument and Supply Set, Dispensary,Field.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 The medical field chest mentioned in 1.1 is covered by Stock No. 6545-914-3480, Chest, Medical Instrument and Supply Set, Field, No. 3, 30 inches Long by 18 inches Wide by 10 inches Deep. Copies of purchase description covering this item may be obtained upon application to the procuring activity or as directed by the contracting officer.

6.4 The plastic specified in 3.2.2.1 for drawers shall be Dow Chemical Company's STYRON 495 super high impact polystyrene, or equal.

6.5 Availability of color chips. The individual 3-by 5-inch chips of the colors referenced in 3.2.5 are available from the Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, Pa. 19120.

6.6 The insert cabinet covered by this specification is listed in the Federal Supply Catalog under the following stock number:

Federal Stock Number	Item Identification
6545-299-8649	Insert Cabinet, Medical Instrument and Supply Set Chest

6.7 This specification does not include all types, classes, grades, or sizes, of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types which are normally procured to meet military requirements.

6.8 Supersession data. This specification includes requirements of MIL-I-36050, dated 17 May 1961 and Purchase Description No 8, dated 8 March 1966.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Review activities:
Army - MD
Navy - MS
Air Force - 03

Preparing Activity:
Defense Supply Agency - DM

Project Number: 6545-0011

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-I-36050A

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:01Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 South 20th Street
Philadelphia, Pa. 19101

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER
ATTN: DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA. 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:01Z
Check the source to verify that this is the current version before use.