MILITARY SPECIFICATION

LATRINE BOX, PREFABRICATED, PORTABLE, M-2

1. SCOPE

1.1 This specification covers a dual capacity, folding, portable, lightweight, field latrine. It is designed to be easily and quickly set up or folded, and is of a completely hinged construction which precludes the loss of component parts.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

MM-L-736	Lumber and Timber, Hardwood.
NN-P-530	Plywood, Flat-Panel.
QQ-A-318	Aluminum Alloy Plate and Sheet 5052.
QQ-A-362	Aluminum Alloy Plate and Sheet, Alclad 2024.
QQ-S-763	Steel Bars, Shapes, and Forgings-Corrosion Resisting.
QQ-S-766	Steel Plates, Sheets, and Strip-Corrosion Resisting.
TT-C-490	Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.
TT-E-527	Enamel, Alkyd, Lustreless.
TT-P-636	Primer Coating, Synthetic, Wood and Ferrous Metal.
UU-P-271	Paper, Wrapping, Waterproofed Kraft.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:06Z
Check the source to verify that this is the current version before use.

Military

MIL-C-5541	Chemical Films for Aluminum and Aluminum Alloys.
MIL-W-6110	Wood, Determination of Moisture Content of.
MIL-P-8296	Plywood, Overlaid.
MIL-P-8585	Primer Coating, Zinc Chromate, Low-Moisture-Sensitivity.
MIL-C-11456	Crates; Wood, Nailed, Unsheathed, Domestic Shipment, 1500 Pounds Maximum Load.
MIL-S-13518	Sealer Surface, Wood Preservative.

STANDARDS

Air Force-Navy Aeronautical

AN545	Screw-Wood, Round Head.
AN550	Screw-Wood, Flat Head, 82 Degree
AN960	Washer, Flat

Federal

Fed. Test Method Std. No. 151	Metals; Test Methods.
Fed. Std. No. 595	Colors.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MS20257	Hinge, Continuous.
MS20426	Rivet, Solid, Countersunk 100°, Precision Head, Aluminum and Aluminum Alloy.
MS20427	Rivet, Solid-100° Countersunk Head, Carbon Steel, Corrosion-Resistant Steel, Monel and Copper.
MS20470	Rivet, Solid-Universal Head, Aluminum and Aluminum Alloy.

DRAWING

Defense Medical Supply Center

5040	Latrine Box, Prefabricated, Portable, M-2 (4 sheets), and Bill of Material.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:06Z
Check the source to verify that this is the current version before use.

2.2 Other publication. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

U.S. DEPARTMENT OF COMMERCE

Commercial Standard CS45-60 Douglas Fir Plywood.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D.C. Price to be obtained from the Superintendent of Documents).

3. REQUIREMENTS

3.1 Materials. Except as specified herein, materials shall conform to the applicable portions of the specifications, standards, and drawing (with bill of material) listed in section 2, and shall be capable of meeting the requirements shown therein. In addition, the metals shall conform to the chemical requirements of their applicable specifications when tested as specified in 4.4.1. When materials to be used are not specifically designated, those used shall be of the highest commercial quality, and suitable for the purpose intended.

3.1.1 Panels. The top panel, seat covers, and seat seal covers shall be plastic-faced plywood, conforming to type I or type II of Specification MIL-P-8296. The plywood shall be 3-ply, 3/8 inch thick. Front, back, and side panels shall conform to Commercial Standard CS45 and Specification NN-P-530 for Douglas fir, exterior type, grade AC, 3-ply, 3/8 inch thick.

3.1.2 Stiffeners. Stiffeners for the top panel shall be constructed of kiln-dried ash, oak, or maple conforming to Specification MM-L-736. Wood shall be free of checks, decay, wormholes, knots, etc., or other defects. The moisture content shall be 12 to 16 percent when tested as specified in 4.4.1.

3.1.3 Base plates. Base plates shall be fabricated from aluminum 5052-H34 conforming to Specification QQ-A-318.

3.1.4 Base plate hinges. Base plate hinges shall be made of AISI 1010 or 1020 carbon steel.

3.1.5 Seat hinges and upright hinge. Seat hinges and upright hinge shall be made of aluminum 5052-H34 conforming to Specification QQ-A-318.

3.1.6 Rivets and washers. All aluminum rivets shall be 2117-T4, anodized, as specified on drawing. Washers shall be made of flat aluminum, 2024-T3, conforming to Specification QQ-A-362.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:06Z
Check the source to verify that this is the current version before use.

3.1.7 Spring hinges. Spring hinges shall be steel, nickel- or brass-plated, H.H. Silverman & Sons Co., Inc.'s Catalog No. 616, or Stanley Works Hinge No. 343-N-2N.

3.1.8 Locking screw and hinge pins. Locking screw and hinge pins shall be of corrosion-resisting steel conforming to class 302 or 304 of Specification QQ-S-763. As an alternate, the hinge pins may be brass.

3.1.9 Locking screw retainer. Locking screw retainer shall be made of steel conforming to class 1 or class 2 of Specification QQ-S-766.

3.2 Construction. The portable latrine shall be two-place and box-shaped, with the seats facing the shorter sides hereinafter referred to as the ends. In the set-up condition, the latrine shall measure 40-3/4 inches long by 16 inches wide across the top, with the seats 18 inches above the ground line. The unit shall be provided with hinged aluminum base plates. The unit shall be simple and easy to set up and dismantle, and shall be secured in the dismantled condition by means of a locking screw and retainer. The procedure is setting up the latrine, starting from the dismantled condition, shall be as follows:

(a) The locking screw shall be unfastened.

(b) The side and end assembly shall be unfolded to form a rectangle, and the base plates shall be extended on all four sides.

(c) The top shall be dropped to the sides.

Dismantling the unit shall be accomplished in the reverse order. The construction shall conform in all details to the requirements specified herein and as shown in the drawing.

3.2.1 Top and cover assembly. The top shall consist of a plywood panel, hinged to one side panel of the base with a continuous hinge, each leaf 2 inches wide as shown in the drawing. The seat covers shall be hinged to the top panel over each toilet opening. The plywood top shall have two cutouts with smoothly lipped peripheries which have been filled with an appropriate waterproof wood filler, consisting of a mixture of one part aluminum powder and one part spar varnish by volume, then painted olive drab to match the existing color of the plywood, and smoothly sanded. The cover hinges shall be spring-loaded, so that the covers will remain tightly closed when the latrine is not in use. The upper face of the top shall be entirely smooth all around with a rounded edge. All edges shall be treated with dope as described above. The cover assembly shall consist of two surfaced plywood sections screwed together with brass screws, an upper retangular section and a lower section shaped to fit the cutout in the top. The rectangular section shall have a smooth lip all around, except on hinged side, and shall be provided with a fingerhole for ease in elevating the lid. Construction shall be as shown in the drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:06Z
Check the source to verify that this is the current version before use.

3.2.2 Side and end panels. The side and end panels shall serve as the latrine enclosures. The side panels shall run the full length of the top panel, and each side panel shall be hinged to the end panels with a continuous hinge, each leaf 1 inch wide, as shown in Standard MS20257 for part number MS20257-P6-1788. To the base of each side panel, there shall be hinged at three points, a side panel base plate. To the base of each end panel, there shall be hinged at two points an end panel base plate.

3.2.3 Base plates. The side and end panels shall each be fitted with a base plate to provide a load-bearing surface and to seal off the latrine pit. Base plates shall be fabricated from aluminum. Construction shall be in accordance with the drawing. In addition, the ends of the hems on base plates shall be tightly closed or shall be sealed by welding so as not to present any crevices for the accumulation of dirt.

3.3 Weight. The finished weight of the latrine shall not exceed 40 pounds.

3.4 Finish.

3.4.1 Prior to assembly.

3.4.1.1 Wood sections. The wood section shall be sanded and shall have all sharp corners and edges removed. Wood surfaces, not plastic coated, shall be sealed with one coat of wood sealer in accordance with Specification MIL-S-13518.

All surfaces shall be given one coat of primer conforming to Specification TT-P-636 and one coat of enamel conforming to Specification TT-E-527. The color of the enamel shall conform to color 34087 (lusterless olive drab) of Federal Standard No. 595 (see 6.2).

3.4.1.2 Steel parts. Base plate hinges shall be pretreated with phosphate coating conforming to type I finish of Specification TT-C-490. The phosphate coating shall be followed by an overall coating of synthetic primer conforming to Specification TT-P-636 and one coat of enamel conforming to Specification TT-E-527. The color of the enamel shall be color 34087 (lusterless olive drab) of Federal Standard No. 595 (see 6.2).

3.4.1.3 Aluminum parts. Aluminum parts shall be passivated with a chemical film in accordance with Specification MIL-C-5541, followed by one coat of zinc-chromate primer, 0.4 to 0.6 mil (dry film) thick, in accordance with Specification MIL-P-8585 and one coat of enamel conforming to Specification TT-E-527.

3.4.2 After assembly. After assembly, all surfaces shall be given a finish coat of enamel as specified in 3.4.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:06Z
Check the source to verify that this is the current version before use.

3.5 Identification marking. Each latrine shall be provided with a nameplate. This plate shall contain the manufacturer's name or registered trade-mark and shall be aluminum, brass, or formica engraving stock. The nameplate shall be located on the underside of the top of the latrine and shall be affixed to the latrine with four roundhead, brass, wood screws.

3.6 Workmanship. Workmanship shall be first class throughout. Latrines shall be free from roughness, splinters, or other defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier responsibilities for inspection. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection, as used in this specification, is defined as both examination (such as visual, etc., investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.2 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with Standard MIL-STD-105.

4.2.2 For tests. Sampling for tests shall be conducted in accordance with Standard MIL-STD-105.

	Inspection level	AQL (percent defective)	Minimum sample size
Component material testing	L2	*	3

*Acceptance number shall be zero (0) for all sample sizes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:06Z
Check the source to verify that this is the current version before use.

4.2.3 For chemical analysis of metals. Four ounces of each lot of each metal used in the construction of the latrine box shall be selected for chemical analysis as specified in 4.4.1.

4.2.4 Component materials. Sufficient samples of the component materials shall be selected from each lot of material used in the manufacture of the latrine box to perform tests as required by the applicable subsidiary specifications and by tests specified herein. When sample size for component materials covered by the subsidiary specifications is not specified, the sample size for each test shall be as indicated in 4.2.2. The unit of product for testing shall be the quantity of material necessary to perform all required tests one time each, taking into consideration the fact that, where possible, the same material may be used to perform two or more tests.

4.3 Examination. The latrine box shall be examined to determine compliance with all requirements contained in this specification.

4.4 Tests. Tests shall be conducted, as necessary, to determine compliance with specification requirements.

4.4.1 Chemical analysis of the metals. The samples selected in accordance with 4.2.3 shall be analyzed in conformance with methods 111 or 112 of Federal Test Method Standard No. 151. In case of dispute, method 111 shall be used for referee analysis.

4.4.2 Moisture content. Moisture content shall be determined in accordance with the procedures set forth in Specification MIL-W-6110.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Level A.

5.1.1 Unit of issue. One (1) latrine box, as specified, constitutes one unit of issue.

5.1.2 Unit preparation. Each unit shall be protected by wrapping with kraft paper and cushioning with excelsior pads or flexible corrugated fiberboard or other suitable materials. Wrapping and cushioning materials shall be secured by tying with cotton cord or tape, or by sealing with kraft gummed paper tape. Work shall be accomplished in such a manner as to insure against marring, scratching, or damage to the unit.

5.1.3 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose within the continental limits of the United States of America.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:06Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level A. Each unit shall be overpacked in an exterior container designed for type 2 load, and constructed in accordance with Specification PPP-B-601, table II, using type III, class 1 plywood, or PPP-B-621, table III. Closure and strapping shall comply with appendix of applicable specification. Each box shall be lined with a sealed waterproof barrier fabricated of material conforming to Specification UU-P-271, class H-3 (a or b), H-4, or L-2 (a or b), and sealed with a suitable waterproof adhesive. The unit shall be adequately secured within the exterior container by means of bolts, wood braces, blocks, or other suitable devices, to insure against shifting and breakage or marring of surfaces.

5.2.2 Level B. Each unit shall be overpacked in an exterior container constructed in accordance with Specification PPP-B-601, table I, using type III, class 1 plywood; PPP-B-621, table I; PPP-B-636, type I, class 1; or MIL-C-11456. The unit shall be adequately secured within the exterior container by means of bolts, wood braces, blocks, or other suitable devices, to insure against shifting and breakage or marring of surfaces.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking. Exterior container shall be marked in accordance with Standard MIL-STD-129, except as follows: The letter "L" shall precede the Federal stock number. One space shall be allowed between the letter "L" and the first digit of the stock number. The terms "Stock number" or "FSN" shall not be indicated. Service color and service symbol markings are required only on direct shipments from the contractor's plant to overseas activities.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.2 Availability of color chips. The individual 3-by 5-inch chips of the color referenced in 3.4.1.1 and 3.4.1.2 are available from General Services Administration, Business Service Center, Region 3, Seventh and D Streets, S.W., Washington 25, D.C. Price 5 cents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:06Z
Check the source to verify that this is the current version before use.

6.3 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Military requirements.

6.4 Transportation description. Transportation description applicable to this item is:

Houses or buildings NOI, aluminum and wood combined, KD or in flat sections, in boxes.

Carload minimum weight 24,000 pounds subject to Rule 34 of the Uniform Freight Classification.

Truckload minimum weight 24,000 pounds per National Motor Freight Classification.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Army-Med
Navy-BuMed
Air Force-AFCSG

Preparing activity:
Defense Medical Supply Center

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:06Z
Check the source to verify that this is the current version before use.