MIL-T-36072B (DSA-DH)
21 September 1973
SUPERSEDING
MIL-T-36072A (DMSC)
15 March 1962

MILITARY SPECIFICATION

TABLE, FOLDING LEGS, LABORATORY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of collapsible folding table.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or requests for proposals form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

NN-P-530	Plywood; Flat Panel.
TT-E-516	Enamel, Lustreless, Quick Drying, Styrenated Alkyd Type.
PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-636	Box, Fiberboard.
PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper (for Carton Sealing).

Military

MIL-W-6110	Wood; Determination of Moisture Content of.
MIL-P-52192	Primer Coating, Epoxy.

FSC 6530

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:03Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-STD-595	Colors.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

DRAWINGS

Defense Personnel Support Center (DPSC)

10073	Table, Folding Legs, Laboratory

(Copies of specifications, standards and drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Plywood. Plywood for the table top shall be Douglas Fir or Hardwood, 5 ply, 3/4 inch, conforming to NN-P-530, except as modified herein. Veneer Quality shall be not less than Grade B-B Exterior-High Density overlay. A certificate of quality from the plywood manufacturer indicating that the material meets the applicable commercial standard shall be acceptable. The color of the plastic face shall conform to color number X24087 (see 6.3) of FED-STD-595. The thickness tolerance of the complete plastic faced panels shall be plus or minus 1/32 inch. The trimming for length and width shall be full and true. The difference in length between the two diagonals of a 48 by 96 inch panel shall not exceed 1/8 inch, and for larger or smaller panels, the tolerance shall be proportionately more or less.

3.1.2 Plastic surfacing. The plastic surfacing on the finished products shall be hard, smooth, uniform in color, free from dents, creases, blisters, low pressure areas, and other defects. In defining the plywood construction, the plastic facing shall not be counted as a ply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:03Z
Check the source to verify that this is the current version before use.

3.1.3 Surface composition. The plywood shall be completely surfaced on both sides with a resin treated laminate overlay. Not less than 40 percent by weight of cured overlay of the finished material shall be a fully cured thermosetting resin of the phenol, resorcinol, or melamine type. The resin treated overlay shall be not less than 0.009 inch thick after pressing and curing including both resin and paper (or other laminate). The surface overlays may be applied to the plywood by either bonding a precured, above-type resin treated sheet to each of the surfaces of a finished, glued, plywood panel with a thermosetting resin of the same type contained in the sheet and which would be equal in performance to the glue used for bonding plywood veneers, or simultaneously curing and bonding an uncured, above-type resin treated sheet to each plywood face surface in which case the overlay sheet would furnish its own bond. The resin treated overlays may be cured and bonded to the plywood face surfaces at the same time that the glue lines of the plywood plies are cured. A two-step process is also permissible in which the plywood base panel is first cured and bonded after which the overlays are cured and bonded to the plywood face surfaces in a second hot pressing operation.

3.1.4 Other materials. Other materials not specified herein shall conform to the requirements of the Bill of Materials which forms a part of Drawing 10073.

* 3.2 Construction. Table shall conform to Drawing 10073 and this specification. All components shall be accurately aligned and assembled to provide a consistently smooth-functioning table. The plywood tabletop work surface shall be flat within 1/4 inch when a straight edge is applied diagonally between the four corners of the table. The table shall rest on all four legs, and shall not rock more than 1/16 inch.

3.2.1 Load. The table shall be without permanent set and the deflection shall not exceed 0.8 inch when tested with an 400-pound load as specified in 4.4.1. With a 50-pound additional horizontal force, the table shall not collapse or exhibit instability and the locking device of the legs shall not become unfastened, when tested as specified in 4.4.2.

* 3.2.2 Vibration. The table shall show no permanent deformation, cracks, or distortion of any components, and all working parts shall function manually, when tested as specified in 4.4.3. A test report indicating that a table, whose design and construction meet the specification requirements, has been tested and meets the vibration test specified in 4.4.3, shall be acceptable, providing such a report is from a testing agency adequately equipped and competent to perform the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:03Z
Check the source to verify that this is the current version before use.

* 3.2.3 Water absorption. When tested as specified in 4.4.4 and 4.4.4.1, the water absorption of the finished plastic-faced plywood shall not be greater than 0.35 ounce (10 grams) per square foot of single surface.

* 3.3 Welding. Welding shall be durable, sound in every detail and in accordance with latest practices recommended by the American Welding Society. All welds shall be produced by qualified welding operators with satisfactory welding equipment using suitable filler metal and/or electrode where applicable to provide the best possible weld. Surfaces to be welded shall be free from grease, oil, oxides or any other foreign matter. Any cleaning method which will remove these substances and leave the surface clean is satisfactory. All aluminum parts shall be welded within 48 hours after a chemical cleaning treatment. Parts must be chemically recleaned if the 48 hour time period is exceeded. All weld joints shall blend into the adjacent metal in gradual, smooth curves. Beads shall be smooth and free of slag, excessive undercut, or excessive spatter. Sufficient metal shall be added to provide a suitable fillet or reinforcement unless otherwise specified. Fusion through the full thickness of the base metal, in areas other than those where 100 percent penetration is a requirement of joint design, are not acceptable when welding materials over 0.050 inch in thickness. Welds shall not be oxidized. All welds shall be continuous with no visible voids, pin holes, or cracks which affect the quality, and have more strength than required for purpose intended.

3.4 Finish.

* 3.4.1 Understructure. The table understructure, including outside and all accessible inside surfaces shall receive an epoxy primer coating conforming to MIL-P-52192 followed by two coats of lustreless enamel conforming to TT-E-516 and to color X24087 (see 6.3) of FED-STD-595. Exposed fastening hardware shall be primed and enameled a matching shade of olive drab after assembly. The drive rivets may be anodized a gold color with no further treatment.

* 3.4.2 Table top. The edges of the plywood table shall be provided with a polyvinyl chloride molding having barbed sawtooth prongs on the inside surface, for application. The outside surface of the molding shall be curved and the top edge of the molding shall be flush with the top of the table. The color of the molding shall be black or shall approximate the color of the table top. The molding shall be flush with the edges of the table.

* 3.5 Identification marking. Each table shall be permanently and legibly marked with the manufacturer's name or registered trademark, the contract or purchase order number, the National Stock Number, and the letters U.S. If a nameplate is used it shall be aluminum or corrosion-resisting steel and shall be affixed to the center of the vertical flange of one longitudinal brace with aluminum or corrosion-resisting steel screws, rivets, or by welding. Marking secured by adhesives shall not be used. As an alternate, the required marking may be stamped in the center of the vertical flange of the longitudinal brace.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:03Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. Workmanship shall be first class throughout. Tables shall be free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of 3 years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual, and auditory, investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the material or component listed in the bill of material may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The Certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the Item Identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105, and Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:03Z
Check the source to verify that this is the current version before use.

Table I

	Inspection level	AQL (defects per hundred units)
For visual examination		
Major defects	II	4.0
Total (major and minor defects combined)	II	6.5
For dimensional examination	S-2	4.0

4.2.2 For tests. Except for the water absorption test, tests shall be performed on two sample tables from the total contract quantity in accordance with table II for the characteristics specified with no indication of failure. For the water absorption test, four 4-1/2 by 4-1/2 inch panels shall be randomly selected from the lot of material used in the fabrication of the tabletops.

Table II

Characteristic	Requirement	Test method
Static load test	3.2.1	4.4.1
Horizontal force test	3.2.1	4.4.2
Vibration test	3.2.2	4.4.3
Water absorption test	3.2.3	4.4.4 and 4.4.4.1

4.3 Examination. The tables shall be examined to determine compliance with all requirements contained in this specification.

4.3.1 Classification of defects. Examination shall be conducted in accordance with the following classification of defects, as shown in table III.

Table III. Categories and defects*

Categories	Defects
Major	
101	Finish not color specified.
102	Finish not free of poor adhesion; i.e., blistering, checking, or peeling.
103	Any component missing.
104	Any component malformed, dented, buckled, or bent, affecting serviceability.
105	Any part not free of sharp edges and projections.

Cont'd

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:03Z
Check the source to verify that this is the current version before use.

Table III. Categories and defects* (cont'd)

Categories	Defects
Major (cont'd)	
106	Any weld not present where specified.
107	Weld not fused, not free of burns, cracks; and fractures.
108	Top not smooth.
109	Top not flat to within 1/4 inch when checked with straight edge.
110	Top not free of gouges, chipped veneer, and any delamination.
111	Table legs do not fold properly or not located as specified.
112	Any component misaligned, affecting serviceability.
Minor	
201	Finish not free of tackiness, soft runs, and sags.
202	Finish not smooth or uniform; not free of imbedded foreign matter.
203	Finish not free of scratches, bare spots, and areas of visibly thin coating.
204	Edge surfaces of tabletop not smooth.
205	Identification marking missing, illegible, incomplete, or in wrong location.

* Examination shall not be restricted to the classified possible defects listed above.

4.3.2 Dimensional examination. The tables shall be examined for defects in dimensions. Any dimension not within the tolerances specified herein shall be classified as a defect.

4.4 Tests. Tests shall be conducted, to determine compliance with specification requirements.

4.4.1 Static load test. With the table erected and with the legs locked in the unfolded position, a dead weight of 400 pounds shall be evenly distributed on the tabletop. The table shall remain loaded for a period of not less than 8 hours.

4.4.2 Horizontal force test. With the table loaded as specified in 4.4.1, an additional 50-pound horizontal force shall be applied to a corner at a direction of 90 degrees to the long edge of the table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:03Z
Check the source to verify that this is the current version before use.

4.4.3 Vibration test. The table with the legs locked in the unfolded position shall be rigidly fastened through mounting holes on a vibrating machine and subjected to vibrations with an amplitude of 1/16 inch (1/8 inch total excursion) at a frequency of 600 cycles per minute, for a period of 1 hour in the direction of the vertical axis.

* 4.4.4 Water absorption test. Water absorption test specimens shall be weighed to the nearest 0.01 gram after preparation. They shall then be immersed in water at room temperature. A rack shall be employed in the soaking tank to separate the specimens and also to protect the sealed edges. The soaking shall continue for 48 hours, after which the specimens shall be removed from the water, blotted dry with paper towel or blotting paper, and allowed to stand for a few minutes until the surface moisture has disappeared. They shall then be weighed to the nearest 0.01 gram and the results recorded. The data thus obtained shall be converted into the terms of ounces (or grams) of water absorbed per square foot of single panel surface. Water abosrbed per square foot of single panel surface = $\frac{\text{water absorbed}}{2} \times \frac{144}{4X4}$.

* 4.4.4.1 Water absorption test specimens. One water abosrption test specimen, 4-1/2 inches by 4-1/2 inches square, shall be cut from each of the 4 test samples of each panel taken for test. At the time of test, the moisture content of water absorption test specimens shall be between 4 percent and 8 percent, determined in accordance with MIL-W-6110. The corners and edges shall be rounded and shall be sealed by dipping repeatedly in a molten mixture (50:50) of beeswax and rosin until continuous seal is attained. The edges shall be dipped just enough to produce an unsealed face area of 4 inches by 4 inches.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be Level A or C as specified (see 6.2).

5.1.1 Unit of issue. One table, as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in Table IV shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Table IV. Packaging Quantities

Unit package	Intermediate package	Exterior container
1 unit	Not required	2 units

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:03Z
Check the source to verify that this is the current version before use.

5.1.2.1 Packing variation permitted. If the required number of units in the entire shipment is less than the number of units specified to be overpacked in an exterior container, such units may be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

* 5.1.3.1 Unit package. Each unit shall be packaged in a box of appropriate size and design, constructed in accordance with PPP-B-636, class domestic, fabricated from not less than 275 pound test fiberboard. Closure shall be adequate to prevent accidental opening.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing. Packing shall be Level A, B or C as specified (see 6.2).

5.2.1 Level A.

* 5.2.1.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 3, style 3; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-636, class weather-resistant, grade V3c. Closure and strapping shall be as specified in the appendix of the applicable box specification. Special requirements for applicable Table shall apply for PPP-B-636 box. Fiberboard box shall be waterproof in accordance with paragraph 30.4 of PPP-B-636.

5.2.2 Level B.

* 5.2.2.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 1, style 3; PPP-B-601, domestic type; PPP-B-621, class 1; or PPP-B-636, class domestic. Closure shall be as specified in the appendix of the applicable box specification. Fiberboard box shall be closed by method II of PPP-B-636. Special requirements of applicable Table shall apply for PPP-B-636 box.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:03Z
Check the source to verify that this is the current version before use.

5.3 Marking.

5.3.1 Unit package. Each unit package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Folding table shall be suitable for field use as a laboratory table, examining table or medical supply table.

6.2 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification.
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 Availability of color standards. The color standards of the color referenced are available from:

Commanding General
Aberdeen Proving Ground, Maryland
Attention: Coating and Chemical Laboratory

6.4 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, which are normally procured to meet Military requirements.

6.5 This specification covers the following item listed in the Federal Supply Catalog:

National Stock Number	Item
6530-00-710-0210	TABLE, FOLDING LEGS Laboratory

6.6 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:03Z
Check the source to verify that this is the current version before use.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Review activities:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 6530-1278

Review information is current as of the date of this document. For future coordination of chang to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:03Z
Check the source to verify that this is the current version before use.