MIL-D-3018D

18 September 1968

SUPERSEDING
MIL-D-3018C
13 November 1964

# MILITARY SPECIFICATION

## DRESS, FOOD HANDLER'S, WOMAN'S

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope.- This specification covers the requirements for a cotton dress for female food handlers.

1.2 Classification.- The dresses shall be of one type in the following sizes as specified (see 6.2):

Schedule of sizes

| | | |
|---|---|---|
| 10 | 16 | 22 |
| 12 | 18 | 24 |
| 14 | 20 | 26 |

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

| | | |
|---|---|---|
| V-B-871 | - | Button, Sewing Hole, and Button, Staple, (Plastic) |
| V-T-276 | - | Thread, Cotton |
| UU-P-268 | - | Paper, Kraft, Untreated, Wrapping |
| CCC-C-432 | - | Cloth, Sheeting, Cotton, (Unbleached, Bleached, and Dyed) |
| DDD-L-20 | - | Label; For Clothing, Equipage and Tentage (General Use) |
| PPP-F-320 | - | Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes |

FSC 8415

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

MILITARY

*MIL-B-17757* - *Boxes, Fiberboard Corrugated (Modular Sizes)*

STANDARDS

FEDERAL

Fed. Std. No. 751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Guide sample.- Samples when furnished, are solely for guidance and information to the supplier (see 6.3). Variation from the specification may appear in the sample, in which case the specification shall govern.

3.2 Materials.-

3.2.1 Basic material.- The material for the dress shall be bleached cotton sheeting, conforming to type VII, class 3 of CCC-C-432.

3.2.2 Thread.- The thread for seaming, stitching and buttonhole sewing shall be cotton, Shade AH, cable No. 66050, White, ticket Nos. 50, 3 ply and 70, 2 ply, conforming to type IA2 of V-T-276.

3.2.3 Labels.- Each dress shall have an identification label and a size label or a combination label conforming to type I of DDD-L-20. The fastness to laundering requirements shall apply.

3.2.3.1 Identification label.- The identification label shall conform to class 1.

3.2.3.2 Size label.- The size label shall conform to class 2.

3.2.3.3 Combination label.- The identification and size label may be combined into one label conforming to classes 1 and 2.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

3.2.4 Buttons.- The buttons shall conform to type II, class D, style 19, 24-line of V-B-871. The buttons shall have a glossy finish and shall conform to shade DOD White BA, cable No. 62031.

* 3.3 Design.- The dress (see figure 1) is a one-piece wrap-around with attached waistband with extension belt; convertible collar; short sleeves; back waist with panel vents; five gored skirt; patch pockets on left waist and right skirt front; reinforcements at underarms and button-down shoulder loops. The front wrap, normally worn right over left, may be reversed when soiled.

3.4 Patterns.- Standard patterns, which provide an allowance of 1/2 inch for double lapped, double stitched seams, and the side seams, and 3/8 inch for all other seams will be supplied by the Government. The standard patterns shall not be altered in any way and are to be used only as a guide for cutting the supplier's working patterns. The working patterns shall be identical to the standard patterns.

3.4.1 List of pattern parts.- The dress shall be cut from the material as specified and in accordance with the following parts:

Pattern parts

| Material | Pattern nomenclature | Cut parts |
|---|---|---|
| | **Waist** | |
| Cotton sheeting, cloth | Front | 2 |
| | Center back | 1 |
| | Side back | 2 |
| | Front facing | 2 |
| | Yoke | 1 |
| | Sleeve | 2 |
| | Cuff | 2 |
| | Shield | 2 |
| | Front sleeve reinforcement | 2 |
| | Back sleeve reinforcement | 2 |
| | Collar | 1 |
| | Pocket | 1 |
| | Shoulder loop | 4 |
| | Waistband | 4 |
| | **Skirt** | |
| | Front | 2 |
| | Center back | 1 |
| | Side back | 2 |
| | Pocket | 1 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

* 3.5 Construction.-

3.5.1 Stitches, seams, and stitching.- Stitch, seam and stitching types, as specified in table I shall conform to Fed. Std. No. 751. Whenever two or more methods of seaming or stitch types are given for the same part of the operation, any one of them may be used. Where stitch type 401 is used, the looper (under thread) shall be on the inside of the dress. Unless otherwise specified, double lapped, double stitched seams shall be 3/16 to 5/16 inch gage with the outer row of stitching 1/16 inch from turned edge on outside of dress. Seam allowances shall be maintained, with seams properly sewn so that no raw edges, run-offs, twists, pleats or puckers shall result.

3.5.2 Stitches per inch.- The minimum and maximum number of stitches per inch shall be as specified in table I.

3.5.3 Thread breaks and ends of seams.- Ends of all seams and stitchings, when not caught in other seams or stitching, shall be backtacked not less than 1/4 inch. The ends of a continuous line of stitching shall be overlapped not less than 1/2 inch. Thread breaks (all stitch types) shall be secured by stitching back of the break not less than 1/2 inch. Skipped stitches or thread breaks on 401 stitch type may be repaired using 301 stitch type.

* 3.5.4 Buttonholes.- The buttonholes shall be the straight cut-after type with a finished cut length of 5/8 to 3/4 inch. The ends shall be tacked. When the purl-type buttonhole is used, the purling shall be on the outside.

* 3.6 Manufacturing operation requirements.- The dress shall be manufactured in accordance with operations requirements specified in table I. The supplier is not required to follow the exact sequence of operations. Any basting or holding stitching to facilitate manufacture is permissible provided the thread is removed or does not show on the finished garment.

3.6.1 Figures.- Figure 1 is furnished for information purposes only. To the extent of any inconsistencies between the written specification and the figure, this specification shall control.

3.6.2 Shade and size marking.- The cut parts shall be marked to insure a uniform shade and size throughout the dress. Any method of marking may be used except:

(a) Corrosive metal fastening devices.
(b) Sew-on type tickets.
(c) Adhesive type tickets which leave traces of paper or adhesive on material upon removal of tickets.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN or LOOPER |
| 1. | Cut dress.-<br><br>a. Cut the dress in strict accordance with the patterns furnished which show garment size, shape and position of pockets, warp directional lines, and notches for proper assembly of all parts.<br><br>b. Cut the long edges of the side backs and the free edge of the front facing of the waist on the selvage. The front edge of the skirt may be cut on the selvage.<br><br>c. Cut all component parts out of one piece of material, except shields, under ply of shoulder loops, and sleeve reinforcement pieces, which may be cut from ends. | | | | | |
| 2. | Replacement of damaged parts.-<br><br>a. Replace at time of cutting, any part containing a hole or weakening defect such as a smash, multiple float or loose slub.<br><br>b. Replace any part damaged during the manufacturing process by a needle chew, cut, tear, hole, mend, burn or exposed drill hole. | | | | | |
| 3. | Shade and size marking (3.6.2).-<br><br>a. Mark all component parts of the dress except those cut from ends to insure a uniform shade and size throughout the dress. | | | | | |

AMXRE Form 423
10 February 1965





Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBI LOO |
| 4. | Overedge stitching.- | | | | | |
| | a. Overedge stitch the curved bottom edge of each shield and the outside edge of each sleeve reinforcement piece. (Outside edge of reinforcement piece may be left raw and the raw edge turned under when stitching reinforcement piece to sleeve (op 8b.) | 502<br>or<br>503 | EFd-1<br>EFd-1 | 6-10<br>6-10 | 70-2<br>70-2 | 70-<br>70- |
| 5. | Make pockets.- | | | | | |
| | a. Fold point of pockets down, as indicated on patterns and with raw edge turned in, to form outside pointed hem, stitch to pocket 1/16 to 1/8 inch from folded edge. | 301 | EFb-1 | 10-14 | 50-3 | 50- |
| 6. | Make shoulder loops.- | | | | | |
| | a. Seam shoulder loop pieces together on sides and pointed end; turn, work out point and stitch 1/16 to 1/8 inch from edge. | 301<br>or<br>401<br>and<br>301 | SSe-2(a)<br><br>SSe-2(b) | 10-14<br><br>10-14 | 50-3<br>50-3<br>50-3 | 50-<br>70-<br>50- |
| | -or- | | | | | |
| | b. With shoulder loop pieces superimposed and raw edges turned in, seam sides and pointed end. | 301 | EFn-2 | 10-14 | 50-3 | 50- |
| | c. Make a buttonhole centered at the pointed end of each shoulder loop (1/4 inch off center tolerance) with the front inside end of buttonhole 1/2 to 5/8 inch from pointed end of loop (see 3.5.4). | 304<br><br><br><br>304 | | 50-52 per buttonhole including tack or<br><br>50-52 per buttonhole including tack | 50-3 (whip)<br><br>50-3 (purl) | 50- (wh<br><br>70- (pu |



AMXRE Form 423
10 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN or LOOPER |
| 7. | Make collar.- | | | | | |
| | a. Fold collar in half lengthwise and seam side edges turn and work out points. | 301 | SSa-1 | 10-14 | 50-3 | 50-3 |
| 8. | Make sleeves.- | | | | | |
| | Finished appearance.- The cuff shall be uniformly stitched and even in width and shall finish 2 to 2 1/8 inches wide. | | | | | |
| | a. Position reinforcement pieces on inside of sleeve on each side of underarm and stitch through sleeve, 1/16 to 1/8 inch from overedge stitching. (Remaining edges of reinforcement pieces may be stitched into position along seam allowances.) | 301 | LSbj-1 | 10-14 | 50-3 | 50-3 |
| | -or- | | | | | |
| | b. If edge is not overedged, turn raw edge under and stitch through sleeve 1/16 to 1/8 inch from folded edge. | 301 | LSd-1 | 10-14 | 50-3 | 50-3 |
| | c. Seam cuff to bottom of sleeve catching bottom edge of reinforcement pieces in the stitching, turn cuff to outside, force out edges and stitch 1/16 to 1/8 inch from edge. | 101 or<br>301 or<br>401 and<br>301 | SSe-2(a)<br>SSe-2(a)<br>SSe-2(a)<br>SSe-2(b) | 10-14<br>10-14<br>10-14<br>10-14 | 50-3<br>50-3<br>50-3<br>50-3 | <br>50-3<br>70-2<br>50-3 |
| | d. Turn in top edge of cuff and stitch 1/16 to 1/8 inch from edge through sleeve. | 301 | LSd-1 | 10-14 | 50-3 | 50-3 |
| | -or- | | | | | |



AMXRE Form 423
10 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN or LOOPER |
| 8. | Make sleeves.- (cont'd) | | | | | |
| | e. Cuff may be set in one operation with top and bottom raw edges turned in and stitched on double needle machine 1-3/4 to 1-7/8 inch gage. Bottom edge of reinforcement pieces shall be turned in and caught in lower row of cuff stitching. | 301<br>or<br>401 | LSk-2<br><br>LSk-2 | 10-14<br><br>10-14 | 50-3<br><br>50-3 | 50-3<br><br>70-2 |
| 9. | Sew darts and pleats in waist fronts.- | | | | | |
| | Finished appearance.- The shoulder darts shall be tapered to a point and pleats at waist shall be uniformly positioned. | | | | | |
| | a. Fold and stitch shoulder darts, as indicated on patterns, with ends of stitching securely backstitched. | 301 | OSf-1 | 10-14 | 50-3 | 50-3 |
| | b. Fold lower front pleats, as indicated on pattern, and single stitch across bottom to hold in place. Fold shall finish toward side seams on outside. | 101 or<br>301 | SSa-1<br>SSa-1 | 10-14<br>10-14 | 50-3<br>50-3 | <br>50-3 |
| 10. | Set pockets.- | | | | | |
| | Finished appearance.- The pockets shall be set smoothly, without fullness and shall be uniformly stitched. | | | | | |
| | a. Seam pocket to left waist front at marks indicated on patterns, with raw edges turned in and stitch 1/16 to 1/8 inch from folded edge. Continue the stitching along top pocket for 1/4 inch and down the width of hem parallel to side edges. | 301<br><br>301 | LSd-1<br>and<br>OSa-1 | 10-14<br><br>10-14 | 50-3<br><br>50-3 | 50-3<br><br>50-3 |



AMXRE Form 423
10 February 1955

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN or LOOPER |
| 10. | Set pockets.- (cont'd) | | | | | |
| | b. Seam pocket to right skirt front at marks indicated on patterns with raw edges turned in and stitch 1/16 to 1/8 inch from folded edge. Continue the stitching along top of pocket for 1/4 inch and down the width of hem parallel to side edges. | 301<br>301 | LSd-1 and OSa-1 | 10-14<br>10-14 | 50-3<br>50-3 | 50-3<br>50-3 |
| 11. | Attach facings to waist fronts.- | | | | | |
| | a. Seam facings to fronts from notch at step to waistline. | 301 | SSa-1 | 10-14 | 50-3 | 50-3 |
| | b. When combination label is not used, the top edge of identification label shall be stitched to selvage edge of left front facing 9 ± 1 inches down from top. | 301 | SSbd-1 | 10-14 | 50-3 | 50-3 |
| 12. | Make back waist.- | | | | | |
| | Finished appearance.- The sides of the center back panel shall be evenly hemmed and uniformly stitched. | | | | | |
| | a. Turn in side edges of center back panel with raw edge turned under and stitch 1/16 to 1/8 inch from edge forming a 1 ± 1/4-inch hem. | 301 | EFb-1 | 10-14 | 50-3 | 50-3 |
| | b. Overlap center panel on each side back in accordance with marks on pattern and join top of waist to bottom of yoke with a double lapped and double stitched seam. The yoke shall overlap the back waist. | 301<br>or<br>401 | LSc-2<br>LSc-2 | 10-14<br>10-14 | 50-3<br>50-3 | 50-3<br>70-2 |







Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN LOOPER |
| 13. | Join waist at shoulders.- | | | | | |
| | a. Seam back yoke to fronts at shoulder with double lapped and double stitched seam. The folded edge of darts shall face toward neck on inside and the yoke shall overlap the fronts. | 301 or 401 | LSc-2 | 10-14 | 50-3 | 50-3 |
| | | | LSc-2 | 10-14 | 50-3 | 70-3 |
| 14. | Set collar.- | | | | | |
| | Finished appearance.- The collar shall be smoothly joined to the neck of the dress with the ends of collar equidistant from front edge of lapels. | | | | | |
| | a. Insert collar at step notch between facing and waist and seam all plies together with top ends of facings turned back in line with top folded edge of shoulder seam and caught in seaming. | 301 | SSa-1 | 10-14 | 50-3 | 50-3 |
| | b. Notch (slash) neck seam allowance at folded edge of facing and continue stitching under collar across back of neck. Turn facings and work out lapel points. | 301 | LScf-2(a) | 10-14 | 50-3 | 50-3 |
| | c. Turn in raw edge of top collar and stitch to neck continuing stitching across ends of facings at shoulder seam, 1/16 to 1/8 inch from edge, catching the top edge of size label or combination label inserted in the collar seam at center back. | 301 | LScf-2(b) | 10-14 | 50-3 | 50-3 |
| 15. | Set sleeves and attach shoulder loops.- | | | | | |
| | Finished appearance.- The sleeves shall be set smoothly without pleats or puckers with the shoulder loops caught in seaming at sleevehead and center of loop placed 1/8 to 3/16 inch forward of center of shoulder seam. | | | | | |



AMXRE Form 423
10 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN o LOOPER |
| 15. | Set sleeves and attach shoulder loops.- (cont'd) | | | | | |
| | a. Seam sleeves to armholes with double lapped and double stitched seam, catching shoulder loops and edge of sleeve reinforcement in the stitching. The body of the dress shall lap the sleeve. | 301 | LSc-2 | 10-14 | 50-3 | 50-3 |
| | | or 401 | LSc-2 | 10-14 | 50-3 | 70-2 |
| 16. | Hem front edge of skirts. | | | | | |
| | a. Turn under front edges of skirt with raw edges turned in (when not cut on selvage) and stitch 1/16 to 1/8 inch from edge. The facings shall be of uniform width and shall finish 1-1/2 ± 3/8 inches wide. | 301 | EFb-1 | 10-14 | 50-3 | 50-3 |
| 17. | Join back of skirt.- | | | | | |
| | Finished appearance.- The joining seams of the skirt shall start and finish evenly without pleats, puckers, or raw edges. | | | | | |
| | a. Seam center back to side backs with double lapped and double stitched seam. The center back shall overlap the side backs. | 301 | LSc-2 | 10-14 | 50-3 | 50-3 |
| | | or 401 | LSc-2 | 10-14 | 50-3 | 70-2 |
| 18. | Join back skirt to back waist.- | | | | | |
| | a. Overlap waist center back on side backs and seam to skirt with double lapped and double stitched seam. | 301 | LSc-2 | 10-14 | 50-3 | 50-3 |
| | | or 401 | LSc-2 | 10-14 | 50-3 | 70-2 |



AMXRE Form 423
10 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN or LOOPER |
| 18. | Join back skirt to back waist.- (cont'd) | | | | | |
| | b. Overedge stitch the raw edge of back seam allowance from 1 to 1-1/2 inches above and below the skirt and waist joining seam. (Operation b may be omitted with overedging done after joining side seams if operation in 20c is used.) | 502<br>or<br>503 | EFd-1<br><br>EFd-1 | 6-10<br><br>6-10 | 70-2<br><br>70-2 | 70-2<br><br>70-2 |
| 19. | Set waistband.- | | | | | |
| | Finished appearance.- The waistband shall finish even in width and be uniformly stitched to waist and skirt. The waistband shall finish 2 ± 1/4 inches wide. | | | | | |
| | a. Seam waistband extensions around pointed ends: turn and work out points. | 301<br>or<br>401 | SSe-2(a) | 10-14 | 50-3<br><br>50-3 | 50-3<br><br>70-2 |
| | b. With waistband, front waist and front skirt side seam allowances aligned, insert waist and skirt between strips and seam through all plies along top and bottom edges on a double needle machine 1/16 to 1/8 inch from each edge. Continue stitching along sides to pointed end of waistband extension. | 301 or<br>401<br>and<br>301 or<br>401 | LSar-2<br>LSar-2<br><br>EFn-2<br>EFn-2 | 10-14<br>10-14<br><br>10-14<br>10-14 | 50-3<br>50-3<br><br>50-3<br>50-3 | 50-3<br>70-2<br><br>50-3<br>70-2 |
| | c. Edge stitch pointed end of waistband extension 1/16 to 1/8 inch from edge with stitching meeting and superimposed on both side stitchings in operation b. | 301<br>or<br>401 | SSe-2(b)<br><br>SSe-2(b) | 10-14<br><br>10-14 | 50-3<br><br>50-3 | 50-3<br><br>70-2 |
| | - or - | | | | | |





USA Information Systems, Inc.
(757)491-7525 / (800)872-8830
www.usainfo.com

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN or LOOPER |
| 19. | Set waistband.- (cont'd) | | | | | |
| | d. With waistband and front waist side seam allowances aligned, insert bottom edge of waist between the two plies of waistband and stitch through all plies extending stitching around pointed end of waistband extension and back along bottom edge, ending line of stitching a sufficient distance from edge of waist to allow for insertion of skirt at bottom. | 301 or 401 and 301 or 401 | SSq-2(a)<br><br>SSe-2(a) | 10-14 10-14<br><br>10-14 10-14 | 50-3 50-3<br><br>50-3 50-3 | 50-3 70-2<br><br>50-3 70-2 |
| | e. Turn waistband, work out points and stitch lower edge of under waistband to top of skirt. | 301 | LScf-2(a) | 10-14 | 50-3 | 50-3 |
| | f. With seam allowance of under waistband turned up, turn in lower raw edge of outer waistband and stitch to outside of skirt 1/16 to 1/8 inch from edge with the line of stitching continued along all edges of waistband. | 301 | LScf-2(b) and SSe-2(b) and SSq-2(b) | 10-14 | 50-3 | 50-3 |
| | g. Turn raw ends of waistbands inward at sides and stitch 1/16 to 1/8 inch from edge. | 301 or 401 | SSc-1 | 10-14 | 50-3 50-3 | 50-3 70-2 |







Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN or LOOPER |
| 20. | Join dress at sides.- | | | | | |
| | a. Join sleeve and side seams in a continuous operation from cuff edge to bottom of dress with a stitch and overedge stitch leaving a 1-3/4- to 2-inch opening centered at waistline for belt insertion. The stitch and overedge stitching shall be performed in one operation. The bight of the overedge stitching shall be 3/16-to 1/4-inch gage. Sleeve reinforcement pieces shall be caught in stitching. | 515<br>or<br>516<br>or<br>519<br>or<br>517<br>or<br>518 | SSa-2 | 10-14 | 50-3 (chain stitching)<br>70-2 (overedge stitching) | 70-2<br>70-2 |
| | | | SSa-2 | 10-14 | 50-3 (lock stitching)<br>70-2 (overedge stitching) | 50-3<br>70-2 |
| | - or - | | | | | |
| | b. Seam sleeve and side seams from cuff to bottom of dress leaving a 1-3/4-to 2-inch opening centered at waistline for belt insertion. Sleeve reinforcement pieces shall be caught in stitching. | 301<br>or<br>401 | SSa-1 | 10-14 | 50-3<br>50-3 | 50-3<br>70-2 |
| | c. Overedge stitch raw edges of sleeve and side seams from cuff to dress bottom including belt opening on the back. | 502<br>or<br>503 | SSa-1 | 6-10 | 70-2<br>70-2 | 70-2<br>70-2 |
| | d. Operation b and c shall be performed separately. | | | | | |



AMXRE Form 423
10 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN or LOOPER |
| * 21. | Bartack belt openings and sleeve seams on outside.- | | | | | |
| | a. Turn seam allowance toward front and bartack each belt opening on outside with a 1/4 to 1/2 inch horizontal bartack at top and bottom of waistband through side seam. | Bartack | | 28 per bartack | 50-3 | 50-3 |
| | b. Turn the seam allowance towards the front of sleeve and bartack each underarm sleeve seam at bottom of cuff, with a 1/4 to 1/2 inch bartack parallel to edge 1/8 to 3/16 inch from edge through seam allowances. | Bartack | | 28 per bartack | 50-3 | 50-3 |
| * 22. | Attach shields.- | | | | | |
| | a. Center each shield on underarm seam on inside of dress. Place raw edge of shield even with the inside folded edge of armhole seam and stitch 3/8 to 1/2 inch from raw edge of shield. | 301 | LSbj-1 | 10-14 | 50-3 | 50-3 |
| | b. Turn down shield and stitch curved edge adjacent to overedging, through waist. | 301 | LSbj-1 | 10-14 | 50-3 | 50-3 |
| 23. | Hem skirt.- | | | | | |
| | a. Turn up hem with bottom raw edges turned in distributing fullness between each gore seam, so that the bottom edge is even and seams meet (1/4 inch tolerance) and stitch 1/16 to 1/8 inch from edge. The hem shall finish 3 $\pm$ 1/4 inches wide. Side seam allowances shall be turned toward front. Bottom edge of skirt may be pre-hemmed with a tension stitch. | 301 | EFb-1 | 10-14 | 50-3 | 50-3 |



AMXRE Form 423
10 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN or LOOPER |
| 24. | Make buttonholes in lapels and waistband extension (sec 3.5.4).- | | | | | |
| | a. Make one horizontal buttonhole in each lapel 1/2 to 5/8 inch from top edge of lapel with front end of buttonhole 3/8 to 1/2 inch from front edge. | 304 | | 50-52 per buttonhole including tack | 50-3 (whip) | 50-3 (whip) |
| | | | | - or - | | |
| | | 304 | | 50-52 per buttonhole including tack | 50-3 (purl) | 70-2 (purl) |
| | b. Make two horizontal buttonholes centered (1/4 in. off center tolerance) at pointed end of left waistband extension. Front end of first buttonhole shall be 7/8 to 1 inch from pointed end and the second, 2 to 2-1/2 inches from first, measured center to center. | 304 | | 50-52 per buttonhole including tack | 50-3 (whip) | 50-3 (whip) |
| | | | | - or - | | |
| | | 304 | | 50-52 per buttonhole including tack | 50-3 (purl) | 70-2 (purl) |





Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN or LOOPER |
| 25. | Sew on buttons.- | | | | | |
| | Finished appearance.- The shoulder loops shall be smooth and flat when buttoned. The lapels shall be smooth and even and when buttoned, the collar at neck shall not be spread more than 1/2 inch apart. | | | | | |
| | a. Sew on six 24-line buttons in positions indicated, to correspond with their respective buttonholes. | 301 or 101 or hand | | 14-16 per button<br>20-24 per button 8 stitches of double thread with ends tacked | 50-3<br>50-3 | 50-3 |
| | (1) One button each shoulder seam. | | | | | |
| | (2) One button each waist front through facing. | | | | | |
| | (3) Two buttons centered on right waistband extension (1/4 inch off center tolerance). Button shall be 7/8 to 1 inch from pointed end of the waistband and the second button shall correspond with the other buttonhole. | | | | | |
| 26. | Clean dress.- | | | | | |
| | a. Trim all thread ends and remove all loose threads from dress. | | | | | |
| | b. Remove all spots, stains and shade or size markings. | | | | | |
| 27. | Press dress.- | | | | | |
| | a. Press dress smooth and flat with heated pressing iron or machine. | | | | | |

AMXRE Form 423
10 February 1965





Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| NO. | MANUFACTURING OPERATIONS REQUIREMENTS TABLE I | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | |
|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN or LOOPER |
| 27. | Press dress.- (cont'd)<br><br>b. Thread waistband extensions through side openings, with right front on top, and button. Button lapels and shoulder loops. | | | | | |
| 28. | Examine and fold for packing (see 5.1.1).- | | | | | |



AMXRE Form 423
10 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

3.7 Measurements.- The finished dress shall conform to the measurements specified in table II.

TABLE II.- Measurements in inches

| | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 24 | 26 | Tolerance ± |
|---|---|---|---|---|---|---|---|---|---|---|
| Cross back width | 14-5/8 | 15-1/8 | 15-5/8 | 16-1/4 | 16-7/8 | 17-1/2 | 18 | 18-1/2 | 19 | 3/8 |
| Back length | 46 | 46-1/2 | 47 | 47-1/2 | 48 | 48-1/2 | 49 | 49 | 49 | 3/4 |
| Sweep | 75 | 77 | 79 | 81 | 83 | 85 | 87 | 92 | 94 | 2 |

3.7.1 Methods of measuring.- The dress shall be buttoned, placed smooth and flat upon a table and measured as follows:

Cross back width - From armhole seam to armhole seam along bottom edge of yoke.
Back length - From collar seam down back to bottom edge of dress.
Sweep - From front edge along bottom of hem to opposite front edge.

3.8 Workmanship.- The finished dress shall conform to the quality of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

4.2 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Component and material inspection.- In accordance with 4.1 above, components and materials shall be tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase documents. All test reports shall contain the individual values utilized in expressing the final result.

4.2.2 Examination of end item.- The classification of defects found during the examination shall be in accordance with list shown in 4.2.2.2, through 4.2.2.4.

* 4.2.2.1 Classification of defects.- All defects shall be classified as indicated below:

4.2.2.2 General defects.-

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| Material defects and workmanship damages | | | |
| a. Any weakening defect such as a smash, multiple float or loose slub, that may develop into a hole | X | | |
| b. Cut, tear, mend, hole, burn, or needle chew | X | | |
| c. Shade bar, or any other material defect | X | | |
| NOTE: Material defects and workmanship damages are to be classified as indicated above only when the condition is one which weakens the fabric or garment or when it is so conspicuously located as to be clearly noticeable. Non-weakening conditions which are inconspicuous shall not be classified. | | | |
| Shaded parts | | | |
| Any outside part | | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| **Cleanness** | | | |
| a. Any spot or stain: | | | |
| - on outside | | X | |
| b. Thread ends not trimmed or loose thread ends throughout dress or one or more shade tickets (if used) not removed | | | X |
| c. Visible basting or holding threads | | | X |
| **Component and assembly** | | | |
| Any component part or required operation omitted (unless otherwise classified herein) | X | | |
| **Cutting** | | | |
| Any part not cut in accordance with directional lines on patterns or specification requirements | X | | |
| **Seams and stitching** | | | |
| a. Accuracy of seaming | | | |
| 1. Any part of dress caught in an unrelated operation or stitching | X | | |
| 2. Seam twisted, puckered or pleated, affecting appearance (unless otherwise specified) | | X | |
| 3. Ends of seams when not caught in other seams or stitching backtacked less than 1/4 inch | | X | |
| 4. Stitching overlapping end of thread break, less than 1/2 inch | | | X |
| 5. Ends of a continuous line of stitching overlapped less than 1/2 inch | | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| Seams and stitching (cont'd) | | | |
| b. Gage of stitching (on edge, raise or top stitching, or turned under edges) or width of seams | | | |
| 1. Irregular, i.e., unevenly gaged or corresponding stitchings not uniformly gaged | | X | |
| 2. Not width specified or not within the range of gage specified or varying more than 1/16 inch when no range is specified | | | X |
| c. Raw edges | | | |
| 1/8 inch to 1/4 inch, inclusive | | | X |
| 1/4 inch to 3/4 inch, inclusive | | X | |
| - over 3/4 inch | X | | |
| d. Runoffs | | | |
| 1/2 inch to 1 inch, inclusive | | | X |
| - over 1 inch | | X | |
| e. Seam and stitch types | | | |
| 1. Not specified seam or stitch type | | X | |
| 2. Looper thread of 401 stitch type on the outside of dress | X | | |
| f. Stitch tension (except bartack) | | | |
| 1. Loose tension resulting in a loose seam | X | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| Seams and stitching (cont'd) | | | |
| 2. Loose tension on raise, top or edge stitching, i.e., loosely exposed loops of lower or top thread | | X | |
| 3. Tight tension (stitches break when normal strain is applied to seam or stitching) | X | | |
| NOTE: Puckering is evidence of tight tension. When puckering is evident, seam shall be tested by exerting normal pull in lengthwise direction of seam. | | | |
| g. Stitches per inch (to be scored only when the condition exists on major portion of seam) | | | |
| 1. Less than minimum number specified for | | | |
| a. All seams except labels | | | |
| - one stitch | | | X |
| - two stitches | | X | |
| - three or more stitches | X | | |
| b. Labels | | | |
| - less than minimum specified | | | X |
| 2. Any number of stitches in excess of maximum specified | | X | |
| h. Stitches skipped or broken | | | |
| 1. On joining seams | | | |
| a. Up to 1/4 inch, inclusive | | | X |
| b. 1/4 inch to 1/2 inch, inclusive | X | | |
| c. Over 1/2 inch | X | | |
| 2. On edge, top or raised stitching | | | |
| a. 1/4 inch to 1/2 inch, inclusive | | X | |
| b. Over 1/2 inch | | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| **Buttonholes (construction)** | | | |
| a. Stitching not securely caught in fabric, causing stitching to pull away from fabric | X | | |
| b. One or more broken or more than two continuous skipped stitches in one or more buttonholes | X | | |
| c. Tack (bar) on one or both ends omitted or insecure on | | | |
| - one buttonhole | | | X |
| - two or more buttonholes | | X | |
| d. Ragged edge on buttonhole, incomplete stitching or uncut | | X | |
| e. Not specified type of buttonhole | | X | |
| f. Buttonhole not corresponding to size of button so that they do not button properly | | X | |
| g. Purling on one or more buttonholes not on side specified | | | X |
| **Buttons** | | | |
| a. One or more missing, loose, insecurely sewn, broken or defective | | | X |
| b. Not specified size, type or color | | X | |
| c. Button stitching not properly locked at end of stitching cycle (tug at the loose end of the thread to determine if it will ravel) | X | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| Bartacks | | | |
| a. One or more missing, loose, insecure, or misplaced, not serving intended purpose | | X | |
| b. Loose tension on bartacks | | | X |
| Pressing | | | |
| a. Burned or scorched | X | | |
| b. Omitted or poorly pressed | | X | |

4.2.2.3 Detailed defects applicable to specific parts.-

| Defects | Classification Major? | Minor A | Minor B |
|---|---|---|---|
| Collar | | | |
| a. Top collar twisted, or tight causing edges to curl up | | X | |
| b. Edges crooked | | X | |
| c. Ends poorly shaped, or not uniform in width, length or shape | | X | |
| d. Collar ends unevenly spaced from front edges of lapel by more than 1/4 inch | | | X |
| e. Ends not securely caught in joining seam at top of lapel | X | | |
| f. Short, i.e., causing puckers or pleats on lapel, front, or yoke | | X | |
| g. Long, i.e., causing puckers or pleats on top or under collar | | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| Lapels | | | |
| a. Poorly shaped or not uniform in shape | | X | |
| b. Facing twisted or full | | X | |
| c. Lapel corners curled, caused by short or tight facing | | X | |
| d. Lapel step or edge not properly forced out | | | X |
| e. Buttonhole less than 1/2 inch or more than 5/8 inch from top of lapel, or less than 3/8 inch or more than 1/2 inch from front edge of lapel | | | X |
| Waist front closure | | | |
| a. Buttonholes off center by more than 1/4 inch of pointed end of left waistband extension | | | X |
| b. Ends of collar at neck spread more than 1/2 inch when buttoned | | | X |
| Waist front | | | |
| a. Shoulder darts not facing neck on inside or varying in length more than 1/2 inch | | | X |
| b. Pleats at waistline | | | |
| 1. Outside folds not facing side seam | | X | |
| 2. Not uniformly positioned from side seam by more than 1/2 inch or spacing between pleats varying by more than 1/4 inch on right and left fronts | | | X |
| c. Underarm shield (front and side back) | | | |
| 1. Tight or twisted | | X | |
| 2. Not centered on sleeve seam | | | X |
| d. Unbuttoned waist fronts uneven in length by more than 1/2 inch | | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| Waist front (cont'd) | | | |
| e. Buttons not sewn through facing | | X | |
| f. Waist not caught securely in waistband joining seam | X | | |
| Waist and skirt front pockets | | | |
| a. Set on crookedly | | X | |
| b. Poorly shaped | | X | |
| c. Excessively full | | | X |
| d. Hem twisted, or point off center by more than 1/4 inch | | | X |
| e. Corners not securely tacked or second row of stitching across width of hem omitted or insecure | | X | |
| f. Waist pocket not placed on left waist front or skirt pocket not placed on right skirt front | X | | |
| Shoulder loops | | | |
| a. Poorly or not uniformly shaped | | X | |
| b. Not uniform in length by more than 3/8 inch, or set on crookedly causing loop to bulge, gap or twist when buttoned | | X | |
| c. Top ply twisted or full, affecting appearance | | X | |
| d. Edges not properly forced out | | | X |
| e. Front edge at armhole unevenly positioned from shoulder seam by more than 1/4 inch, or center of loop positioned in back of shoulder seam, or more than 3/16 inch in front of shoulder seam | | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| Shoulder loops (cont'd) | | | |
| f. Buttonhole | | | |
| 1. Off center by more than 1/4 inch | | X | |
| 2. From pointed end | | | |
| - less than 1/2 inch or more than 5/8 inch from pointed end | | | X |
| g. Button | | | |
| 1. Not aligned with buttonhole causing a noticeable bulge or twist on loop or shoulder when fastened | | | X |
| 2. Not sewn through all plies | | X | |
| Shoulder seams | | | |
| Yoke not overlapping front | | | X |
| Armholes, sleeves and cuffs | | | |
| a. Sleeve lapped on body at armhole | | X | |
| b. Sleeve tight at armhole, causing puckers on waist front, shoulder loop, yoke and side back | | X | |
| c. Sleeve pleated or puckered at armhole or cuff joining seam | | X | |
| d. Sleeve reinforcement | | | |
| 1. Tight or twisted | | X | |
| 2. Stitching irregular or not uniformly stitched on sleeve fronts or backs | | | X |
| 3. Not caught in cuffband joining seam | | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| Armholes, sleeves and cuffs (cont'd) | | | |
| e. Cuff | | | |
| 1. Twisted or puckered | | X | |
| 2. Noticeably uneven in width | | | X |
| 3. Less than 2 inches or more than 2-1/8 inches wide | | | X |
| 4. Bottom edge (when seamed, turned and stitched) not properly forced out | | | X |
| 5. Sleeve exposed below bottom edge of cuff for a distance of more than 1/2 inch | | | X |
| Waistband (with belt extension) | | | |
| a. Twisted | | X | |
| b. Pointed ends poorly or not uniformly shaped | | | X |
| c. Less than 1-3/4 inches or more than 2-1/4 inches wide | | | X |
| d. Noticeably uneven in width | | | X |
| e. Belt edges (when seamed, turned and stitched) not properly forced out | | | X |
| f. Stitching of under waistband to skirt exposed below edge of outside waistband | | | X |
| g. Buttonholes | | | |
| 1. Off center by more than 1/4 inch | | | X |
| 2. Buttonholes constructed on right waistband extension | | | X |
| 3. Front end of first buttonhole | | | |
| - less than 7/8 inch or more than 1 inch from pointed end of left waistband extension | | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| Waistband (with belt extension) (cont'd) | | | |
| 4. Second buttonhole | | | |
| - less than 2 inches or more than 2-1/2 inches from first buttonhole (center to center) | | | X |
| h. Button | | | |
| 1. Not aligned with buttonholes causing a noticeable bulge or twist in waistband extension when fastened, or edges of belt not aligned | | | X |
| 2. Center of first button less than 7/8 inch or more than 1 inch from pointed end | | | X |
| Skirt front | | | |
| a. Skirt not caught securely in waistband joining seam | X | | |
| b. Bottom of left front exposed below right front or front edge of right front longer than left front by more than 1/2 inch when waist front and belt are fastened | | X | |
| c. Front edges uneven in length by more than 1/2 inch | | | X |
| d. Hem on front edges | | | |
| 1. Less than 1-1/8 inches or more than 1-7/8 inches in width | | | X |
| 2. Uneven in width by more than 1/4 inch | | | X |
| Waist back | | | |
| a. Yoke not lapped on top of center back and side backs or center back not lapped over side backs | | X | |
| b. Hem on side edges of back less than 3/4 inch or more than 1-1/4 inches in width | | X | |
| c. Length of hemmed edges of center back short causing side back to be full or to gap | | | X |
| d. Puckered or pleated in joining seam to skirt | | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

| Defects | Classification Major | Minor A | Minor B |
|---|---|---|---|
| Skirt back seams | | | |
| Center back not lapped over side backs | | X | |
| **Inside of dress** | | | |
| Waist facing | | | |
| a. Top edge not turned under or not stitched down | | X | |
| b. Identification label | | | |
| 1. Missing, incorrect, illegible or insecurely caught in stitching | | X | |
| 2. Less than 8 inches or more than 10 inches down from top of left facing | | | X |
| 3. Top end not stitched to back edge of left front facing | | | X |
| Size or combination label | | | |
| a. Missing, incorrect, illegible or insecurely caught in stitching | X | | |
| b. Not inserted in seaming of top collar or not centered by more than 1 inch | | | X |
| Sleeve seam and side seams in waist and skirt | | | |
| Not turned toward front | | | X |
| Hem | | | |
| a. Twisted, affecting outside appearance or front ends extending beyond front edges more than 1/8 inch | | X | |
| b. Bottom edge irregular | | | X |
| c. Less than 2-3/4 inches or more than 3-1/4 inches in width | | X | |
| d. Hem irregular in width by more than 3/4 inch | | | X |
| e. Seams in hem turn up and skirt not aligned by more than 1/4 inch (center to center) | | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

4.2.2.4 Measurements (see 3.7).- Any measurement deviating from the nominal dimension and tolerance in table II shall be scored as a size measurement defect.

* 4.2.2.5 Inspection levels and acceptable quality levels.- The inspection levels and acceptable quality levels (AQL's) expressed in defects per 100 units (DHU) shall be as follows:

| | AQL'S | Inspection level |
|---|---|---|
| For 4.2.2.2 and 4.2.2.3 (combined) | | II |
| Major | 2.5 | |
| Major and Minor A (combined) | 15.0 | |
| Totals (Major, Minor A and Minor B combined) | 40.0 | |
| For 4.2.2.4: | | S-3 |
| One class | 4.0 | |

* 4.3 Examination of preparation for delivery requirements.- An examination shall be made to determine that packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

| Examine | Defect |
|---|---|
| Marking (exterior and interior) | Omitted, incorrect, illegible, of improper size, location, sequence, or method of application. |
| Materials | Any component missing, damaged or not as specified. |
| Workmanship | Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling. |
| | Open and non-continuous heat sealed seams and closure of polyethylene bag. Omission of vent hole in polyethylene bag. Alternative polyethylene bag not provided with tuck or reverse flap. |
| | Bulged or distorted containers. |
| Content | Number of unit packages per shipping container is more or less than required. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A.- Each dress shall be buttoned and neatly folded to approximate dimensions of 14-inches in length by 11-1/2-inches in width. The dress shall be folded in such a manner that the identification label is clearly visible. Each folded dress shall be placed in a snug-fitting flat style clear polyethylene film bag of 0.00125-inch thickness (± 20 percent tolerance). The polyethylene bag shall be formed with heat sealed seams that are straight, continuous and parallel to each other and the formed edges of the bag. The bag closure shall be effected by heat sealing with the heat seal made as close as possible to the open end. A 1/4-inch diameter hole shall be made at one corner of each bag to allow excess air to escape. Alternatively, the final closure of the polyethylene bag may be accomplished by means of a tuck or reverse flap.

5.1.2 Level C- Dresses shall be packaged to afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

5.2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.- Thirty dresses of one size only, packaged as specified in 5.1, shall be packed within a fiberboard shipping container assembled, closed, and reinforced conforming to class weather-resistant, type SF, grade V2s, size 3A of MIL-B-17757. The liner shall conform to type CF, class weather-resistant, variety DW, grade V15c of PPP-F-320. Level A packages shall be packed flat two in length, one in width, and fifteen in depth within a shipping container. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound basis weight kraft paper conforming to grade B of UU-P-268. Toward the end of the contract or when there are less than the required amount per container of the same size, mixed sizes may be packed within the same shipping container.

5.2.2 Level B.- Thirty dresses of one size only, packaged as specified in 5.1, shall be packed within a fiberboard shipping container, assembled and closed conforming to class domestic, grade 275, size 3A of MIL-B-17757. The liner shall conform to type CF, class domestic, variety DW, grade 275 of PPP-F-320. Level A packages shall be packed flat two in length, one in width, and fifteen in depth within a shipping container. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound basis weight kraft paper conforming to grade B of UU-P-268. Toward the end of the contract or when there are less than the required amount per container of the same size, mixed sizes may be packed within the same shipping container.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

5.2.2.1 When specified (see 6.2), the shipping container shall be grade V3c or V3s fiberboard box fabricated in accordance with MIL-B-17757 and closed in accordance with the appendix of the box specification. The shipping container material may also be grade V4s of PPP-F-320.

5.2.3 Level C.- Dresses, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.- In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

5.3.1 Polyethylene bagged packages.- Polyethylene bagged packages shall have the required information legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification. The bag or label shall indicate the following information:

STOCK NUMBER
NOMENCLATURE
SIZE
QUANTITY

5.3.2 Labels, mixed sizes.- Each shipping container, packed with mixed sizes shall have securely attached to the end and side, directly under the printing or stencilling, a white paper label 5 to 4-inches, with the words "MIXED SIZES" plainly stamped or printed thereon, and under these words shall be legibly stamped or printed the correct quantity and sizes contained therein.

6. NOTES

6.1 Intended use.- Dresses are intended for wear by female cooks and bakers in the Department of Defense.

* 6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Size required (see 1.2).
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 Samples.- For access to sample of the end item, address the procuring office issuing the invitation for bids.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

* 6.4 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of the document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 82

Review activities:

Army - MD
Navy - SA
Air Force - 11, 82, 85

User activities:

Navy - MC, MS

Preparing activity:

Army - GL

Project No. 8415-0305



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.