MIL-N-3019D
15 November 1982
SUPERSEDING
MIL-N-3019C
10 August 1970

MILITARY SPECIFICATION

NECKLACE, PERSONNEL, IDENTIFICATION TAG

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size of necklace for identification tags.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on the date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-766	-	Steel Plates, Sheets and Strip-Corrosion Resisting
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-676	-	Boxes, Set-up

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:02Z
Check the source to verify that this is the current version before use.

DRAWING

US ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

4-1-486 - Necklace, Personnel, Identification Tag

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.2 Materials (see 6.4) and components. Materials and components shall be as specified on the applicable drawings and as specified herein.

3.2.1 Steel, corrosion-resisting. Corrosion-resisting steel shall conform to classes 304 or 305, condition A, HR or CR of QQ-S-766.

3.3 Construction. The construction shall conform in all respects to the drawing listed in section 2 and as specified herein.

3.3.1 Loop and extension. The main loop and the extension loop shall be made up of chain. The chain shall be composed of bead shaped and dumbbell shaped elements fabricated from steel specified in 3.2.1. There shall be not less than 7 nor more than 10 bead shaped elements in each inch of necklace length. All parts of the necklace shall be freely rotatable and longitudinally movable relative to each other.

3.3.1.1 Dimensions. The overall length of the main loop including the splicing link shall be 27 inches, plus 1/4 inch, minus 0 inch. The overall length of the extension loop including the splicing link shall be 5-1/2 inches, plus 1/4 inch, minus 0 inch.

3.3.2 Splicing links. The splicing links shall be fabricated from steel specified in 3.2.1 and shall conform to the details and dimensions of Drawing 4-1-486 (see figure 1). One splicing link shall be used to join the ends of the main loop and one splicing link shall be used to join the ends of the extention loop.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:02Z
Check the source to verify that this is the current version before use.

3.4 Breaking strength. When tested as specified in 4.5.1, the main loop and the extension loop shall have a breaking strength of not less than 15 pounds nor more than 32 pounds. The section of the loop tested shall include the splicing link.

3.5 Finish. The necklaces shall be given a bright polished finish.

3.6 Marking. The contractor may place his identification on the splicing link provided there are no rough edges and the splicing link is not damaged or impaired.

3.7 Workmanship. Necklaces shall be clean, well made, and shall meet the acceptable quality levels established by this document. In addition, the necklaces shall be suitable for immediate wear, shall be flexible and non-kinking, shall be free from oil, rough surfaces or irregularities which may scratch, cut, or otherwise cause discomfort to the wearer and shall be free from other defects which will affect appearance or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3 and tested for the characteristics specified in 4.4.4. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:02Z
Check the source to verify that this is the current version before use.

4.4.2 End item visual examination. The end item shall be examined for the defects listed below. The lot size shall be expressed in units of necklaces. The sample unit shall be one necklace. The inspection level shall be I and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.0 for major defects and 4.0 for total (major and minor combined) defects.

Examine	Defect	Classification Major	Minor
Design	Not in accordance with specified requirements	X	
	All parts not freely rotatable and not longitudinally movable relative to each other	X	
Finish	Not bright		X
	Oily or dirty		X
Construction and workmanship	Any part missing, i.e., main loop, extension loop, or splicing links (1 link to join ends of main loop and 1 link to join ends of extension loop)	X	
	Not flexible	X	
	Chain kinks	X	
	Any rough surface or irregularity which may cause injury or discomfort to wearer	X	
	Splicing links are malformed, bent, or otherwise damaged, preventing assembly or disassembly of the necklace	X	
	Any defect which renders necklace unsuitable for immediate personal wear		X
	Not made of specified material	X	
	Metal cracks in beads or splicing links		X
	More than 10 or less than 7 beads per inch	X	
Marking identification	When applicable, splicing link is damaged, impaired, or has rough edges due to identification marking		X

4.4.3 End item dimensional examination. The end item shall be examined for conformance to the specified dimensions. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of necklaces. The sample unit shall be one necklace. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:02Z
Check the source to verify that this is the current version before use.

4.4.4 End item testing. The end item shall conform to the breaking strength requirements specified in 3.4 when tested as specified in 4.5.1. The lot size shall be expressed in necklaces. The sample unit shall be one necklace. Any test failure shall be classified as a defect. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.4.5 Packaging inspection. An examination shall be made to determine that preservation, packing, and marking requirements comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged with the exception that it need not be closed. Examination of closure defects listed below shall be made on shipping containers fully packaged. The lot size shall be the number of containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling. Bulged or distorted containers.
Content	Number of intermediate containers per box is more or less than required. Number of necklaces per intermediate container is less than specified. 1/

1/ For this defect, examine one intermediate container from each shipping container in the sample.

4.5 Methods of inspection.

4.5.1 Breaking strength test. Two breaking strength determinations shall be made on each sample unit (one on the main loop and one on the extension loop). The testing machine shall consist of a means of supporting the chain; a means for applying, slowly and uniformly, the load to the chain and a means for determining the applied load. The chain material shall be inserted in the machine in such a manner that there are no kinks in the chain, that the supporting means and the load applying means do not damage or distort the beads, and that the chain section tested includes the splicing link. A load of 0 to 15 pounds shall be applied uniformly

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:02Z
Check the source to verify that this is the current version before use.

over a period of 1 minute. The load shall then be uniformly increased to determine the maximum breaking strength. If the chain breaks within three beads of the clamping device the test shall be disregarded and repeated. The results shall be reported for each loop to the nearest 0.1 pound. Any result not falling within the limits specified in 3.4 shall be considered a test failure.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packing. Each necklace shall be unit packed in a 2-3/4 inches by 3-1/2 inches, end opening, coin type envelope made from kraft paper of minimum 20 pound basis weight and the open end sealed or wire stapled.

5.1.1.2 Intermediate packing. One hundred necklaces unit packed as specified in 5.1.1.1 shall be compactly packed on edge in one row in a snug-fitting, intermediate set-up paperboard box conforming to type 1, variety 2, class A, style 4 of PPP-B-676. Box closure shall be in accordance with the appendix of the container specification.

5.1.2 Commercial. Necklaces shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Two thousand necklaces, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.5.

5.2.2 Level B packing. Two thousand necklaces, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, grade 275, or type SF, class domestic of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.5.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:02Z
Check the source to verify that this is the current version before use.

5.2.3 Commercial packing. Bags, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Marking. In addition to any special marking required by the contract or purchase order, unit and intermediate packs and shipping containers shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

6. NOTES

6.1 Intended use. The necklace covered by this document is intended to be worn by military personnel to support, in a regulation manner, two personnel identification tags about their neck.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this document.
(b) When a first article is required (see 3.1, 4.3 and 6.3).
(c) Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample consisting of one complete necklace. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

6.5 Changes from the previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Preparing activity:

Army - GL

Project No. 8465-0856

Review activities:

Army - MD
Navy - CG, PE
Air Force - 82
DLA - CT

User activity:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:02Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:02Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12032 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Laboratories
ATTN: DRDNA-ES
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-N-3019D Necklace, Personnel, Identification Tag

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:02Z
Check the source to verify that this is the current version before use.