INCH-POUND

MIL-N-3019E
9 February 1990
SUPERSEDING
MIL-N-3019D
15 November 1982

MILITARY SPECIFICATION

NECKLACE, PERSONNEL, IDENTIFICATION TAG

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size of necklace for personnel identification tags.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-S-766 - Steel Plates, Sheets and Strip-Corrosion Resisting
PPP-B-636 - Boxes, Shipping, Fiberboard
PPP-B-676 - Boxes, Set-up

MILITARY

MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-731 - Quality of Wood Members for Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

4-1-486 Necklace, Personnel, Identification Tag

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.2 Materials and components. Materials and components shall be as specified on the applicable drawings and as specified herein. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.2.1 Steel, corrosion-resisting. Corrosion-resisting steel shall conform to classes 304 or 305, condition A, HR or CR of QQ-S-766.

3.3 Construction. The construction shall conform in all respects to the drawing listed in section 2 and as specified herein.

3.3.1 Loop and extension. The main loop and the extension loop shall be made up of chain. The chain shall be composed of bead shaped and dumbbell shaped elements fabricated from steel specified in 3.2.1. There shall be not less than 7 nor more than 10 bead shaped elements in each inch of necklace length. All parts of the necklace shall be freely rotatable and longitudinally movable relative to each other.

3.3.1.1 Dimensions. The overall length of the main loop including the splicing link shall be 27 inches, plus 1/4 inch, minus 0 inch. The overall length of the extension loop including the splicing link shall be 5-1/2 inches, plus 1/4 inch, minus 0 inch.

3.3.2 Splicing links. The splicing links shall be fabricated from steel specified in 3.2.1 and shall conform to the details and dimensions of Drawing 4-1-486. One splicing link shall be used to join the ends of the main loop and one splicing link shall be used to join the ends of the extention loop.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

3.4 Breaking strength. When tested as specified in 4.5.1, the main loop and the extension loop shall have a breaking strength of not less than 15 pounds and not greater than 32 pounds. The section of the loop tested shall include the splicing link.

3.5 Finish. The necklace shall be given a bright polished finish.

3.6 Marking. The contractor may place his identification on the splicing link provided there are no rough edges and the splicing link is not damaged or impaired.

3.7 Workmanship. The necklaces shall be suitable for immediate wear, shall be flexible and non-kinking, shall be free from oil, rough surfaces or irregularities which may scratch, cut, or otherwise cause discomfort to the wearer and shall be free from other defects which will affect appearance or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3 and tested for the characteristics specified in 4.4.4.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of necklaces. The sample unit shall be one necklace. The inspection level shall be I and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.0 for major defects and 4.0 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Design	Not in accordance with specified requirements	101	
	All parts not freely rotatable and not longitudinally movable relative to each other	102	
Finish	Not bright		201
	Oily or dirty		202
Construction and workmanship	Any part missing, i.e., main loop, extension loop, or splicing links (one link to join ends of main loop and one link to join ends of extension loop)	103	
	Not flexible	104	
	Chain kinks	105	
	Any rough surface or irregularity which may cause injury or discomfort to wearer	106	
	Splicing links are malformed, bent, or otherwise damaged, preventing assembly or disassembly of the necklace	107	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (cont'd)	Any defect which renders necklace unsuitable for immediate personal wear		203
	Not made of specified material	108	
	Metal cracks in beads or splicing links		204
	More than 10 or less than 7 beads per inch	109	
Marking identification	When applicable, splicing link is damaged, imparied, or has rough edges due to identification marking		205

4.4.3 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified in 3.3.1.1 and on the drawing. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of necklaces. The sample unit shall be one necklace. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.4 End item testing. The end items shall conform to the breaking strength requirements specified in 3.4 when tested as specified in 4.5.1. The lot size shall be expressed in necklaces. The sample unit shall be one necklace. Any test failure shall be classified as a defect. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

Examine	Defect
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling. Bulged or distorted containers.
Content	Number of intermediate containers per box is more or less than required. Number of necklaces per intermediate container is less than specified. 1/

1/ For this defect, examine one intermediate container from each shipping container in the sample.

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

4.5 Methods of inspection.

4.5.1 Breaking stength test. Two breaking strength determinations shall be made on each sample unit (one on the main loop and one on the extension loop). The testing machine shall consist of a means of supporting the chain; a means for slowly and uniformly applying the load to the chain, and a means for determining the applied load. The chain material shall be inserted in the machine in such a manner that there are no kinks in the chain, that the supporting means and the load applying means do not damage or distort the beads, and that the chain section tested includes the splicing link. A load of 0 to 15 pounds shall be applied uniformly over a period of 1 minute. The load shall then be uniformly increased to determine the maximum breaking strength. If the chain breaks within three beads of the clamping device the test shall be disregarded and repeated. The results shall be reported for each loop to the nearest 0.1 pound. Any result not falling within the limits specified in 3.4 shall be considered a test failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A preservation.

5.1.1.1 Unit packing. Each necklace shall be unit packed in a 2-3/4 inches by 3-1/2 inches, end opening, coin type envelope made from kraft paper of minimum 20 pound basis weight and the open end sealed or wire stapled.

5.1.1.2 Intermediate packing. One hundred necklaces unit packed as specified in 5.1.1.1 shall be compactly packed on edge in one row in a snug-fitting, intermediate set-up paperboard box conforming to type 1, variety 2, class A, style 4 of PPP-B-676. Inside dimensions of the box shall be approximately 14 inches in length, 3-3/4 inches in width, and 3 inches in depth. Box closure shall be in accordance with the appendix of the container specification.

5.1.2 Commercial preservation. Necklaces shall be preserved in accordance with ASTM-D-3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Two thousand necklaces, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. Level A intermediate packs shall be packed two in length, two in width, and five in depth. Inside dimensions of the box shall be approximately 28 1/2 inches in length, 8 inches in width, and 15 1/2 inches in depth. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.5. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class load specified (see 6.2). Stripping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Two thousand necklaces, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, grade 275, or type SF, class domestic of PPP-B-636. Level A intermediate packs shall be packed two in length, two in width, and five in depth. Inside dimensions of the box shall be approximately 28 1/2 inches in length, 8 inches in width, and 15 1/2 inches in depth. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Bags, preserved as specified in 5.1, shall be packed in accordance with ASTM-D-3951.

5.3 Palletization. When specified (see 6.2), necklaces packed as specified in 5.2.2 or 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood group I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 35 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit and intermediate packs and shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM-D-3951.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The necklace is intended to be worn by military personnel to support, in a regulation manner, two personnel identification tags.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. Type and class of unit load required (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Chain
Dog tags

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Preparing activity:

Army - GL

(Project 8465-0033)

Review activities:

Army - MD
Navy - CG, PE
Air Force - 82
DLA - CT

User activities:

Navy - MC
Air Force - 45

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

Commander
US Army Natick RD&E Center
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick RD&E Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-N-3019E	NECKLACE, PERSONNEL, IDENTIFICATION TAG

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:01Z
Check the source to verify that this is the current version before use.