MIL-D-2940A
AMENDMENT-2
5 June 1964
SUPERSEDING
Amendment-1
17 November 1959

MILITARY SPECIFICATION

DAMPENERS, FLUID PRESSURE, GAGE PROTECTION

This amendment forms a part of Military Specification MIL-D-2940A, 16 March 1959 and has been approved by the Department of Defense and is mandatory for use by the Departments of the army, the Navy and the Air Force.

Pages 1 and 2, paragraph 2.1: Under Military Specification add:

"MIL-F-21467 - Fittings, Flareless, Fluid Connection (Shipboard Use)."

and under Military Standards add:

"MS16142 - Boss, Gasket Seal Straight Thread Tube Fitting, Standard Dimensions for."

Page 3, paragraph 3.3.2: Delete and substitute:

"3.3.2 End connections.- The end connections of the dampeners shall be externally threaded on one end and internally threaded on the other end. The size of the end connections shall be in accordance with the following as specified (see 6.2):

Thread size	Applicable document
1/4 inch NPT internal	H28
1/4 inch NPT external	H28
7/16-20 internal Threaded for "O" ring	MS16142
7/16-20 external Threaded for "O" ring	MIL-F-21467

FSC 6685

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:57Z
Check the source to verify that this is the current version before use.

Page 3, paragraph 3.3.3, last sentence: Add "and IV".

Page 5, paragraph 4.5, line 3: Delete "designated" and substitute "satisfactory to".

Page 6: Add as paragraph 6.1.1:

"6.1.1 Dampeners with 1/4 inch NPT end connections are intended for use as replacements where this type of connection is acceptable. Dampeners with 7/16-20 end connections shall be used on new construction and where the dampener joins 1/4 inch OD tubing."

Page 6, paragraph 6.2: Add item (d):

"(d) Size of end connection required (see 3.3.2)."

Custodians:
Army - MO
Navy - Ships

Preparing activity:
Navy - Ships
(Project 6685-0111)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:57Z
Check the source to verify that this is the current version before use.