MILITARY SPECIFICATION

OXYGEN SYSTEMS, PORTABLE, HIGH PRESSURE, AIRCRAFT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.6, delete and substitute the following:

"3.6 Cylinder charge requirement. The cylinder shall be kept charged with a residual pressure of a minimum of 20 pounds per square inch gage (psig) to a maximum of 25 psig with oxygen conforming to MIL-O-27210, Type I. The cylinder valve shall be closed to retain the oxygen in the cylinder."

PAGE 7

5.1, line 1: Delete "or C".

5.1.1, line 2: After first sentence, add "Immediately after cleaning, the cylinder shall be charged with oxygen to the residual pressure specified in 3.6."

line 6: Delete "Directly after cleaning oxygen systems,".

5.1.2, delete in its entirety.

Custodians:
Army-AV
Navy-AS

Preparing activity:
Navy - AS
(Proj. No. 1660-0538)

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

AMSC - N/A

☆U.S. GOVERNMENT PRINTING OFFICE: 1986-605-036/42665

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:37Z
Check the source to verify that this is the current version before use.