NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-23648/10C
4 April 1995
SUPERSEDING
MIL-T-23648/10B
15 July 1988

PERFORMANCE SPECIFICATION

RESISTOR, THERMAL (THERMISTOR), INSULATED
NEGATIVE TEMPERATURE COEFFICIENT
STYLE RTH24

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for style RTH24 thermistors. This style is available in resistance ratios A and B. Terminal leads S and W are available. Resistance tolerance versus temperature characteristics F, G, J, and K are applicable through the maximum temperature of 200°C.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

SPECIFICATION

MILITARY

MIL-R-23648 - Resistor, Thermal (Thermistor), Insulated, General Specification For.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Defense Printing Service Detachment Office, Building 4D (Customer Service), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this document and references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Supply Center, Columbus, ATTN: DSCC-VAM, Post Office Box 3990, Columbus, OH 43216-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5905
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:31Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS


* 3.1 Requirements. Requirements shall be in accordance with MIL-R-23648, and as specified herein.

3.2 Design and construction. The thermistors shall be of the design, construction, and physical dimensions specified on figure 1.

3.3 Thermal time constant. The thermal time constant shall be 8 seconds maximum.

3.4 Dissipation constant. The dissipation constant shall be .35 milliwatts per degrees Celsius minimum.

* 3.5 Power rating. The thermistor shall be capable of dissipating a maximum power of 0.035 watts at 25°C. Thermistors shall be derated in accordance with figure 2.



NOTES:
1. Dimensions are in inches.
2. Millimeters are in parentheses.
3. Metric equivalents are given for general information only.

FIGURE 1. Style RTH24 thermistors.




FIGURE 2. Derating curve for high ambient temperatures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:31Z
Check the source to verify that this is the current version before use.

3.6 Resistance.

* 3.6.1 Resistance at 25°C. Standard values shall be as specified in MIL-R-23648 except that the 5 percent decade values shall also be used for resistance tolerances F and G. Minimum and maximum resistance values shall be in accordance with table I.

* TABLE I. Minimum and maximum resistance values (at 25°C) for each available resistance ratio.

Ratio 19.8 (A)	Ratio 29.4 (B)
ohms	ohms
1k min 2.7k max	10k min 27k max

* 3.6.2 Resistance at temperatures other than 25°C. Resistance at temperatures other than 100°C are determined by multiplying the zero-power resistance at 25°C by the factors shown in table II for the applicable resistance ratio.

TABLE II. Resistance temperature characteristic factors.

Temperature	Ratio 19.8 (A)	Ratio 29.4 (B)
-55	54.9	100
-15	5.77	7.38
0	2.85	3.27
25	1.00	1.00
50	.405	.360
75	.184	.148
100	.0923	.0675
125	.0503	.0340
200	.0119	.0066

3.7 Short time overload. The maximum allowable change in zero-power resistance as the result of the short time load test shall be ±0.35 percent.

3.8 Low temperature storage. The maximum allowable change in zero-power resistance as the result of the low temperature storage test shall be ±0.5 percent.

3.9 High temperature storage. The maximum allowable change in zero-power resistance as the result of the high temperature storage test shall be ±0.35 percent.

3.10 Terminal strength. When tested in accordance with 4.3, the maximum allowable change in zero-power resistance shall be ±0.5 percent.

3.11 Thermal shock. The maximum allowable change in zero-power resistance as the result of the thermal shock test shall be ±0.35 percent.

3.12 Moisture resistance. The maximum allowable change in zero-power resistance as the result of the moisture resistance test shall be ±0.5 percent.

3.13 Life. The maximum allowable change in zero-power resistance as the result of the life test shall be ±5 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:31Z
Check the source to verify that this is the current version before use.

3.14 High temperature exposure. The maximum allowable change in zero-power resistance as the result of the high temperature exposure test shall be ±0.35 percent after 100 hours, and ±0.5 percent after 1,000 hours.

3.15 Vibration, high frequency. The maximum allowable change in zero-power resistance as the result of the vibration test shall be ±0.35 percent.

3.16 Shock, specified pulse. The maximum allowable change in zero-power resistance as the result of the shock test shall be ±0.35 percent.

3.17 Immersion. The maximum allowable change in zero-power resistance as the result of the immersion test shall be ±0.35 percent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Qualification inspection. Qualification inspection is not applicable to this document.

* 4.2 Sampling and inspection. The sampling, acceptance inspection, and test procedures specified in tables IV and V of MIL-R-23648 are applicable as sampling, inspection, and test procedures of this detail specification.

4.3 Terminal strength.

4.3.1 Direct load. Direct load shall be applied gradually until the load reaches 25 grams.

4.4 Solderability (type S). The solderability test is not applicable to this specification, however, the supplier must certify that S terminal leads are solderable.

4.5 Resistance to soldering heat. The resistance to soldering heat is not applicable to this specification.

4.6 Dielectric withstanding voltage. Dielectric withstanding voltage test is not applicable to this specification.

4.7 Insulation resistance. Insulation resistance tests is not applicable to this specification.

5. PACKAGING

* 5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-R-23648.

6. NOTES

* 6.1 Notes. In addition to the notes specified herein, the notes specified in MIL-R-23648 are applicable.

* 6.2 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:31Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, AT, AV, ME
Navy - AS, CG, MC, OS
Air Force - 17, 19, 99

Preparing activity:
DLA - ES

(Project 5905-1411-06)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:31Z
Check the source to verify that this is the current version before use.