MILITARY SPECIFICATION

PROPELLANT, MIXED AMINE FUEL, MAF-3

This amendment forms a part of Military Specification MIL-P-23686A, 15 April 1964, and is mandatory for use by all Departments and Agencies of the Department of Defense.

Page 2: Delete "Table I" and substitute:

"TABLE I - Chemical and Physical Requirements

Requirements	Limits
MAF-3 assay:	
Unsymmetrical dimethylhydrazine, UDMH ($C_2H_8N_2$), MIL-D-25604, percent by weight	20.0±1.0
Diethylenetriamine, DETA ($C_4H_{13}N_3$), MIL-D-50025, percent by weight 1/	80.0±1.0
Water, max., percent by weight	1.0
Particulate, max., milligrams per liter	10.0
Density, g/ml at 25°C (77°F)	0.909-0.920
1/ Specific gravity at 20°C/20°C	0.950-0.958"

Custodians:
Army-MI
Navy-WP
Air Force-12

Review Interest:
Army-MI
Navy-WP
Air Force-12

Preparing Activity:
Navy-WP

Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

FSC 9135

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.