MIL-S-23665B(AS)
AMENDMENT 2
1 September 1972
SUPERSEDING
AMENDMENT 1
22 July 1970

MILITARY SPECIFICATION

SONOBUOYS, DETECTION DEVICES, PRESERVATION, PACKAGING AND PACKING, PROCEDURES FOR

This amendment forms a part of Military Specification MIL-S-23665B(AS), dated 12 September 1968, and has been approved by the Naval Air Systems Command, Department of the Navy.

Page 2

2.1 Add the following specification under "Military":

MIL-P-3938 - Pallet, Material Handling, Hardwood, Stringer Construction, 4 Way Partial

2.1, document source paragraph, second line: Delete "Government quality control representative." and substitute "Contract Administration Office."

Page 3

3.2.5, line 2 after "MIL-D-3464": Delete "Type II".

Page 4

3.4.1: Delete paragraph in its entirety.

3.4.2: Change to paragraph number "3.4.1".

Add new paragraph as follows:

"3.4.1.1 Functional tests of sonobuoy or detection device - After accelerated environmental tests Series I and II, the sonobuoy or detection device shall perform within the applicable specification limits."

FSC PACK

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:34Z
Check the source to verify that this is the current version before use.

3.5.2: Delete paragraph in its entirety and substitute:

3.5.2 Palletizing - Unless otherwise specified by the contracting officer, groups of two or four unit containers, as applicable, shall be palletized and secured in an upright condition as shown in Figure 3 on stringer type pallets conforming to Type I, class B, MIL-P-3938, except that the size shall be 43 1/2 by 57 1/2 inches (maximum). Pallet construction shall be modified for this size from the standard 40 by 48 inch size as necessary, but the width of the center bottom board shall be maintained at the 7 1/2 to 7 3/4 inch dimension on the 40 inch side and the distance between outside edges of the two center stringers shall be 8 inches (maximum) on the 57 1/2 inch side. Clearance for fork lift arms shall be maintained as in MIL-P-3938. Wooden top and bottom caps shall be incorporated over the unitized groups to secure, immobolize and protect the palletized load. Metal strapping shall be utilized to secure the caps tightly to the pallet. Containers shall be unitized and palletized so that there will be one frequency channel to a pallet. Where quantities do not permit this arrangement, no more than three adjacent frequency channels shall be on a pallet. All additional odd containers (in excess of multiples of two or four of a particular frequency channel) shall be shipped intermingled on one pallet.

Page 6

3.7.1, first sentence: Delete balance of sentence after "markings," and insert the following:

"each container shall be durably marked or shall have a transparent plastic envelope securely attached containing a card with the following instructions:".

3.7.2 Delete paragraph in its entirety and substitute:

3.7.2 Packing list - the packing list shall be attached to a two or four unit pack. The packing list shall be visible from the side of the pack when palletized and shall be attached only to item one of a shipment. (see 3.7.5).

3.7.3, Add the following sentence:

"Directly below the Method II label, stencil, or add a suitable label, with the following statement: IF HUMIDITY INDICATOR SHOWS PINK ON INSPECTION, ADVISE NAVAL AIR SYSTEMS COMMAND."

Page 8

4.3.2, line 5: Delete "5203", and substitute "5344".

Pages 8 and 9

4.4.1.2 End of paragraph, add:

Pallets not satisfactory and load is not immobilized or secure (3.5.2)

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:34Z
Check the source to verify that this is the current version before use.

Page 10

4.5.1.1, Delete in its entirety, and substitute the following:

"4.5.1.1 Free-fall drop test of groups - A group of two or four containers, as submitted, assembled, closed, and protected as for shipment, strapped or banded, shall be considered a specimen. The group shall be tested in accordance with Method 5007 Procedure E as a rectangular container in Fed. Test Method Std. No. 101, using the Level A drop heights. The first four drops shall be from the attitude required by Method 5007 and the last four drops shall be made so that the vertical axis of the group is at 45 degrees from the floor at impact."

4.5.2.1.1, line 3: Delete "241" and substitute "5009".

Page 12

4.5.2.2.1

(a) line 3: Delete "215", and substitute "5018".

(b) Delete the last three sentences, and substitute the following:

"The contact (impact) shall be made onto a nominal 6- by 6 inch Group IV, MIL-STD-731, wood board secured to the ground. The impact on the container shall occur at a point 62 percent of the distance from the end upon which it is standing."

4.5.2.3 and 4.5.2.4: Delete in their entirety, and substitute the following paragraphs:

"4.5.2.3 Drop test (free fall) of containers - The drop test shall be specified in Method 5007 Procedure E, rectangular containers of Fed. Test Method Std. No. 101. The drop height shall be 21 inches. The containers shall be loaded with sonobuoy or detection device, assembled, closed and protected as for shipment."

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:34Z
Check the source to verify that this is the current version before use.

"4.5.2.4 Group tipover test - The test shall be conducted using either 2 or 4 containers loaded with sonobuoy or detection device, assembled, closed and protected as for shipment, banded together, with the containers parallel lengthwise. The tipover shall be made with the banded group standing upright on the floor (on ends of the containers) in the same attitude as loaded on pallet. The contact (impact) shall be made onto the upper edge of a nominal 6- by 6-inch Group IV, MIL-STD-731 wood board, secured to the ground. When tipped over, the banded group shall impact on the wood board, at a point approximately 62 percent of the length of an individual container measured from its bottom. The banded group shall be tipped over so that two of the containers strike the edge of the wood board at the same time, with the weight of the entire banded group behind the individual containers impacted."

Page 13

4.5.2.5, line 5: Delete "241" and substitute "5009".

4.5.3, line 2, Before word "Series" delete "the" and add "Series I and".

line 3: Insert period after "function", and delete the balance of the sentence.

4.5.4 After first sentence insert the following sentence: "This stacked load shall be allowed to remain in this manner for 5 days, and shall be run concurrently with the rough handling and cyclic tests."

Page 14

6.2.1.1: Delete in its entirety and substitute following paragraph:

"6.2.1.1 First article drawings - a set of repreducible detailed drawings which includes a drawing of the proposed palletization details should be furnished to the Naval Air Systems Command, Code AIR 5344, Washington, D.C. 20360, with one copy to the Naval Air Development Center, Attention: Code VTMAE Warminster, Pennsylvania 18974. (see 3.1.) The drawings should also show internal surface area in square inches and volume in cubic inches and location of C.G. of container. The contractor

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:34Z
Check the source to verify that this is the current version before use.

ıould also submit copies of test data showing conformance to the require-
ənts of this specification. Submittal of drawings is mandatory only in
ıe first order or contract for the container under which this specification
ɜ used or when subsequent changes in design are desired. It will be under-
tood that the furnished drawing(s) can be reproduced for government use.
rawings should be in accordance with MIL-D-1000."

.3: Delete "5203" substitute "5344".

.4: Delete in its entirety.

.5: Change paragraph number to 6.4.

Page 17

.gure 3. Delete note in upper left hand side and substitute the follow-
ıg note:

NOTE: The wood caps shall be a snug fit for this total load of
ɔntainers. The space between the containers and the straps shall
ɜ filled as necessary to prevent shifting of the containers in the event
ıat pallets are impacted.

.gure 3. Delete "(optional; see note)" from right hand side of figure.

Preparing Activity:
Navy - AS
(Project No. PACK-N027)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:34Z
Check the source to verify that this is the current version before use.