MILITARY SPECIFICATION

THERMISTOR, (THERMALLY SENSITIVE RESISTOR), INSULATED NEGATIVE TEMPERATURE COEFFICIENT STYLE RTH28

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for style RTH28 thermistors. This style is available in resistance ratios A and B only. Terminal lead type S and W are available. Resistance tolerance versus temperature characteristics F, G, J, and K are applicable through the maximum temperature of 200°C.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standard. The following specification and standard form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards and supplement thereto, cited in the solicitation.

SPECIFICATION

MILITARY

MIL-T-23648	-	Thermistor, (Thermally Sensitive Resistor) Insulated, General Specification For.

STANDARD

MILITARY

MS90178	-	Standard 24-Value Series Decade for Electronic Components of 5-, 10-, and 20- Percent Tolerances.

(Copies of the specification and standard required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Electronics Supply Center, ATTN: DESC-ES, 1507 Wilmington Pike, Dayton, OH 45444-5276, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:31Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS


3.1 Requirements. Requirements shall be in accordance with MIL-T-23648, and as specified herein.

3.2 Design and construction. The thermistors shall be of the design, construction, and physical dimensions specified on figure 1.

3.3 Thermal time constant. The thermal time constant shall be 1.25 seconds maximum.

3.4 Dissipation constant. The dissipation constant shall be 0.08 milliwatts per °C minimum.

3.5 Power rating. The thermistor shall be capable of dissipating a maximum power of .014 watts at 25°C. Thermistors shall be derated in accordance with figure 2.



NOTES:
1. Dimensions are in inches.
2. Millimeters are in parentheses.
3. Metric equivalents are given for general information only.

FIGURE 1. Style RTH28 thermistors.




FIGURE 2. Derating curve for high ambient temperatures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:31Z
Check the source to verify that this is the current version before use.

3.6 Resistance.

3.6.1 Resistance at 25°C. Standard values shall be as specified in MS90178 except that the 5 percent decade values shall also be used for resistance tolerances F and G.

TABLE I. Minimum and maximum resistance values (at 25°C) for each available resistance ratio.

Ratio 19.8 (A)	Ratio 29.4 (B)
ohms	ohms
8.2 k min	82 k min
15 k max	120 k max

3.6.2 Resistance at temperatures other than 25°C. Resistance at temperatures other than 25 C are determined by multiplying the zero-power resistance at 25°C by the factors shown in table II for the applicable resistance ratio.

TABLE II. Resistance temperature characteristic factors.

Temperature	Ratio 19.8 (A)	Ratio 29.4 (B)
-55	54.9	100
-15	5.77	7.38
0	2.85	3.27
25	1.00	1.00
50	.405	.360
75	.184	.148
100	.0923	.0675
125	.0503	.0340
200	.0119	.00660

3.7 Short time load. The maximum allowable change in zero-power resistance as the result of the short time load test shall be ±.35 percent.

3.8 Low temperature storage. The maximum allowable change in zero-power resistance as the result of the low temperature storage test shall be ±0.5 percent.

3.9 High temperature storage. The maximum allowable change in zero-power resistance as the result of the high temperature storage test shall be ±.35 percent.

3.10 Terminal strength. When tested in accordance with 4.3, the maximum allowable change in zero-power resistance shall be ±0.5 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:31Z
Check the source to verify that this is the current version before use.

3.11 Thermal shock. The maximum allowable change in zero-power resistance as the result of the thermal shock test shall be ±.35 percent.

3.12 Moisture resistance. The maximum allowable change in zero-power resistance as the result of the moisture resistance test shall be ±0.5 percent.

3.13 Life. The maximum allowable change in zero-power resistance as the result of the life test shall be ±5 percent.

3.14 High temperature exposure. The maximum allowable change in zero-power resistance as the result of the high temperature exposure test shall be ±.35 percent after 100 hours, and ±0.5 percent after 1000 hours.

3.15 Vibration, high frequency. The maximum allowable change in zero-power resistance as the result of the vibration test shall be ±.35 percent.

3.16 Shock, specified pulse. The maximum allowable change in zero-power resistance as the result of the shock test shall be ±.35 percent.

3.17 Immersion. The maximum allowable change in zero-power resistance as the result of the immersion test shall be ±.35 percent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Qualification inspection. Qualification inspection is not applicable to this document.

4.2 Sampling and inspection. The sampling, acceptance inspection, and test procedures specified in tables IV and V of MIL-T-23648 are applicable as sampling, inspection, and test procedures of this detail specification.

4.3 Terminal strength.

4.3.1 Direct load. Direct load shall be applied gradually until the load reaches 5 grams.

4.4 Solderability (type S). The solderability test is not applicable to this specification, however, the supplier must certify that S terminals leads are solderable.

4.5 Resistance to soldering heat (type S). The resistance to soldering heat for type S terminals is not applicable to this specification.

4.6 Dielectric withstanding voltage. Dielectric withstanding voltage tests are not applicable to this specification.

4.7 Insulation resistance. Insulation resistance tests are not applicable to this specification.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-T-23648.

6. NOTES

6.1 Notes. In addition to the notes specified herein, the notes specified in MIL-T-23648 are applicable.

6.2 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:31Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - AS, OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - CG, MC
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5905-1129-9)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:31Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

Defense Electronics Supply Center
Dayton, OH 45444-5000

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 Alexandria, VA
POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Electronics Supply Center
ATTN: DESC-ES
1507 Wilmington Pike
Dayton, OH 45444-5276

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions - Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-23648/12B	THERMISTOR, (THERMALLY SENSITIVE RESISTOR), INSULATED NEGATIVE TEMPERATURE COEFFICIENT STYLE RTH28

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITIONS ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-19117:312
Check the source to verify that this is the current version before use.