MILITARY SPECIFICATION SHEET

ELECTRON TUBE, TRIODE, POWER

TYPE 7835

This amendment forms a part of Military Specification Sheet MIL-E-1/1401(USAF) dated 27 January 1971.

Page 2

Anode voltage standoff: Delete "35" in the Max LIMITS column and delete "psi" in UNIT COLUMN. In CONDITIONS column, change "Ec1/Ib = .01 Adc" to "EC1/Ib = .01 Adc max."

Page 4

NOTE 7: Delete present Note 7 and add new Note 7 as follows:

"Preproduction Test" and "First Article Test" are synonymous terms concerning this document. All tests and requirements listed herein shall be performed during Preproduction Testing. Sample size and acceptance criteria for Preproduction Testing shall be in accordance with Table I of MIL-E-1. Preproduction Test Reports shall be prepared in accordance with MIL-STD-831.

The preparing activity reserves the right to waive the requirements for first article testing as to those bidders offering a product which has been previously procured or tested by the Government. Bidders offering such products who wish to rely on such procurement action or test must furnish evidence with the bid that prior Government approval is presently appropriate for the pending procurement.

Page 14

Figure 6, Input Strap-Resonant Frequency Test: Change the "3.593 dia." dimension to "3.598 dia. (ref)" and change the "4.625 ±.005 dia." dimension to "4.825 ±.005 dia."

Figure 6, Note 1, second line: Change "1.03 ±.20" to "1.03 ±.02".

Figure 6, Note 2, first line: Change "1.13 ±.20" to "1.13 ±.02".

Custodian:
Air Force - 85

Review activities:
Air Force - 11, 17, 80
DSA - ES

Preparing activity:
Air Force - 85

(Project 5960-F981)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:39Z
Check the source to verify that this is the current version before use.