The documentation and process conversion measures necessary to comply with this amendment shall be completed by 30 January 1995

INCH-POUND

MIL-S-19500/322B
AMENDMENT 4
30 August 1994
SUPERSEDING
AMENDMENT 3
30 December 1990

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, SILICON, MIXER
TYPES 1N23WE, 1N23WEM, 1N23WEMR, 1N23WG, 1N23WGM, AND 1N23WGMR

This amendment forms a part of MIL-S-19500/322B, dated 16 December 1974, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Supersession information; delete and substitute:

"SUPERSEDING
MIL-S-19500/322A
20 March 1967
MIL-S-19500/233C
24 June 1970 and
MIL-S-19500/281A
6 July 1967"

After the preamble, insert the following:

"THIS SPECIFICATION INACTIVE FOR NEW DESIGN AFTER 19 September 1978"

1.2, following the table; add "Burnout by multiple RF pulses, (see 3.6)".

PAGE 2

3.3, at the end of the paragraph; add "Organic package sealants may be used at the option of the manufacturer."

3.6, delete and substitute:

"3.6 Burnout by multiple RF pulses. The following burnout by exposure to a series of RF pulses using the test conditions stated below shall be performed on a qualification basis only (LTPD = 10). End-point electrical measurements shall be group A, subgroup 2.

P = 20 watts
f = 8.8 to 9.8 GHz
R_L = 100 ohms
t_p = 6.3 nanoseconds
Exposure = 15,000 pulses minimum
Holder: see below

Test data demonstrates that the holder meeting this requirement shall be made available to the Government representative upon request (see figures 3 and 4)."

DISTRIBUTION STATEMENT A. Approved for public release;distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:21Z
Check the source to verify that this is the current version before use.

PAGE 3

* FIGURE 1: Delete "

⌀	C	.0075 TIR

"; after PINS - SEE NOTE 2, add "AND NOTE 7"; dimension 'Q' minimum inches dimension, delete ".020" and substitute ".017"; minimum millimeters column, delete ".51" and substitute ".43". After note 6, add the following:

"7. Eccentricity between both pins and the base dimension 'C' should not exceed 0.0075."

PAGE 7

4.4.3, add the following as a second sentence:

"Group C inspection shall be conducted on one lot every 6 months."

PAGE 9

TABLE II, subgroup 1, details column, second parenthetical statement; delete "Dim. N, and M and".

TABLE II, examination or test column, subgroup 2, after 1N23WG; add "A separate sample may be used for each test."

PAGE 10

TABLE II, subgroup 5, LTPD column; add "λ = 15."

PAGE 11

CONCLUDING MATERIAL; delete and substitute as printed below.

NOTE: The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

"CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC
Air Force - 19, 85, 99
DLA - ES"

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5961-1594)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:21Z
Check the source to verify that this is the current version before use.