INCH-POUND

MIL-C-48605A (AR)
AMENDMENT 1
25 September 1992

MILITARY SPECIFICATION

CONTROL ASSEMBLY R.F. (Unit 1): 11748205

This Amendment forms a part of Military Specification MIL-C-48605A, dated, 14 June 1991, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1: Add the following military specification:

"MIL-T-28800 - Test Equipment for use with Electrical and Electronic Equipment, General Specification for"

PAGE 2

2.1.1: Delete the following military standard:

"MIL-STD-2000 - Standard Requirements for Soldering Electrical and Electronic Assemblies"

2.1.2: Add the following drawing:

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete paragraph in its entirety and substitute:

"3.3.1 Vibration. The control assembly shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to sinusoidal vibrations, in each of three mutually perpendicular axes, as specified in MIL-T-28800 for Type 1, Class 2, Style A test equipment."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

PAGE 3

3.3.2, 3.3.2.1 and 3.3.2.2: Delete paragraphs in their entirety and substitute:

"3.3.2 Altitude Operating. The control assembly shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

PAGE 18

3.8: Delete paragraph 3.8 in its entirety and substitute:

"3.8 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 23

4.7.1.1: Delete paragraph 4.7.1.1 in its entirety and substitute:

"4.7.1.1 Vibration. This test shall be performed as specified in MIL-T-28800 for Type I, Class 2 Style A test equipment with the exception that Step 4.c Resonance Dwell does not apply. The control assembly shall be attached to the vibration generator directly or with a fixture, and securely held by its normal means of attachment. After vibration, the control assembly shall be tested as specified in 4.7.2 and 4.7.3 herein to determine compliance with 3.3.1."

PAGE 24

4.7.1.2: Delete paragraph 4.7.1.2 in its entirety and substitute:

"4.7.1.2 Altitude Operating. This test shall be performed as specified in Procedure II, Method 500, of MIL-STD-0810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.2."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

PAGE 44

4.8: Delete paragraph 4.8 in its entirety and substitute:

"4.8 Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.8."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1240-AB37)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.