MILITARY SPECIFICATION

ELECTRONIC UNIT: 11743131

This Amendment forms a part of Military Specification MIL-E-48491B (AR), dated 30 June 1981, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 15

3.3.10, Line 4, Delete “Figure 4” and substitute “Figure 3“.

3.3.12, Line 4, Delete “Figure 5” and substitute “Figure 4”.

3.3.15, Line 2, Delete “J2-i, the connected” and substitute “J2-i, the loads connected”.

3.3.16, Line 2, Delete “applied between J3-x and J3-m” and substitute “applied for not less than 1 sec and not greater than 2 sec between J3-x and J3-m”.

PAGE 16

Note 1, Delete "Sychronous per figure 4" and substitute “synchronous per Figure 3“.

PAGE 17

TABLE VI. output condition, Column K:

Delete:	and substitute:
"1 ON	"1 ON
2 ON	2 ON
3 ON	3 ON
4 OFF	4
5 OFF	5 OFF
6 ON	6 OFF
7"	7 ON"

PAGES 20 & 21

TABLE VIII, Delete in its entirety and substitute:

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

TABLE VIII. Target select, RESET, RBI, FEED, and 9995

Item	Input Conditions at Pins of J3 1/, 2/							Outputs 1/, 3/				
	W 7/	AA 7/	Y	Z	a	U	V	J3-m	J3-n	J3-k	Returns 5/	Range 5/ ±15
1	0	1	1	1	1	0 4/	1	OFF	OFF	ON	0	0000
2	1 4/	0 4/	1	1	1	1	1	OFF	ON	ON	1	830
3	0	1	0	1	1	1	1	OFF	ON	ON	1	830
4	0	1	1	0	1	1	1	OFF	ON	ON	1	830
5	0	1	1	1	0	1	1	OFF	ON	ON	1	830
6	1 4/	0 4/	1	1	1	1	1	OFF	ON	ON	2	1830
7	1 4/	0 4/	1	1	1	1	1	OFF	ON	ON	3	2830
8	1 4/	0 4/	1	1	1	1	1	ON	OFF	ON	4	2830
9	0	1	0	1	1	1	1	ON	OFF	OFF	4	830
10	0	1	1	0	1	1	1	ON	OFF	OFF	4	1830
11	0	1	1	1	0	1	1	ON	OFF	ON	4	2830

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:29Z
Check the source to verify that this is the current version before use.

"TABLE VIII. Target select, RESET, RBI, FEED, and 9995. Continued

Item	Input Conditions at Pins of J3 1/, 2/							Outputs 1/, 3/				
	W 7/	AA 7/	Y	Z	a	U	V	J3-m	J3-n	J3-k	Returns 5/	Range 5/ ±15
12	0	1	1	1	1	1	0	OFF	ON	ON	4	2830
13	0	1	1	1	1	0 4/	1	OFF	OFF	ON	0	0000
14	0	1	1	0	1	1	1	OFF	OFF	OFF	0	0000
15	1 4/	0 4/	1	1	1	1	1	ON	OFF	OFF	1	9995 6/

1/ Input and output signal voltage referenced to Pin J2-V.

2/ Input signal legend: 1 = logical one, digital type - A (item 3.1 of table I).
0 = logical zero, digital type - A signal (item 3.1 of table I).

3/ Output legend: ON = 0.4 + 0.4 Vdc
OFF = 13.5 ± 2.0 Vdc

4/ Signal applied for not less than one second and not greater than two seconds.

5/ Readouts to the CLRC.

6/ Range readout may be 000 or 9990.

7/ J3-W is complement of J3-AA.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:29Z
Check the source to verify that this is the current version before use.

3.3.17, Delete in its entirety and substitute:

"3.3.17 BIT test. With J2-h connected to J2-j, J2-k connected to J2-i, and with a logical one, digital type A signal applied for not less than 1 sec. and not greater than 2 sec. between J6-C and J6-L (return), the output between J6-F and J6-L shall be 0.2 ± 0.2 Vdc, and the read out shall indicate 1830 ± 15 (4.6.2.17)."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1240-A877)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.