INCH-POUND
MIL-DTL-24784/10B (SH)
15 February 2002
SUPERSEDING
MIL-DTL-24784/10A(SH)
15 March 1999

ASSOCIATED DETAIL SPECIFICATION

TRAINING AID BOOKLET (TAB) REQUIREMENTS FOR NAVAL SHIPS SYSTEMS

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification sets forth requirements for the preparation of Training Aid Booklets (TABs) for use on naval ships (see 6.1).

1.2 TAB coverage. The TAB is a schematic and pictorial representation of systems and equipment installed aboard a specific ship. TAB coverage does not include maintenance information, nor does the TAB coverage include the internal details of nomenclature type or otherwise uniquely identified systems or equipment documented by other technical manuals supplied aboard ship.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, ATTN SEA 05Q, 1333 Isaac Hull Ave SE Stop 5160, Washington Navy Yard DC 20376-5160 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A AREA TMSS
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

DEPARTMENT OF DEFENSE

MIL-DTL-24784	Manuals, Technical: General Acquisition and Development Requirements.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Standardization Documents Order Desk, 700 Robbins Avenue, Building. 4D, Philadelphia, PA 19111-5094.)

2.3 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI Y32.4	Graphic Symbols for Plumbing Fixtures for Diagrams Used in Architecture and Building Construction.
ANSI Y32.10	Graphic Symbols for Fluid Power Diagrams.

(Application for copies should be addressed to the American National Standards Institute, Inc., 11 West 42nd Street, New York, NY 10036.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

ASME Y14.38M	Abbreviations and Acronyms

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM F1000 Standard Practice for Piping System Drawing Symbols

(Application for copies should be addressed to the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS (IEEE)

IEEE 315 Graphic Symbols for Electrical and Electronics Diagrams (DoD adapted).

(Application for copies should be addressed to the Institute of Electrical and Electronics Engineers, Inc., 445 Hoes Lane, P.O. Box 1331, Piscataway, N.J. 08855-1331).

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The requirements for acquiring the product described herein shall consist of this document and MIL-DTL-24784.

3.2 Security classifications, distribution statement and destruction notice. The security classifications, distribution statement and destruction notice shall be in accordance with MIL-DTL-24784.

3.3 Deliverable products and data items. Deliverable products and data items shall be in accordance with MIL-DTL-24784 (see 6.2).

3.3.1 Final reproducible copy Final reproducible copy (FRC) shall be developed in accordance with MIL-DTL-24784 and exceptions noted herein (see 6.2).

3.3.1.1 Format and layout. All typed and illustrative matter developed for final production shall be in a horizontal (landscape) format. Layout of text pages shall be in accordance with figure 10-1. Layout of illustration pages shall be in accordance with figure 10-2 or figure 10-3, as appropriate.

3.3.1.2 Marginal copy. Marginal copy shall consist of running heads and feet of illustration titles. Marginal copy shall be located on each page as indicated in figures 10-2 and 10-3. Typography requirements (see 6.2) shall be as indicated in Table I. Format for 4-1/4 by 11 inch TABs shall be in accordance with figure 10-2 and shall maintain the same margins and marginal copy.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

TABLE I. Typography and lettering.

Use	Face and point	Case
Publication number	10 point	
Security Classification (supplement only)	12 point bold	Upper
Note (word only)	12 point extra bold	Upper
Danger (word only)	12 point extra bold	Upper
Caution (word only)	12 point extra bold	Upper
Warning (word only)	12 point extra bold	Upper
Diagram titles	12 point	Upper
Diagram Legends	8 point	Upper
Diagrams, plan views, and so forth	Not less than a letter size of 0.050 inch. Type shall be sans serif and shall be equivalent to that obtained by reducing Varityper 1040-12A, IBM 12 or 14 point registry, or IBM 14 point directory	
Front matter, general information text, and other large blocks of written matter	Upper case letter size not less than 0.060 inch with lower case letters of corresponding size. Type shall be equivalent to reductions of Vari-typer 1040-12a, IBM 12 or 14 point registry, or IBM 14 point directory	Upper or upper and lower

3.3.1.3 Running heads. The running head for each page shall include the ship applicability notation (ship class or hull number), security classification (supplement) or distribution limitation, NAVSEA publication identification number, and the generic title of the diagram or contents (see 3.6.6.1).

3.3.1.4 Running feet.

3.3.1.4.1 Page number positioning. All page numbers shall be located at the lower outside of the page, approximately 1/4 inch from the bottom and 1/4 inch from the outside edge.

3.3.1.5 Page size. Unless otherwise specified in the technical manual contract requirements (TMCR) (see 6.2), the page size for all preliminary and final TABs shall be 11 by 8-1/2 inches with a maximum image area of 9-1/2 by 7-1/2 inches (see figure 10-1). Alternate page size, when so specified in the TMCR, shall be 4-1/4 by 11 inches (see 6.2).

3.4 Arrangement. Unless otherwise specified in the TMCR (see 6.2), the manual shall be arranged in a standardized format [that is, front matter, technical content, appendices, glossaries, indices and Technical Manual Deficiency Evaluation Report (TMDER)] and appropriately divided by volume, part, chapter and section in accordance with MIL-DTL-24784 and the following.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

3.4.1 Division of coverage. The TAB shall consist of at least two unclassified volumes. A third volume (supplement) shall be used when classified information must be included in the TAB coverage. The division of coverage shall be as follows:

a. Volume 1 - Piping systems.
b. Volume 2 - Electrical and electronic systems.
c. Volume 3 - Supplement (classified data applicable to both volumes).

3.4.2 Volume and part limitation. Volumes, or parts thereof, shall not exceed 500 pages (250 sheets).

3.4.3 Cover or title page. The cover or title page shall be prepared in a horizontal (landscape) format as shown in MIL-DTL-24784.

3.5 Format and development instructions. Unless otherwise specified in the TMCR (see 6.2), the writing style, safety precautions, tabular material, graphics, and numbering shall be in accordance with MIL-DTL-24784.

3.5.1 Illustration titles. Titles shall be located adjacent to the page number. The primary source document from which the illustration was developed shall be identified immediately below the illustration title in the manner shown in figures 10-2 and 10-3.

3.5.2 Line widths. Line artwork shall be prepared with line widths of sufficient size and strength to reproduce a minimum final line width, without dropout (when reduced), of 0.01 inch.

3.5.3 Piping illustrations. Pipe sizes shall be indicated by line width. A code to indicate the pipe size scale shall appear on the illustration. Recommended pipe size scale for oversized artwork is shown on figure 10-4.

3.5.4 Electrical system illustrations. Electrical distribution wire and cable sizes shall be annotated on the illustration. Bus bars shall be depicted in rectangular form and identified accordingly.

3.5.5 Illustration size. All original artwork shall be prepared for reproduction at final sizes as indicated in table II. Original artwork shall not exceed the maximum size indicated.

TABLE II. Illustration sizes.

Maximum original	Final	Final format (printed page)
23-¾ by 18-¾	9-½ by 7-½	Single illustration page (see figure 10-2)
23-¾ by 8-¾	9-½ by 3-½	Double illustration page (see figure 10-3)

3.5.6 Multiple or parallel installations. Only one system shall be illustrated when multiple or parallel systems or components are installed in the ship. A note shall be added to the illustration to indicate the existence of the system(s) or component(s) not shown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

3.5.7 Color in illustrations When specified in the TMCR (see 6.2), only the Pantone PMS colors and variations of use identified in table III shall be used for TABs. The color-coded drawing copies shall identify each color by number and variation of use.

TABLE III. Printing colors and variations.

Color	Pantone PMS number	Acceptable for use as			
		Solid area	Solid thin line	40 percent screened area	40 percent screened line
Red	185	Yes	Yes	Yes	Yes
Yellow	108	Yes	Yes	No	No
Green	354	Yes	Yes	Yes	Yes
Blue	299	Yes	Yes	Yes	Yes
Orange	151	Yes	Yes	No	No
Purple	253	Yes	Yes	No	No
Black	-	Yes	Yes	Yes	Yes

3.6 Technical content. The technical content of each volume of the TAB shall be as specified in 3.6.1 through 3.6.6 and shall be arranged as follows:

a. General information (see 3.6.1).
b. List of abbreviations (see 3.6.2).
c. List of symbols (see 3.6.3).
d. System and component designation tables (see 3.6.4).
e. Perspective and plan views (see 3.6.5).
f. System and component diagrams (see 3.6.6).

3.6.1 General information. The general information page(s) shall provide as a minimum the following data:

a. Full title and Government identification numbers of all volumes and separately bound parts of volumes comprising the TAB (including supplements).
b. Explanation of the purpose and scope of the TAB.
c. Explicit applicability of the TAB.
d. A brief synopsis of the content of each volume.
e. A brief description of the graphic techniques used in the TAB.
f. A statement on reporting of errors (see TMDER in MIL-DTL-24784).

3.6.1.1 Use of general information page(s). The general information page(s) shall be included in each volume of the TAB, and shall be identical.

3.6.1.2 Multipart volumes. When multiple parts are used for Volume 1 or Volume 2 (or both) of the TAB, the general information page(s) shall be included only in Part 1 of each volume.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

3.6.2 List of abbreviations. A complete listing of abbreviations and their meaning shall be included in each volume immediately following the general information page(s). For multipart volumes, the list of abbreviations shall appear in Part 1 only.

3.6.2.1 Nonstandard abbreviations. The use of nonstandard abbreviations shall be held to a minimum. Nonstandard abbreviations shall be used only when no authorized equivalent exists in MIL-STD-12. When used, nonstandard abbreviations shall not be in conflict with a MIL-STD-12 abbreviation.

3.6.3 List of symbols. A list of symbols shall be included in each volume (Part 1 only, on multipart volumes) of the TAB, immediately following the list of abbreviations. The listing for each volume shall be limited to symbols used in the applicable volume but shall be inclusive of all symbols used therein.

3.6.3.1 Symbols. Graphic symbols for use on TAB diagrams shall be in accordance with the following:

a. Electrical and electronic - IEEE 315.
b. Plumbing - ANSI Y32.4.
c. Fluid power - ANSI Y32.10.
d. Piping - ASTM F1000.

3.6.3.1.1 Nonstandard symbols. The use of nonstandard symbols shall be held to a minimum. Nonstandard symbols shall be used only when no authorized equivalent exists in the documents specified above. Where nonstandard symbols are used, explanations shall be provided. When used, nonstandard symbols shall not be in conflict with the above documents.

3.6.4 System and component designation tables. Data shall be included in tabular form to explain the use of color codes, piping system designators, location identification numbers for controls and instruments, switchboard and circuit breaker identifications, and so forth, and shall be arranged in logical order immediately following the list of symbols. Any other data that will enable users to better understand the TAB shall be presented in additional tables or by suitable notes positioned near the system or component illustrations to which they apply.

3.6.5 Perspective and plan views. Perspective and plan views (see figure 10-5) shall be included in the TAB to illustrate such specific aspects of the ship as:

a. Antenna and mast arrangements.
b. Exterior installations including superstructure details and cavity drain systems.
c. Compartment and access arrangements.
d. Arrangement of tanks.
e. Electrical generator location and numbering.
f. Bulkheads (pressure).
g. Hull and hull openings.
h. Tanks and compartments (volumes).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

3.6.6 System and component diagrams. Each installed system (piping, electrical, and electronic) shall be illustrated through the use of functional schematic diagrams (see figures 10-6 and 10-7). Where essential to the understanding of system operation, components of the system shall be separately illustrated and may be depicted using other types of drawings such as perspective, orthographic projection, cross-section, or isometric projection. Text shall be restricted to safety precautions and shall only be used to provide instructions or explanations which cannot be covered adequately by annotating the illustrations. Systems which shall be covered include, but are not limited to the following categories:

a. High pressure air systems.
b. Low pressure air systems.
c. Ventilation systems.
d. Gas (refrigerants, oxygen, compressed gasses, and so forth) distribution systems.
e. Water (potable, sea water, air conditioning, chilled water for electronic system cooling, waste, drain, and so forth) systems.
f. Hydraulic systems.
g. Electric power [60 hertz (Hz) and 400 Hz, alternating current (ac), 250 volts direct current (Vdc), and battery] generation and distribution systems.
h. Interior communication (IC) systems.
i. Fire alarm, firefighting, and damage control systems.
j. Steam systems.
k. Feed and condensate systems.
l. Distilling plant systems.
m. Fuel and lube oil systems.
n. Those systems presently covered by the engine room fluid systems composite.
o. Salvage systems.
p. Oxygen generator, CO_2 scrubber, CO-H_2 burner.
q. Electronic equipment cooling flow.
r. Escape systems.

3.6.6.1 Specific examples. Specific examples of system and component diagrams to be included are presented below. Note that the generic categories and titles under which the examples have been placed are neither exclusive nor all-encompassing.

VOLUME I - PIPING

Air Conditioning and Ventilation:

Air Conditioning Chilled Water System
Refrigerant 11 Air Conditioning Plant
Ventilation and Air Conditioning Control System
Ventilation System
Ventilation Flow Diagram

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

Atmosphere Systems and Components:

Atmosphere Analyzing System
CO_2 Removal System
CO-H_2 Burner
Lithium Bromide Absorption System
Main Oxygen System
Oxygen Generator System

Compressed Air Systems and Components:

High Pressure Air System
HP Air System Air Dryer
HP Air Compressor Condensate Drain
700 lb/in^2 Service Air System
100 and 150 lb/in^2 Service Air Systems
20 lb/in^2 Service Air System
Diesel Engine Air Start

Emergency Systems:

Air Salvage System
Emergency Air Breathing System
Forward and After Escape Trunks

Fuel Oil Systems:

Diesel Generator Fuel System
Fuel and Compensating Water System
Fuel Filter Separator

Fresh Water Systems and Components:

Fresh Water Drain Collecting System
Plumbing System
Potable Water System
3000 Gallons per Day Distilling System
1800 Gallons per Day Distilling System
Auxiliary Fresh Water Cooling System
Diesel Generator Fresh Water Cooling System

Hydraulic Systems and Components:

Hydraulic Power Plant
Main and Vital Hydraulic System

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

External Hydraulic System
Snorkel Mast Hydraulic Operation
Periscope Hydraulic Operation
Antenna Masts Hydraulic Operation
Hydraulic Accumulator Indicators
Steering Hydraulic System
Fairwater Planes Hydraulic System
Stern Planes Hydraulic System
Windlass and Capstan Hydraulic Operation
Steering and Diving Control Station

Lube Oil Systems and Components:

Diesel Generator Lub Oil System
Main Lub Oil System
Shaft Lube Oil System
SSTG Lube Oil System
Turbine Lube Oil Fill, Transfer, and Purification System

MBT Systems and Components:

MBT Flooding and Venting
MBT HP Blow System
MBT HP Blow Valves
MBT LP Blow System

Sea Water Systems and Components:

Main Sea Water Cooling System
Main and Auxiliary Sea Water Hull and Backup Valve Operation
Auxiliary Sea Water Cooling System
Air Conditioning Sea Water Cooling System
Diesel Generator Sea Water Cooling System
Drain System
Auxiliary Drain System
Gravity Drains
Surge Tank Arrangement

Snorkel System:

Snorkel System and Panels
Inboard and Outboard Induction and Ventilation Exhaust Valves
Induction Head Valve
Inboard and Outboard Diesel Exhaust Valves

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

Steam Systems and Components:

Auxiliary Steam System
Gland Seal and Exhaust Systems
High Pressure Steam Drain System
Steam Generator Cutout Valve Operation
Main Steam Root Valve and Crossover Valve Operation

Trim System and Components:

Trim System Suction and Discharge Valves
Trim System - Forward and Aft
Hovering and Depth Control System

Miscellaneous Systems and Components:

Battery Electrolyte Agitation System
Clutch Control System
Depth Gage Piping
Floating Wire Antenna Operating Gear
Forward and After Signal Ejectors
Mode Selector Switch
Propulsion Turbine Throttle Valve and Governor Operation
Refrigeration System
SSTG Throttle Valve and Governor Operation
Torpedo Loading, Stowage and Handling
Torpedo Firing Sequence
Torpedo Tube Hydraulic System
Torpedo Tube Flood and Drain System
Trash Disposal Unit
Trash Disposal Compactor
Vibration Reducer Control System

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

VOLUME II - ELECTRIC - ELECTRONICS

Electric Propulsion:

- Electric Propulsion Motor Control
- Propulsion Clutch and Hydraulic Pump Control
- Secondary Propulsion Motor Control
- Storage Battery - Cell Arrangement and Metering

Electric Power Generation and Control:

- Electric Power Sources and Major Circuit Breakers
- Motor Generator Sets Operating Controls
- Ship Service Turbine Generator Sets Operating Controls
- Diesel Generator Control
- Electric Power Generation Block Diagram
- 400 Hz Motor Generator Sets Control
- Synchronizing Scheme Diagram
- Electric Plant Circuit Breakers Control
- Ground Detection

Electric Power Distribution and Lighting:

- Ship Service 400 Hz Power Distribution
- Outboard Lighting
- Ship Service Lighting Power Distribution
- Emergency Lighting Power Distribution

Electrical Auxiliaries:

- Lube Oil and Fuel Oil Equipment
- Auxiliary Sea Water Cooling Pumps Equipment
- Main Sea Water Cooling Pumps Equipment
- Auxiliary Fresh Water Cooling Pumps Equipment
- Main Feed Pumps Equipment
- Main Condensate Pumps Equipment
- Ventilation and Heating Equipment
- Air Conditioning Equipment
- High Pressure Air Compressor and Low Pressure Blower Equipment
- Trim and Drain Pumps and Submersible Pumps Equipment
- Hydraulic Power Plant Equipment
- Distilling Equipment
- Atmosphere Analyzer System
- Hydrocarbon Analyzer System
- Air Sampling and Analysis Equipment
- Atmosphere Cleansing and Replenishment Equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

Galley and Laundry Equipment
Refrigeration Equipment

Interior Communications:

Main Ballast Tank Vent Valves Indicators and Control System
Ballast Control Panel
Ballast Control Panel Common Alarm Circuits
Depth and Course Control System
Hovering and Depth Control System
Ship Control Panel
Pressure Indicating System
Snorkel System
Hull Opening Indicator and Control System
Trim and Drain Indicator and Control System
High Pressure Air Indicator and Control System
Electronic Mast Position and Hoist Control System
Remote Tank Level Indicator System
Trim and Drain Pump Remote Flow Indicator System
Refrigeration Temperature Indicator System
Hydraulic Accumulator Contents Indicator System
Rudder, Fairwater and Stern Planes Angle Indicator System
Depth Indicator System
Ship Safety Alarm System
Dead Reckoning System
Maneuvering Room Panel Common Alarm Circuits
Reactor Compartment Bilge Liquid Level Indicator and Alarm System
Propeller Shaft Revolution Indicator System
Engine Order and Wrong Direction Indicator System
Battery Electrolyte Agitation System
Battery Air Flow Indicator System
Hydrogen Detector System
Gyrocompass Repeater and Gyrocompass System
Underwater Log and Dummy Log System
Ships Angle Indicator System
Trim Angle Indicator System
Main and Auxiliary Sea Water System Status Panel
Sea Water Valve Control and Position Indicator System
Salinity Indicator System
Temperature Monitoring System
Electronic Equipment Cooling Water Temperature and Flow
Monitoring System
Propeller Shaft IC Circuit
Diesel Generator IC Circuit
Integrated Announcing System

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

Officer Call System
Dial Telephone System
Sound Powered Telephone System

Steam Plant:

Steam Plant Valve Position Indicator System
Steam Plant Alarms

Electronic Systems:

Hz Electronics Power Distribution
Hz Electronics Power Distribution
ECM Systems
Radar Systems:
- Surface Search
- Air Search
- Tracking
- IFF

Radio Systems:
- Communications
- Tactical
- LORAN
- SatNav
- RDF

Sonar Systems:
- Receiving
- Detecting Ranging
- Depth Sounding
- Distress Alert
- Underwater Telephone
- Tracking - Speed
- Hydrophone and Transducer Arrangement

4. VERIFICATION

4.1 Quality assurance provisions. The quality assurance requirements for delivery of book plans, review draft copies, preliminary technical manuals, final reproducible copy, technical manuals, replenishment materials, changes and revisions shall be in accordance with MIL-DTL-24784.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging.
For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but it is not mandatory.)

6.1 Intended use. TABs prepared in accordance with this specification are primarily intended as a training aid for use by the ship crews in studying the installed systems of the ship. The TAB is also intended to be used as a reference document by engineering and technical personnel.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification (or any TMCR referencing this specification).
b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1 and 2.3).
c. Type and quantity of deliverable products (see 3.3).
d. When FRC developed other than as specified in MIL-DTL-24784 (see 3.3.1).
e. Typography, if other than specified (see 3.3.1.2).
f. Page size (see 3.3.1.5).
g. Arrangement other than standardized format (see 3.4).
h. Indicate format items, if other than specified (see 3.5).
i. Color in illustrations, if other than specified (see 3.5.7 and MIL-DTL-24784).
j. Packaging requirements (see 5.1).

6.2.1 Distribution statement. A statement will be provided by the Government defining the conditions of availability for distribution, release, or disclosure of the data contained in the TAB. This statement must be included on the cover and title page in the appropriate location.

6.2.2 Page size. Only when the increased cost of production can be justified by the effectiveness of the page layout will the alternate page size of 4-1/4 by 11 inches be specified. When this alternate is specified, the acquisition documents must prohibit the use of foldouts and foldups (see 3.3.1.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

6.3 Definitions. The words or phrases used throughout this specification are defined in MIL-DTL-24784.

6.4 Subject term (key word) listing.

Equipment
Pictorial

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.




FIGURE 10-1. Page size and format.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.




FIGURE 10-2. Single illustration page layout and dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.





FIGURE 10-3. Double illustration page layout and dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.



NOTE

PIPE SIZING IS SUBJECT TO VARY, AS IT IS DEVELOPED FROM THE PIPE SIZES THAT ARE INDICATED ON THE SYSTEM DIAGRAM BEING USED.

FIGURE 10-4. Recommended pipe size scale.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.




FIGURE 10-5. Perspective and plan views. (Sample)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.




FIGURE 10-6. Functional schematic diagram. (Sample)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.




FIGURE 10-7. Functional schematic diagram, 2-page spread. (Sample)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

Custodian:
Navy - SH

Review Activity:
Navy - EC

Preparing activity:
Navy - SH
(Project TMSS-N319)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4,5,6, and 7 and send to preparing activity.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-DTL-24784/10B (SH)	2. DOCUMENT DATE *(YYYYMMDD)* 15 February 2002

3. DOCUMENT TITLE
TRAINING AID BOOKLET (TAB) REQUIREMENTS FOR NAVAL SHIPS SYSTEMS

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(if applicable)*	7. DATE SUBMITTED *(YYYYMMDD)*

8. PREPARING ACTIVITY

a. NAME SEA 05Q	b. TELEPHONE *(Include Area Code)* (1) Commercial (202) 781-3726 (2) DSN
c. ADDRESS *(Include Zip Code)* Commander, Naval Sea Systems Command ATTN: SEA 05Q, 1333 Isaac Hull Ave SE Stop 5160, Washington Navy Yard DC 20376-5160	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman Road, Suite 2533, Fort Belvoir, VA 22060-6221 Telephone (703) 767-6888 DSN 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:23Z
Check the source to verify that this is the current version before use.